

Appendix 3 – Noise Monitoring Reports

Noise Monitoring Report – Q1 2023

Noise Monitoring Report – Q2 2023

Noise Monitoring Report – Q3 2023

Noise Monitoring Report – Q4 2023

Page
67 of 399



Karuah East Quarry

Quarterly Attended Noise Monitoring - Q1 2023

Prepared for Karuah East Quarry Pty Limited

March 2023

Karuah East Quarry

Quarterly Attended Noise Monitoring - Q1 2023

Karuah East Quarry Pty Limited

E230083 RP1

March 2023

Version	Date	Prepared by	Reviewed by	Comments
1	17 February 2023	Lucas Adamson	Najah Ishac	Draft
2	3 March 2023	Lucas Adamson	Najah Ishac	Final

Approved by

Najabiliac

Najah Ishac Director 3 March 2023

Level 3 175 Scott Street Newcastle NSW 2300

This report has been prepared in accordance with the brief provided by Karuah East Quarry Pty Limited and, in its preparation, EMM has relied upon the information collected at the times and under the conditions specified in this report. All findings, conclusions or recommendations contained in this report are based on those aforementioned circumstances. The contents of this report are private and confidential. This report is only for Karuah East Quarry Pty Limited's use in accordance with its agreement with EMM and is not to be relied on by or made available to any other party without EMM's prior written consent. Except as permitted by the *Copyright Act 1968* (Cth) and only to the extent incapable of exclusion, any other use (including use or reproduction of this report for resale or other commercial purposes) is prohibited without EMM's prior written consent. Except where expressly agreed to by EMM in writing, and to the extent permitted by law, EMM will have no liability (and assumes no duty of care) to any person in relation to this document, other than to Karuah East Quarry Pty Limited (and subject to the terms of EMM's agreement with Karuah East Quarry Pty Limited).

© EMM Consulting Pty Ltd, Ground Floor Suite 01, 20 Chandos Street, St Leonards NSW 2065, March 2023.

TABLE OF CONTENTS

1	Intro	duction	1
	1.1	Background	1
	1.2	Attended monitoring locations	1
	1.3	Terminology and abbreviations	3
2	Noise	e limits	4
	2.1	Project approval	4
	2.2	Environment protection licence	4
	2.3	Noise management plan	4
	2.4	Noise limits	4
	2.5	Meteorological conditions	4
	2.6	Additional requirements	5
3	Meth	odology	6
	3.1	Overview	6
	3.2	Attended noise monitoring	6
	3.3	Meteorological data	6
	3.4	Modifying factors	7
	3.5	Instrumentation	7
4	Resul	ts	8
	4.1	Total measured noise levels and atmospheric conditions	8
	4.2	Site only noise levels	9
5	Sumr	nary	12

Appendices

Appendix A	Noise perception and examples	A.1
Appendix B	Regulator documents	B.1
Appendix C	Calibration certificates	C.1

Tables

Table 1.1	Attended noise monitoring locations	1
Table 1.2	Terminology and abbreviations	3
Table 2.1	Noise impact limits, dB	4
Table 3.1	Attended noise monitoring equipment	7
Table 4.1	Measured noise levels – Q1 2023 ¹	8

Table 4.2	Measured atmospheric conditions – Q1 2023	9
Table 4.3	Site noise levels and limits – Q1 2023	10
Table A.1	Perceived change in noise	A.2
Figures		
Figure 1.1	Attended noise monitoring locations	2
Figure A.1	Common noise levels	A.2

1 Introduction

1.1 Background

EMM Consulting Pty Ltd (EMM) was engaged by Karuah East Quarry Pty Limited to conduct a quarterly noise survey of operations at Karuah East Quarry (KEQ, the site) located at Blue Rock Close, Karuah NSW. The survey is needed to quantify the acoustic environment and used to compare site noise levels against specified limits.

Attended environmental noise monitoring described in this report was done during morning shoulder, day and evening periods on Tuesday 7 and Wednesday 8 February 2023 at five monitoring locations.


1.2 Attended monitoring locations

Site monitoring locations are detailed in Table 1.1 and shown on Figure 1.1. It should be noted that Figure 1.1 shows actual monitoring positions, not necessarily the location of residences.

Table 1.1 Attended noise monitoring locations

Location	Description/address	Coordinates (MGA56)		
descriptor/ID		Easting	Northing	
А	Private Residence - 74 Mill Hill Close, Karuah	406623	6388704	
В	Private Residence - 64 Mill Hill Close, Karuah	406405	6388859	
F	Private Residence - 1714 The Branch Lane, Karuah	405639	6389782	
G	Private Residence - 2 Halloran Road, North Arm Cove	405629	6389766	
Н	Private Residence - 21 Halloran Road, North Arm Cove	407795	6389868	





KEY

- Site boundary
- A ttended noise monitoring location
- Approved disturbance area
- - Minor road
 - Vehicular track
- Cadastral boundary
- Waterbody
- NPWS reserve
- State forest

Attended noise monitoring locations

Karuah East Quarry Quarterly attended noise monitoring Figure 1.1



1.3 Terminology and abbreviations

Some definitions of terms and abbreviations which may be used in this report are provided in Table 1.2.

Table 1.2 Terminology and abbreviations

Term/descriptor	Definition
dB(A)	Noise level measurement units are decibels (dB). The "A" weighting scale is used to approximate how humans hear noise.
L _{Amax}	The maximum root mean squared A-weighted noise level over a time period.
L _{A1}	The A-weighted noise level which is exceeded for 1 per cent of the time.
LA1,1minute	The A-weighted noise level which is exceeded for 1 per cent of the specified time period of 1 minute.
LA10	The A-weighted noise level which is exceeded for 10 percent of the time.
LAeq	The energy average A-weighted noise level.
LA50	The A-weighted noise level which is exceeded for 50 per cent of the time, also the median noise level during a measurement period.
La90	The A-weighted noise level exceeded for 90 percent of the time, also referred to as the "background" noise level and commonly used to derive noise limits.
LAmin	The minimum A-weighted noise level over a time period.
LCeq	The energy average C-weighted noise energy during a measurement period. The "C" weighting scale is used to take into account low-frequency components of noise within the audibility range of humans.
SPL	Sound pressure level. Fluctuations in pressure measured as 10 times a logarithmic scale, with the reference pressure being 20 micropascals.
Hertz (Hz)	The frequency of fluctuations in pressure, measured in cycles per second. Most sounds are a combination of many frequencies together.
AWS	Automatic weather station used to collect meteorological data, typically at an altitude of 10 metres
VTG	Vertical temperature gradient in degrees Celsius per 100 metres altitude.
Sigma-theta	The standard deviation of the horizontal wind direction over a period of time.
ΙΑ	Inaudible. When site noise is noted as IA then there was no site noise at the monitoring location.
NM	Not Measurable. If site noise is noted as NM, this means some noise was audible but could not be quantified.
Day	Monday – Saturday: 7 am to 6 pm, on Sundays and Public Holidays: 8 am to 6 pm.
Evening	Monday – Saturday: 6 pm to 10 pm, on Sundays and Public Holidays: 6 pm to 10 pm.
Night	Monday – Saturday: 10 pm to 7 am, on Sundays and Public Holidays: 10 pm to 8 am.

Appendix A provides further information that gives an indication as to how an average person perceives changes in noise level, and examples of common noise levels.

2 Noise limits

2.1 Project approval

Karuah East Quarry noise limits are detailed in Condition 3 of Project Approval (PA) 09_0175. Relevant sections of PA 09_0175 are reproduced in Appendix B.1.

2.2 Environment protection licence

Karuah East Quarry noise limits are detailed in Condition L4.1 of Environment Protection Licence (EPL) 20611. Relevant sections of EPL 20611 are reproduced in Appendix B.2.

2.3 Noise management plan

The approved Noise Management Plan (NMP) adopts five attended noise monitoring locations that are representative of residences outlined in PA 09_0175 and EPL 20611. Relevant sections of the NMP are reproduced in Appendix B.3.

2.4 Noise limits

Noise impact limits based on PA 09_0175 and EPL 20611 are as shown in Table 2.1.

Table 2.1Noise impact limits, dB

Location	Day L _{Aeq,15} minute	Evening L _{Aeq,15} minute		
A	42	40	35	52
В	40	40	35	52
F	40	35	35	52
G	43	39	35	52
Н	44	46	35	52

Notes: 1. Morning shoulder period is from 5:00 am to 7:00 am.

2.5 Meteorological conditions

PA 09_0175 specifies that noise generated by the project is to be measured in accordance with the relevant requirements, and exemptions (including certain meteorological conditions), of the NSW Noise Policy for Industry. Similarly, the requirements of Condition L4.3 of EPL 20611 state that noise limits do not apply under the following meteorological conditions:

- wind speeds greater than 3 m/s at 10 m above ground level;
- stability category F temperature inversion conditions and wind speeds greater than 2 m/s at 10 m above ground level; or
- stability category G temperature inversion conditions.

2.6 Additional requirements

Monitoring and reporting have been done in accordance with the NSW EPA 'Noise Policy for Industry' (NPfI) issued in October 2017 and the 'Approved methods for the measurement and analysis of environmental noise in NSW' (Approved Methods) issued in January 2022.

3 Methodology

3.1 Overview

Attended environmental noise monitoring was done in general accordance with Australian Standard AS1055 'Acoustics, Description and Measurement of Environmental Noise' and relevant EPA requirements. Meteorological data was obtained from the KEQ on-site meteorological station which allowed correlation of atmospheric parameters with measured noise levels.

3.2 Attended noise monitoring

During this survey, attended noise monitoring was conducted during the morning shoulder, day and evening periods at each location. The duration of each measurement was 15 minutes. Atmospheric conditions were measured at each monitoring location.

Measured sound levels from various sources were noted during each measurement, and particular attention was paid to the extent of site's contribution (if any) to measured levels. At each monitoring location, the site-only $L_{Aeq,15minute}$ and L_{Amax} were measured directly or determined by other methods detailed in Section 7.1 of the NPfI.

If the exact noise levels from site could not be established due to masking by other noise sources in a similar frequency range, but site noise was determined to be at least 5 dB lower than relevant limits, then a maximum estimate of site noise may be provided. This is expressed as a 'less than' quantity, such as <20 dB or <30 dB.

The terms 'Inaudible' (IA) or 'Not Measurable' (NM) may be used in this report. When site noise is noted as IA, no site noise was audible at the monitoring location. When site noise is noted as NM, this means site noise was audible but could not be quantified. All results noted as NM in this report were due to one or more of the following:

- Site noise levels were extremely low and unlikely, in many cases, to be noticed.
- Site noise levels were masked by other more dominant noise sources that are characteristic of the environment, such as breeze in foliage or continuous road traffic noise, that cannot be eliminated by monitoring at an alternate or intermediate location.
- It was not feasible or reasonable to employ methods such as to move closer and back calculate. Cases may include rough terrain preventing closer measurement, addition/removal of significant source to receiver shielding caused by moving closer, and meteorological conditions where back calculation may not be accurate.

For this assessment, the measured L_{Amax} has been used as a conservative estimate of $L_{A1,1minute}$. The EPA accepts sleep disturbance analysis based on either the $L_{A1,1minute}$ or L_{Amax} metrics, with the L_{Amax} representing a more conservative assessment of site noise emissions.

3.3 Meteorological data

Meteorological data for the monitoring period was sourced from the Karuah East Quarry on-site meteorological station to determine applicability of criteria in accordance with the EPL and PA.

3.4 Modifying factors

All measurements were evaluated for potential modifying factors in accordance with the NPfI. Assessment of modifying factors is undertaken at the time of measurement if the site was audible and directly quantifiable. If applicable, modifying factor penalties have been reported and added to measured site-only L_{Aeq} noise levels.

Low-frequency modifying factor penalties have only been applied to site-only L_{Aeq} levels if the site was the only contributing low-frequency noise source. Specific methodology for assessment of each modifying factor is outlined in Fact Sheet C of the NPfI.

3.5 Instrumentation

Equipment used to measure environmental noise levels is detailed in Table 3.1. Calibration certificates are provided in Appendix C.

Table 3.1 Attended noise monitoring equipment

Item	Serial number	Calibration due date	Relevant standard
Brüel & Kjær 2250 sound level meter	2759405	2/2/2024	IEC 61672-1:2002
Svantek SV-36 calibrator	79952	26/9/2023	IEC 60942

4 **Results**

4.1 Total measured noise levels and atmospheric conditions

Overall noise levels measured at each location during attended measurements are provided in Table 4.1.

Location	Start date and time	L _{Amax} dB	L _{A1} dB	L _{A10} dB	L _{Aeq} dB	L _{A50} dB	L _{A90} dB	L _{Amin} dB
А	7/02/2023 5:00	80	76	69	65	58	50	44
В	7/02/2023 5:16	73	70	65	61	59	50	44
F	7/02/2023 5:34	81	61	46	54	43	41	38
G	7/02/2023 5:58	77	60	48	52	46	44	42
Н	7/02/2023 6:15	67	52	46	45	43	42	39
А	7/02/2023 7:00	77	75	70	66	63	54	47
В	7/02/2023 7:16	73	71	66	63	62	58	49
F	7/02/2023 7:34	80	61	51	54	47	44	40
G	7/02/2023 8:18	64	48	40	40	36	34	32
Н	7/02/2023 8:35	66	48	40	39	34	33	31
А	8/02/2023 18:01	78	74	69	66	63	56	47
В	8/02/2023 18:17	77	71	67	63	61	55	49
F	8/02/2023 18:35	69	56	47	47	44	41	38
G	8/02/2023 18:59	63	50	45	43	42	41	38
Н	8/02/2023 19:16	63	48	44	42	42	40	38

Table 4.1Total measured noise levels – Q1 20231

Notes: 1. Levels in this table are not necessarily the result of activity at site.

Atmospheric condition data measured by the operator during each measurement using a hand-held weather meter is shown in Table 4.2. The wind speed, direction and temperature were measured at approximately 1.5 metres above ground. Attended noise monitoring is not done during rain, hail, or wind speeds above 5 m/s at microphone height.

Location	Start date and time	Temperature °C	Wind speed m/s	Wind direction ^o Magnetic north ¹	Cloud cover 1/8s
A	7/02/2023 5:00	19.7	0.3	85	0
В	7/02/2023 5:16	20.1	0.6	85	0
F	7/02/2023 5:34	20.6	0.4	90	0
G	7/02/2023 5:58	20.5	0.3	85	1
Н	7/02/2023 6:15	20.6	0.3	85	1
A	7/02/2023 7:00	22.0	0.6	90	1
В	7/02/2023 7:16	22.2	0.5	85	1
F	7/02/2023 7:34	22.9	0.7	90	0
G	7/02/2023 8:18	23.5	0.7	85	0
н	7/02/2023 8:35	23.8	0.8	90	0
А	8/02/2023 18:01	26.5	1.9	90	0
В	8/02/2023 18:17	25.9	1.5	85	0
F	8/02/2023 18:35	25.3	1.7	90	0
G	8/02/2023 18:59	24.9	1.6	90	0
Н	8/02/2023 19:16	23.9	1.5	85	0

Table 4.2 Measured atmospheric conditions – Q1 2023

Notes: 1. "-" indicates calm conditions at monitoring location.

4.2 Site only noise levels

4.2.1 Modifying factors

There were no modifying factors, as defined in the NPfI, applicable during the survey.

4.2.2 Monitoring results

Table 4.3 provides site noise levels in the absence of other sources, where possible, and includes weather data obtained from the site's AWS. Limits are applicable if weather conditions were within specified parameters during each measurement.

Table 4.3Site noise levels and limits – Q1 2023

Location	Start Date and Time (Period)	Wi	nd	Stability Class	Limits apply? ¹	Limit, dB		Site level, dB ²		Exceedance, dB	
		Speed m/s	Direction ⁴			L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}
А	7/02/2023 5:00 (MS)	1.1	101	F	Y	35	52	IA	IA	No	No
В	7/02/2023 5:16 (MS)	1.0	127	F	Y	35	52	IA	IA	No	No
F	7/02/2023 5:34 (MS)	1.2	97	F	Y	35	52	IA	IA	No	No
G	7/02/2023 5:58 (MS)	0.9	123	F	Y	35	52	IA	IA	No	No
Н	7/02/2023 6:15 (MS)	0.8	111	F	Y	35	52	IA	IA	No	No
A	7/02/2023 7:00 (D)	0.7	145	А	Y	42	N/A	IA	N/A	No	N/A
В	7/02/2023 7:16 (D)	0.6	133	А	Y	40	N/A	IA	N/A	No	N/A
F	7/02/2023 7:34 (D)	0.4	101	А	Y	40	N/A	IA	N/A	No	N/A
G	7/02/2023 8:18 (D)	1.1	118	А	Y	43	N/A	<30	N/A	No	N/A
Н	7/02/2023 8:35 (D)	1.3	114	А	Y	44	N/A	<30	N/A	No	N/A

Table 4.3Site noise levels and limits – Q1 2023

Location	Start Date and Time (Period)	Wi	nd	Stability Class	Limits apply? ¹	Limit, dB		Site level, dB ²		Exceedan	ce, dB
		Speed m/s	Direction ⁴			L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}
А	8/02/2023 18:01 (E)	3.6	144	D	Ν	40	N/A	IA	N/A	No	N/A
В	8/02/2023 18:17 (E)	2.9	141	E	Υ	40	N/A	IA	N/A	No	N/A
F	8/02/2023 18:35 (E)	2.9	135	E	Y	35	N/A	IA	N/A	No	N/A
G	8/02/2023 18:59 (E)	1.8	135	F	Y	39	N/A	IA	N/A	No	N/A
Н	8/02/2023 19:16 (E)	1.8	154	F	Υ	46	N/A	IA	N/A	No	N/A

Notes: 1. Noise emission limits do not apply during periods of rainfall or winds greater than 3 metres per second (at a height of 10 metres).
 2. Site-only LAeq,15minute, includes modifying factor penalties if applicable.

3. NA in exceedance column means criterion was not applicable due to atmospheric conditions outside those specified in project approval.

4. Degrees magnetic north, "-" indicates calm conditions.

5. MS = Morning Shoulder period; D = Day period; E = Evening period.

5 Summary

EMM Consulting Pty Ltd (EMM) was engaged by Karuah East Quarry Pty Limited to conduct a quarterly noise survey of operations at the site. The survey purpose was to quantify the acoustic environment and compare site noise levels against specified PA and EPL noise limits.

Attended environmental noise monitoring described in this report was done during the morning shoulder, day and evening periods on Tuesday 7 and Wednesday 8 February 2023 at five monitoring locations.

Noise levels from site complied with relevant limits at all monitoring locations during the Q1 2023 survey.

Appendix A

Noise perception and examples




A.1 Noise levels

Table A.1 gives an indication as to how an average person perceives changes in noise level. Examples of common noise levels are provided in Figure A.1.

Table A.1Perceived change in noise

Change in sound pressure level (dB)	Perceived change in noise
up to 2	Not perceptible
3	Just perceptible
5	Noticeable difference
10	Twice (or half) as loud
15	Large change
20	Four times (or quarter) as loud





Appendix B Regulator documents



B.1 Project approval

SCHEDULE 3 ENVIRONMENTAL PERFORMANCE CONDITIONS

IDENTIFICATION OF APPROVED LIMITS OF EXTRACTION

- 1. The Applicant shall, prior to carrying out quarrying operations on the site:
 - (a) engage a registered surveyor to mark out the boundaries of the approved limits of extraction within the Extraction Area; and
 - (b) submit a survey plan of the extraction boundaries,
 - to the satisfaction of the Planning Secretary.
- 2. The Applicant must ensure that the extraction boundaries are clearly marked at all times while quarrying operations are being carried out, in a manner that allows the limits of extraction to be clearly identified.

NOISE

Operational Noise Criteria

3. Except for the carrying out of construction works, the Applicant must ensure that the operational noise generated by the development does not exceed the criteria in Table 2 at any residence^a on privately-owned land.

Noise Assessment Location ^a	Morning Shoulder LAeq (15 min)	Morning Shoulder L _{Amax}	Day L _{Aeq (15 min)}	Evening L _{Aeq (15 min)}
А	35	52	42	40
В	35	52	40	40
G	35	52	43	39
Н	35	52	44	46
I	35	52	40	37
All other residences	35	52	40	35

Table 2: Operational noise criteria dB

^a Noise Assessment Locations referred to in Table 2 are shown in Appendix 2.

Noise generated by the development must be monitored and measured in accordance with the relevant procedures and modifications (including certain meteorological conditions) of the NPfI.

3A. The noise criteria in Table 2 do not apply if the Applicant has an agreement with the owner/s of the relevant residence or land to exceed the noise criteria, and the Applicant has advised the Department in writing of the terms of this agreement.

Road Traffic Noise Criteria

4. The Applicant must take all reasonable and feasible measures to ensure that the traffic noise generated by the development does not cause additional exceedances of the criteria in Table 3 at any residence on privately-owned land.

Table 3: Road traffic noise criteria

Road	Criteria (Dayª)
Pacific Highway	60 dB(A) LAeq (15 hour)
Local roads	55 dB(A) LAeq (1 hour)

^a Day is the period from 7 am to 10 pm every day in accordance with the EPA's NSW Road Noise Policy (2011).

5. Deleted

Noise Operating Conditions

- 6. The Applicant must:
 - (a) take all reasonable steps to minimise noise from construction and operational activities, including low frequency noise and other audible characteristics, associated with the development;
 - (b) implement reasonable and feasible noise attenuation measures on all plant and equipment that will operate in noise sensitive areas;
 - (c) operate a comprehensive noise management system commensurate with the risk of impact;
 - (d) take all reasonable steps to minimise the noise impacts of the development during noiseenhancing meteorological conditions when the noise criteria in this consent do not apply (see NPfI);
 - (e) carry out quarterly attended noise monitoring (unless otherwise agreed by the Planning Secretary) to determine whether the development is complying with the relevant conditions of this consent; and
 - (f) regularly assess the noise monitoring data and modify or stop operations on the site to ensure compliance with the relevant conditions of this consent.

Noise Management Plan

- 7. The Applicant must prepare a Noise Management Plan for the development to the satisfaction of the Planning Secretary. This plan must:
 - (a) be prepared by a suitably qualified and experienced person/s whose appointment has been endorsed by the Planning Secretary;
 - (b) be prepared in consultation with the EPA;
 - (c) describe the measures to be implemented to ensure:
 - (i) compliance with the noise criteria and operating conditions in this consent;
 - (ii) best practice management is being employed;
 - (iii) noise impacts of the development are minimised during noise-enhancing meteorological conditions when the noise criteria in this consent do not apply (see NPfI);
 - (d) describe the noise management system in detail; and
 - (e) include a monitoring program that:
 - (i) is capable of evaluating the performance of the development;
 - (ii) monitors noise at the nearest and/or most affected residences;
 - (iii) adequately supports the noise management system;
 - (iv) includes a protocol for distinguishing noise emissions of the development from any neighbouring developments; and
 - includes a protocol for identifying any noise-related exceedance, incident or noncompliance and for notifying the Department and relevant stakeholders of any such event.
- 7A. The Applicant must implement the plan as approved by the Planning Secretary.

BLASTING

Blasting Criteria

8. The Applicant must ensure that blasting on the site does not cause exceedances of the criteria in Table 5.

B.2 Environmental protection licence

Licence - 20611

L3 Waste

L3.1 The licensee must not cause, permit or allow any waste generated outside the premises to be received at the premises for storage, treatment, processing, reprocessing or disposal or any waste generated at the premises to be disposed of at the premises, except as expressly permitted by the licence.

L4 Noise limits

L4.1 Noise generated at the premises must not exceed the noise limits in the table below. The locations referred to in the table below are indicated in Table 2: Operational Noise Criteria, and Figure 1 of the document titled Project Approval 09_0175 Modification 9 (MOD 9) Department of Planning, Industry& Environment - which has been filed on EPA file Doc22/715570-1.

Noise Assesment Location	Morning Shoulder LAeq(15 min)	Morning shoulder LAmax	Day LAeq (15 min)	Evening LAeq (15 min)
A (74 Mill Hill Close, Karuah, Lot 100 DP 1028885)	35	52	42	40
B (64 Mill Hill Close, Karuah, Lot 3 DP785172)	35	52	40	40
G (2 Halloran Road, North Arm Cove Lot 1 DP1032636)	35	52	43	39
H (21 Halloran Road, North Arm Cove Lot 10 DP1032636)	35	52	44	46
l (83 Halloran Road, North Arm Cove Lot 12 DP1032636)	35	52	40	37
All other residences	35	52	40	35

L4.2 Noise limit definitions - For the purpose of the table at L4.1, the following definitions apply: Day is defined as the period from 7am to 6pm Monday to Saturday and 8am to 6pm Sunday and Public Holidays;

Morning Shoulder is defined as the period from 5:00am to 7:00am Monday to Saturday; Evening is defined as the period from 6:00pm to 10:00pm Monday to Saturday.

- L4.3 The noise limits set out in this licence apply under all meteorological conditions except for the following:
 - a) Wind speed greater than 3 metres/second at 10 metres above ground level; or

b) Stability category F temperature inversion conditions and wind speeds greater than 2 metres/second at 10 metres above ground level; or

NSU Manual in the second second

Licence - 20611

c) Stability category G temperature inversion conditions.

L4.4 Determining Compliance

To determine compliance with the noise limits set out in the table above, the licensee must locate monitoring equipment:

a) within 30 metres of a dwelling façade (but not closer than 3 metres) where any dwelling on the property is situated more than 30 metres from the property boundary that is closest to the premises;

b) approximately on the boundary where any dwelling is situated 30 metres or less from the property boundary that is closest to the premises;

c) at the most affected point at a location where there is no dwelling at the location; and

d) within approximately 50 metres of the boundary of a national park or nature reserve.

Note: A non-compliance of the Noise Limits table will still occur where noise generated from the premises in excess of the appropriate limit is measured:

i) at a location other than an area prescribed in part (a) and part (b); and/or

ii) at a point other than the most affected point at a location.

L4.5 For the purposes of determining the noise generated at the premises the modification factors in Fact Sheet C of the EPA's "Noise Policy for Industry" must be applied, as appropriate, to the noise levels measured by the noise monitoring equipment.

L5 Blasting

- L5.1 Blasting in or on the premises must only be carried out between the hours of 9:00 am and 4:00 pm Monday to Friday. No blasting is permitted on Saturdays, Sundays or public holidays. Blasting outside of the hours specified in this condition can only take place with the written approval of the EPA.
- L5.2 Blasting is not permitted simultaneously with adjacent quarry(s).
- L5.3 The airblast overpressure level from blasting operations in or on the premises must not exceed:
 a) 115 dB (Lin Peak) for more than 5% of the total number of blasts during each reporting period; and
 b) 120 dB (Lin Peak) at any time,
 at monitoring point 11 detailed in Condition P1.4.
- L5.4 The ground vibration peak particle velocity from blasting operations carried out in or on the premises must not exceed:

a) 5 mm/second for more than 5% of the total number of blasts during each reporting period; and

b) 10 mm/second at any time,

at monitoring point 11 detailed in Condition P1.4.

- L5.5 Error margins associated with any monitoring equipment used to measure airblast overpressure or peak particle velocity are not to be taken into account in determing whether or not the limit has been exceeded.
- L5.6 The airblast overpressure and ground vibration levels in the conditions above do not apply at noise sensitive locations that are owned by the licensee or subject to a private agreement, relating to airblast overpressure and ground vibration levels, between the licensee and land owner.

USN SURVEY



Licence - 20611

a) the date and time of the complaint;

b) the method by which the complaint was made;

c) any personal details of the complainant which were provided by the complainant or, if no such details were provided, a note to that effect;

d) the nature of the complaint;

e) the action taken by the licensee in relation to the complaint, including any follow-up contact with the complainant; and

f) if no action was taken by the licensee, the reasons why no action was taken.

- M5.3 The record of a complaint must be kept for at least 4 years after the complaint was made.
- M5.4 The record must be produced to any authorised officer of the EPA who asks to see them.

M6 Telephone complaints line

- M6.1 The licensee must operate during its operating hours a telephone complaints line for the purpose of receiving any complaints from members of the public in relation to activities conducted at the premises or by the vehicle or mobile plant, unless otherwise specified in the licence.
- M6.2 The licensee must notify the public of the complaints line telephone number and the fact that it is a complaints line so that the impacted community knows how to make a complaint.
- M6.3 The preceding two conditions do not apply until 1 month after the date of the issue of this licence.

M7 Blasting

M7.1 To determine complaince with Blast Limit conditions of this licence:

a) Airblast overpressure and ground vibration levels must be measured and electronically recorded for monitoring point 11 for the parameters specified in Column 1 of the table below; and
b) The licensee must use the units of measure, sampling method, and sample at the frequency specified opposite in the other columns.

Parameter	Units of Measure	Frequency	Sampling Method
Airblast Overpressure	Decibels (Linear Peak	All blasts	Australian Standard AS 2187.2-2006
Ground Vibration Peak Particle Velocity	millimetres/second	All blasts	Australian Standard AS 2187.2-2006

M8 Noise monitoring

- M8.1 To assess compliance with the noise limits for this premises attended noise monitoring must be undertaken in accordance with all noise conditions and:
 - a) during a period of normal quarry operations;
 - b) at each one of the locations listed in the noise limits table of this licence;



Licence - 20611

c) occur quarterly in the reporting period;

d) occur during each day period as defined in the NSW Noise Policy for Industry.

Note: Quarterly attended noise monitoring must be completed (unless otherwise agreed by the Planning Secretary) to determine whether the development is complying with the relevant conditions of this consent. The frequency of noise monitoring will be reviewed, upon request.

6 Reporting Conditions

R1 Annual return documents

- R1.1 The licensee must complete and supply to the EPA an Annual Return in the approved form comprising:
 - 1. a Statement of Compliance,
 - 2. a Monitoring and Complaints Summary,
 - 3. a Statement of Compliance Licence Conditions,
 - 4. a Statement of Compliance Load based Fee,
 - 5. a Statement of Compliance Requirement to Prepare Pollution Incident Response Management Plan,
 - 6. a Statement of Compliance Requirement to Publish Pollution Monitoring Data; and
 - 7. a Statement of Compliance Environmental Management Systems and Practices.

At the end of each reporting period, the EPA will provide to the licensee notification that the Annual Return is due.

- R1.2 An Annual Return must be prepared in respect of each reporting period, except as provided below.
- Note: The term "reporting period" is defined in the dictionary at the end of this licence. Do not complete the Annual Return until after the end of the reporting period.
- R1.3 Where this licence is transferred from the licensee to a new licensee:

a) the transferring licensee must prepare an Annual Return for the period commencing on the first day of the reporting period and ending on the date the application for the transfer of the licence to the new licensee is granted; and

b) the new licensee must prepare an Annual Return for the period commencing on the date the application for the transfer of the licence is granted and ending on the last day of the reporting period.

- Note: An application to transfer a licence must be made in the approved form for this purpose.
- R1.4 Where this licence is surrendered by the licensee or revoked by the EPA or Minister, the licensee must prepare an Annual Return in respect of the period commencing on the first day of the reporting period and ending on:

a) in relation to the surrender of a licence - the date when notice in writing of approval of the surrender is given; or

b) in relation to the revocation of the licence - the date from which notice revoking the licence operates.

R1.5 The Annual Return for the reporting period must be supplied to the EPA via eConnect EPA or by registered

B.3 Noise management plan

5 Noise limits

5.1 Operational noise

Condition 3 of Schedule 3 of PA 09_0175 provides the operational noise limits for KEQ. These are reproduced in Table 5.1.

Table 5.1 Operational noise criteria (dB) from Table 2 of PA 09_0175

Noise Assessment Location ¹	Morning Shoulder L _{Aeq(15 minute)}	Morning Shoulder L _{Amax}	Day L _{Aeq(15 minute)}	Evening L _{Aeq(15 minute)}
A	35	52	42	40
В	35	52	40	40
G	35	52	43	39
Н	35	52	44	46
I	35	52	40	37
All other residences	35	52	40	35

Noise assessment locations are shown in Figure 3.1.

Noise generated by the development must be monitored and measured in accordance with the relevant procedures and exemptions (including certain meteorological conditions) of the NPfI (EPA 2017).

The noise limits provided in Table 5.1 apply under standard and noise-enhancing meteorological conditions (as defined in the NPfI) determined by monitoring at the relevant weather station. In accordance with Condition L4.3 of EPL 20611 and consistent with Condition 3 of Schedule 3 of PA 09_0175 the noise limits provided in Table 5.1 apply under all meteorological conditions except for the following:

- wind speeds greater than 3m/s at 10m above ground level;
- stability category F temperature inversion conditions and wind speeds greater then 2m/s at 10m above ground level; or
- stability category G temperature inversion conditions.

In accordance with Fact Sheet D of the NPfI, for 'very noise enhancing meteorological conditions' the applicable noise limit is set at 5dB above those provided in Table 5.1.

Noise limits do not apply if Karuah East has an agreement with the owner/s of the relevant residence or land to exceed the noise criteria, and Karuah East has advised the Department in writing of the terms of this agreement.

5.2 Road traffic noise

Condition 4 of Schedule 3 of PA 09_0175 states that all reasonable and feasible measures must be taken to ensure that the traffic generated by KEQ does not cause additional exceedances of the criteria provided in Table 5.2 at any residence on privately-owned land.

Appendix C Calibration certificates



CERTIFICATE OF CALIBRATION

CERTIFICATE NO: C33872

EQUIPMENT TESTED: Sound Level Calibrator

	e No: wner: med:	L3, 17 Newca Measu	Seria Consulting Pt 5 Scott Stree astle, NSW 23	y Ltd t 300 essure le	79952 vel, Frequency Passed.	& Distortion
Parameter	Pre- Adj	Adj Y/N			Frequency (Hz)	THD&N (%)
Level1:	NA	N	94.09	dB	1000.00 Hz	1.12 %
Level2:	NA	N	114.06	dB	1000.00 Hz	0.71 %
Unce	ertainty	1	±0.11	dB	±0.05%	±0.20 %
Uncertainty (at	95% c.l	.) k=2	enerth Mitchen	E. Mar	al sociation is	CO repairs
CONDITION OF Ambient Pre Temper Relative Hun	essure ature	1004 23	hPa ±1 hPa °C ±1º C % ±5%		ate of Receipt : of Calibration : Date of Issue :	26/09/2022 29/09/2022 29/09/2022
Acu-Vib Procee Checked b	dure:		2 (Calibrators) lethod: AS IEC Authoris Signatu	SED	A	ein Soe

Accredited for compliance with ISO/IEC 17025 - Calibration

Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part. The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.




WORLD RECOGNIBED ACCREDITATION Accredited Lab No. 9262 Acoustic and Vibration Measurements

Head Office & Calibration Laboratory Unit 14, 22 Hudson Ave. Castle Hill NSW 2154 (02) 9680 8133 www.acu-vib.com.au

Acu-Vib Electronics

CALIBRATIONS SALES RENTALS REPAIRS

Page 1 of 2 Calibration Certificate AVCERT02.1 Rev.2.0 14.04.2021



CERTIFICATE NO: SLM31670

EQUIPMENT TESTED: Sound Level Meter

Manufacturer: B&K Type No: 2250 Mic. Type: 4189 Pre-Amp. Type: ZC0032

Serial No: 2759405 Serial No: 2983733 Serial No: 22666

Filter Type: 1/3 Octave

Owner: EMM Consulting Level 3, 175 Scott Street Newcastle, NSW 2300

Tests Performed: IEC 61672-3:2013 & IEC 61260-3:2016

Comments: All Test passed for Class 1. (See overleaf for details) **CONDITIONS OF TEST:**

Ambient Pressure Temperature **Relative Humidity**

992 hPa ±1 hPa 26 °C ±1° C 48 % ±5%

Date of Receipt : 02/02/2022 Date of Calibration: 02/02/2022 Date of Issue : 03/02/2022

Test No: F031671

Acu-Vib Test Procedure: AVP10 (SLM) & AVP06 (Filters) **CHECKED BY:**

AUTHORISED SIGNATURE:

Jack Kielt

Accredited for compliance with ISO/IEC 17025 - Calibration

Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part. The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.



REDITATION Accredited Lab No. 9262 Acoustic and Vibration

Measurements

Acu-Vib Electronics CALIBRATIONS SALES RENTALS REPAIRS

Head Office & Calibration Laboratory Unit 14, 22 Hudson Ave. Castle Hill NSW 2154 (02) 9680 8133 www.acu-vib.com.au

Page 1 of 2 Calibration Certificate AVCERT10.14 Rev.2.0 14/04/2021

Australia

SYDNEY

Ground floor 20 Chandos Street St Leonards NSW 2065 T 02 9493 9500

NEWCASTLE

Level 3 175 Scott Street Newcastle NSW 2300 T 02 4907 4800

BRISBANE Level 1 87 Wickham Terrace Spring Hill QLD 4000

Spring Hill QLD 4000 T 07 3648 1200

CANBERRA

Suite 2.04 Level 2 15 London Circuit Canberra City ACT 2601

ADELAIDE

Level 4 74 Pirie Street Adelaide SA 5000 T 08 8232 2253

MELBOURNE

Suite 8.03 Level 8 454 Collins Street Melbourne VIC 3000 T 03 9993 1900

PERTH

Suite 9.02 Level 9 109 St Georges Terrace Perth WA 6000 T 08 6430 4800

Canada

TORONTO 2345 Yonge Street Suite 300 Toronto ON M4P 2E5 T 647 467 1605

VANCOUVER

60 W 6th Ave Vancouver BC V5Y 1K1 T 604 999 8297



linked in.com/company/emm-consulting-pty-limited



emmconsulting.com.au



Karuah East Quarry

Quarterly Attended Noise Monitoring - Q2 2023

Prepared for Karuah East Quarry Pty Limited

May 2023

Karuah East Quarry

Quarterly Attended Noise Monitoring - Q2 2023

Karuah East Quarry Pty Limited

E230083 RP2

May 2023

Version	Date	Prepared by	Reviewed by	Comments
1	2 May 2023	Lucas Adamson	Najah Ishac	Draft
2	3 May 2023	Lucas Adamson	Najah Ishac	Final

Approved by

Vijab hac

Najah Ishac Director 3 May 2023

Level 3 175 Scott Street Newcastle NSW 2300

This report has been prepared in accordance with the brief provided by Karuah East Quarry Pty Limited and, in its preparation, EMM has relied upon the information collected at the times and under the conditions specified in this report. All findings, conclusions or recommendations contained in this report are based on those aforementioned circumstances. The contents of this report are private and confidential. This report is only for Karuah East Quarry Pty Limited's use in accordance with its agreement with EMM and is not to be relied on by or made available to any other party without EMM's prior written consent. Except as permitted by the *Copyright Act 1968* (Cth) and only to the extent incapable of exclusion, any other use (including use or reproduction of this report for resale or other commercial purposes) is prohibited without EMM's prior written consent. Except where expressly agreed to by EMM in writing, and to the extent permitted by law, EMM will have no liability (and assumes no duty of care) to any person in relation to this document, other than to Karuah East Quarry Pty Limited (and subject to the terms of EMM's agreement with Karuah East Quarry Pty Limited).

© EMM Consulting Pty Ltd, Ground Floor Suite 01, 20 Chandos Street, St Leonards NSW 2065, May 2023.

TABLE OF CONTENTS

1	Intro	duction	1
	1.1	Background	1
	1.2	Attended monitoring locations	1
	1.3	Terminology and abbreviations	3
2	Noise	e limits	4
	2.1	Project approval	4
	2.2	Environment protection licence	4
	2.3	Noise management plan	4
	2.4	Noise limits	4
	2.5	Meteorological conditions	4
	2.6	Additional requirements	5
3	Meth	odology	6
	3.1	Overview	6
	3.2	Attended noise monitoring	6
	3.3	Meteorological data	6
	3.4	Modifying factors	7
	3.5	Instrumentation	7
4	Resu	ts	8
	4.1	Total measured noise levels and atmospheric conditions	8
	4.2	Site only noise levels	9
5	Sumr	nary	12

Appendices

Appendix A	Noise perception and examples	A.1
Appendix B	Regulator documents	B.1
Appendix C	Calibration certificates	C.1

Tables

Table 1.1	Attended noise monitoring locations	1
Table 1.2	Terminology and abbreviations	3
Table 2.1	Noise impact limits, dB	4
Table 3.1	Attended noise monitoring equipment	7
Table 4.1	Total measured noise levels – Q2 2023 ¹	8

Table 4.2	Measured atmospheric conditions – Q2 2023	9
Table 4.3	Site noise levels and limits – Q2 2023	10
Table A.1	Perceived change in noise	A.2
Figures		
Figure 1.1	Attended noise monitoring locations	2
Figure A.1	Common noise levels	A.2

1 Introduction

1.1 Background

EMM Consulting Pty Ltd (EMM) was engaged by Karuah East Quarry Pty Limited to conduct a quarterly noise survey of operations at Karuah East Quarry (KEQ, the site) located at Blue Rock Close, Karuah NSW. The survey is needed to quantify the acoustic environment and used to compare site noise levels against specified limits.

Attended environmental noise monitoring described in this report was done during morning shoulder, day and evening periods on Wednesday 19 and Monday 24 April 2023 at five monitoring locations.


1.2 Attended monitoring locations

Site monitoring locations are detailed in Table 1.1 and shown on Figure 1.1. It should be noted that Figure 1.1 shows actual monitoring positions, not necessarily the location of residences.

Table 1.1 Attended noise monitoring locations

Location	Description/address	Coordinates (MGA56)			
descriptor/ID		Easting	Northing		
А	Private Residence - 74 Mill Hill Close, Karuah	406623	6388704		
В	Private Residence - 64 Mill Hill Close, Karuah	406405	6388859		
F	Private Residence - 1714 The Branch Lane, Karuah	405639	6389782		
G	Private Residence - 2 Halloran Road, North Arm Cove	405629	6389766		
Н	Private Residence - 21 Halloran Road, North Arm Cove	407795	6389868		





KEY

- Site boundary
- A ttended noise monitoring location
- Approved disturbance area
- - Minor road
 - Vehicular track
- Cadastral boundary
- Waterbody
- NPWS reserve
- State forest

Attended noise monitoring locations

Karuah East Quarry Quarterly attended noise monitoring Figure 1.1



1.3 Terminology and abbreviations

Some definitions of terms and abbreviations which may be used in this report are provided in Table 1.2.

Table 1.2 Terminology and abbreviations

Term/descriptor	Definition
dB(A)	Noise level measurement units are decibels (dB). The "A" weighting scale is used to approximate how humans hear noise.
L _{Amax}	The maximum root mean squared A-weighted noise level over a time period.
L _{A1}	The A-weighted noise level which is exceeded for 1 per cent of the time.
LA1,1minute	The A-weighted noise level which is exceeded for 1 per cent of the specified time period of 1 minute.
LA10	The A-weighted noise level which is exceeded for 10 percent of the time.
LAeq	The energy average A-weighted noise level.
LA50	The A-weighted noise level which is exceeded for 50 per cent of the time, also the median noise level during a measurement period.
La90	The A-weighted noise level exceeded for 90 percent of the time, also referred to as the "background" noise level and commonly used to derive noise limits.
LAmin	The minimum A-weighted noise level over a time period.
LCeq	The energy average C-weighted noise energy during a measurement period. The "C" weighting scale is used to take into account low-frequency components of noise within the audibility range of humans.
SPL	Sound pressure level. Fluctuations in pressure measured as 10 times a logarithmic scale, with the reference pressure being 20 micropascals.
Hertz (Hz)	The frequency of fluctuations in pressure, measured in cycles per second. Most sounds are a combination of many frequencies together.
AWS	Automatic weather station used to collect meteorological data, typically at an altitude of 10 metres
VTG	Vertical temperature gradient in degrees Celsius per 100 metres altitude.
Sigma-theta	The standard deviation of the horizontal wind direction over a period of time.
ΙΑ	Inaudible. When site noise is noted as IA then there was no site noise at the monitoring location.
NM	Not Measurable. If site noise is noted as NM, this means some noise was audible but could not be quantified.
Day	Monday – Saturday: 7 am to 6 pm, on Sundays and Public Holidays: 8 am to 6 pm.
Evening	Monday – Saturday: 6 pm to 10 pm, on Sundays and Public Holidays: 6 pm to 10 pm.
Night	Monday – Saturday: 10 pm to 7 am, on Sundays and Public Holidays: 10 pm to 8 am.

Appendix A provides further information that gives an indication as to how an average person perceives changes in noise level, and examples of common noise levels.

2 Noise limits

2.1 Project approval

Karuah East Quarry noise limits are detailed in Condition 3 of Project Approval (PA) 09_0175. Relevant sections of PA 09_0175 are reproduced in Appendix B.1.

2.2 Environment protection licence

Karuah East Quarry noise limits are detailed in Condition L4.1 of Environment Protection Licence (EPL) 20611. Relevant sections of EPL 20611 are reproduced in Appendix B.2.

2.3 Noise management plan

The approved Noise Management Plan (NMP) adopts five attended noise monitoring locations that are representative of residences outlined in PA 09_0175 and EPL 20611. Relevant sections of the NMP are reproduced in Appendix B.3.

2.4 Noise limits

Noise impact limits based on PA 09_0175 and EPL 20611 are as shown in Table 2.1.

Table 2.1Noise impact limits, dB

Location	Day L _{Aeq,15} minute	Evening L _{Aeq,15} minute	Morning Shoulder L _{Aeq,15} minute	Morning Shoulder L _{A1,1minute}
А	42	40	35	52
В	40	40	35	52
F	40	35	35	52
G	43	39	35	52
Н	44	46	35	52

Notes: 1. Morning shoulder period is from 5:00 am to 7:00 am Monday to Saturday as defined in Condition L4.2 of EPL 20611.

2.5 Meteorological conditions

PA 09_0175 specifies that noise generated by the project is to be measured in accordance with the relevant requirements, and exemptions (including certain meteorological conditions), of the NSW Noise Policy for Industry. Similarly, the requirements of Condition L4.3 of EPL 20611 state that noise limits do not apply under the following meteorological conditions:

- wind speeds greater than 3 m/s at 10 m above ground level;
- stability category F temperature inversion conditions and wind speeds greater than 2 m/s at 10 m above ground level; or
- stability category G temperature inversion conditions.

2.6 Additional requirements

Monitoring and reporting have been done in accordance with the NSW EPA 'Noise Policy for Industry' (NPfI) issued in October 2017 and the 'Approved methods for the measurement and analysis of environmental noise in NSW' (Approved Methods) issued in January 2022.

3 Methodology

3.1 Overview

Attended environmental noise monitoring was done in general accordance with Australian Standard AS1055 'Acoustics, Description and Measurement of Environmental Noise' and relevant EPA requirements. Meteorological data was obtained from the KEQ on-site meteorological station which allowed correlation of atmospheric parameters with measured noise levels.

3.2 Attended noise monitoring

During this survey, attended noise monitoring was conducted during the morning shoulder, day and evening periods at each location. The duration of each measurement was 15 minutes. Atmospheric conditions were measured at each monitoring location.

Measured sound levels from various sources were noted during each measurement, and particular attention was paid to the extent of site's contribution (if any) to measured levels. At each monitoring location, the site-only $L_{Aeq,15minute}$ and L_{Amax} were measured directly or determined by other methods detailed in Section 7.1 of the NPfI.

If the exact noise levels from site could not be established due to masking by other noise sources in a similar frequency range, but site noise was determined to be at least 5 dB lower than relevant limits, then a maximum estimate of site noise may be provided. This is expressed as a 'less than' quantity, such as <20 dB or <30 dB.

The terms 'Inaudible' (IA) or 'Not Measurable' (NM) may be used in this report. When site noise is noted as IA, no site noise was audible at the monitoring location. When site noise is noted as NM, this means site noise was audible but could not be quantified. All results noted as NM in this report were due to one or more of the following:

- Site noise levels were extremely low and unlikely, in many cases, to be noticed.
- Site noise levels were masked by other more dominant noise sources that are characteristic of the environment, such as breeze in foliage or continuous road traffic noise, that cannot be eliminated by monitoring at an alternate or intermediate location.
- It was not feasible or reasonable to employ methods such as to move closer and back calculate. Cases may include rough terrain preventing closer measurement, addition/removal of significant source to receiver shielding caused by moving closer, and meteorological conditions where back calculation may not be accurate.

For this assessment, the measured L_{Amax} has been used as a conservative estimate of $L_{A1,1minute}$. The EPA accepts sleep disturbance analysis based on either the $L_{A1,1minute}$ or L_{Amax} metrics, with the L_{Amax} representing a more conservative assessment of site noise emissions.

3.3 Meteorological data

Meteorological data for the monitoring period was sourced from the Karuah East Quarry on-site meteorological station to determine applicability of criteria in accordance with the EPL and PA.

3.4 Modifying factors

All measurements were evaluated for potential modifying factors in accordance with the NPfI. Assessment of modifying factors is undertaken at the time of measurement if the site was audible and directly quantifiable. If applicable, modifying factor penalties have been reported and added to measured site only L_{Aeg} noise levels.

Low-frequency modifying factor penalties have only been applied to site-only L_{Aeq} levels if the site was the only contributing low-frequency noise source. Specific methodology for assessment of each modifying factor is outlined in Fact Sheet C of the NPfI.

3.5 Instrumentation

Equipment used to measure environmental noise levels is detailed in Table 3.1. Calibration certificates are provided in Appendix C.

Table 3.1 Attended noise monitoring equipment

Item	Serial number	Calibration due date	Relevant standard
Brüel & Kjær 2250 sound level meter	3029363	3/11/2024	IEC 61672-1:2002
Svantek SV-36 calibrator	86311	17/10/2024	IEC 60942

4 **Results**

4.1 Total measured noise levels and atmospheric conditions

Overall noise levels measured at each location during attended measurements are provided in Table 4.1.

Location	Start date and time	L _{Amax} dB	L _{A1} dB	L _{A10} dB	L _{Aeq} dB	L _{A50} dB	L _{A90} dB	L _{Amin} dB
Н	19/04/2023 15:35	65	49	45	43	42	40	38
G	19/04/2023 15:54	73	56	45	48	42	40	38
F	19/04/2023 16:20	83	69	48	57	45	43	40
В	19/04/2023 16:54	79	74	69	66	64	59	53
А	19/04/2023 17:15	67	61	57	54	53	50	47
Н	19/04/2023 18:00	51	45	42	41	40	39	36
G	19/04/2023 18:17	59	46	42	40	39	38	36
F	19/04/2023 18:42	77	53	48	50	45	42	38
В	19/04/2023 19:02	83	75	70	66	62	54	46
A	19/04/2023 19:19	78	75	70	66	61	54	48
Н	24/04/2023 5:06	51	48	45	42	40	36	30
G	24/04/2023 5:24	54	50	46	43	42	38	34
F	24/04/2023 6:06	77	61	54	54	49	45	41
В	24/04/2023 6:25	80	74	68	65	61	56	50
A	24/04/2023 6:43	65	54	52	50	50	47	44

Table 4.1Total measured noise levels – Q2 20231

Notes: 1. Levels in this table are not necessarily the result of activity at site.

Atmospheric condition data measured by the operator during each measurement using a hand-held weather meter is shown in Table 4.2. The wind speed, direction and temperature were measured at approximately 1.5 metres above ground. Attended noise monitoring is not done during rain, hail, or wind speeds above 5 m/s at microphone height.

Location	Start date and time	Temperature °C	Wind speed m/s	Wind direction ^o Magnetic north ¹	Cloud cover 1/8s
Н	19/04/2023 15:35	22.7	1.9	60	1
G	19/04/2023 15:54	22.5	1.8	60	1
F	19/04/2023 16:20	22.1	<0.5	-	0
В	19/04/2023 16:54	21.4	0.7	70	0
А	19/04/2023 17:15	20.1	<0.5	-	0
Н	19/04/2023 18:00	18.2	<0.5	-	0
G	19/04/2023 18:17	17.8	<0.5	-	0
F	19/04/2023 18:42	17.1	<0.5	-	0
В	19/04/2023 19:02	16.3	<0.5	-	0
A	19/04/2023 19:19	16.0	<0.5	-	0
Н	24/04/2023 5:06	15.9	<0.5	-	1
G	24/04/2023 5:24	16.2	<0.5	-	1
F	24/04/2023 6:06	17.6	<0.5	-	1
В	24/04/2023 6:25	17.3	<0.5	-	1
А	24/04/2023 6:43	17.8	<0.5	-	1

Table 4.2 Measured atmospheric conditions – Q2 2023

Notes: 1. "-" indicates calm conditions at monitoring location.

4.2 Site only noise levels

4.2.1 Modifying factors

There were no modifying factors, as defined in the NPfI, applicable during the survey.

4.2.2 Monitoring results

Table 4.3 provides site noise levels in the absence of other sources, where possible, and includes weather data obtained from the site's AWS. Limits are applicable if weather conditions were within specified parameters during each measurement.

Table 4.3Site noise levels and limits – Q2 2023

Location	Start Date and Time (Period)	Wind		Stability Class	Limits apply? 1	Limit, dB		Site level, dB ²		Exceedance, dB	
		Speed m/s	Direction ⁴	-	-	L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}
Н	19/04/2023 15:35 (D)	2.4	136	А	Y	44	N/A	IA	N/A	No	N/A
G	19/04/2023 15:54 (D)	2.0	128	А	Y	43	N/A	IA	N/A	No	N/A
F	19/04/2023 16:20 (D)	1.7	131	А	Y	40	N/A	IA	N/A	No	N/A
В	19/04/2023 16:54 (D)	0.9	137	А	Y	40	N/A	IA	N/A	No	N/A
А	19/04/2023 17:15 (D)	1.2	128	А	Y	42	N/A	IA	N/A	No	N/A
Н	19/04/2023 18:00 (E)	0.7	130	F	Y	46	N/A	IA	N/A	No	N/A
G	19/04/2023 18:17 (E)	0.8	136	F	Y	39	N/A	IA	N/A	No	N/A
F	19/04/2023 18:42 (E)	0.9	135	F	Y	35	N/A	IA	N/A	No	N/A
В	19/04/2023 19:02 (E)	0.9	141	F	Y	40	N/A	IA	N/A	No	N/A
А	19/04/2023 19:19 (E)	1.0	141	E	Y	40	N/A	IA	N/A	No	N/A

Table 4.3Site noise levels and limits – Q2 2023

Location	Start Date and Time (Period)	Wind		Stability Class	Limits apply? 1	Limit, dB		Site level, dB ² Exceedance, dB		e, dB	
		Speed m/s	Direction ⁴			L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}
Н	24/04/2023 5:06 (MS)	0.4	333	F	Y	35	52	IA	IA	No	No
G	24/04/2023 5:24 (MS)	0.4	322	F	Y	35	52	IA	IA	No	No
F	24/04/2023 6:06 (MS)	0.1	336	F	Y	35	52	IA	IA	No	No
В	24/04/2023 6:25 (MS)	0.3	321	F	Y	35	52	IA	IA	No	No
А	24/04/2023 6:43 (MS)	0.1	331	F	Y	35	52	IA	IA	No	No

Notes: 1. Noise emission limits do not apply during periods of rainfall or winds greater than 3 metres per second (at a height of 10 metres).
 2. Site-only LAeq,15minute, includes modifying factor penalties if applicable.

3. NA in exceedance column means criterion was not applicable due to atmospheric conditions outside those specified in project approval.

4. Degrees magnetic north, "-" indicates calm conditions.

5. MS = Morning Shoulder period; D = Day period; E = Evening period.

5 Summary

EMM Consulting Pty Ltd (EMM) was engaged by Karuah East Quarry Pty Limited to conduct a quarterly noise survey of operations at the site. The survey purpose was to quantify the acoustic environment and compare site noise levels against specified PA and EPL noise limits.

Attended environmental noise monitoring described in this report was done during the morning shoulder, day and evening periods on Wednesday 19 and Monday 24 April 2023 at five monitoring locations.

Karuah East Quarry was confirmed inaudible at all locations during the day, evening and morning shoulder periods. Typically, when this type of noise source is not audible above ambient (not withstanding insect noise and other sources of varied character), the likely level of that source is at least 10 dB below the measured background (L_{A90}) level. However, given the locality of locations A and B (directly adjacent to the Pacific Highway), the L_{A90} is controlled by road traffic noise. Karuah East Quarry was also confirmed to be inaudible during lulls in road traffic noise which, for the measurements at A and B, would correlate with the L_{Amin} measured during the surveys. Given this, the measured background noise levels and measured L_{Amin} (for locations A and B), Karuah East Quarry was estimated to be below the relevant noise limits. The Karuah East Quarry L_{Amax} was also deemed to satisfy the relevant limits given site was inaudible at all locations during the morning shoulder period.

Noise levels from site complied with relevant limits at all monitoring locations during the Q2 2023 survey.

Appendix A

Noise perception and examples




A.1 Noise levels

Table A.1 gives an indication as to how an average person perceives changes in noise level. Examples of common noise levels are provided in Figure A.1.

Table A.1Perceived change in noise

Change in sound pressure level (dB)	Perceived change in noise
up to 2	Not perceptible
3	Just perceptible
5	Noticeable difference
10	Twice (or half) as loud
15	Large change
20	Four times (or quarter) as loud





Appendix B Regulator documents



B.1 Project approval

SCHEDULE 3 ENVIRONMENTAL PERFORMANCE CONDITIONS

IDENTIFICATION OF APPROVED LIMITS OF EXTRACTION

- 1. The Applicant shall, prior to carrying out quarrying operations on the site:
 - (a) engage a registered surveyor to mark out the boundaries of the approved limits of extraction within the Extraction Area; and
 - (b) submit a survey plan of the extraction boundaries,
 - to the satisfaction of the Planning Secretary.
- 2. The Applicant must ensure that the extraction boundaries are clearly marked at all times while quarrying operations are being carried out, in a manner that allows the limits of extraction to be clearly identified.

NOISE

Operational Noise Criteria

3. Except for the carrying out of construction works, the Applicant must ensure that the operational noise generated by the development does not exceed the criteria in Table 2 at any residence^a on privately-owned land.

Noise Assessment Location ^a	Morning Shoulder LAeq (15 min)	Morning Shoulder L _{Amax}	Day L _{Aeq (15 min)}	Evening L _{Aeq (15 min)}
А	35	52	42	40
В	35	52	40	40
G	35	52	43	39
Н	35	52	44	46
I	35	52	40	37
All other residences	35	52	40	35

Table 2: Operational noise criteria dB

^a Noise Assessment Locations referred to in Table 2 are shown in Appendix 2.

Noise generated by the development must be monitored and measured in accordance with the relevant procedures and modifications (including certain meteorological conditions) of the NPfI.

3A. The noise criteria in Table 2 do not apply if the Applicant has an agreement with the owner/s of the relevant residence or land to exceed the noise criteria, and the Applicant has advised the Department in writing of the terms of this agreement.

Road Traffic Noise Criteria

4. The Applicant must take all reasonable and feasible measures to ensure that the traffic noise generated by the development does not cause additional exceedances of the criteria in Table 3 at any residence on privately-owned land.

Table 3: Road traffic noise criteria

Road	Criteria (Dayª)
Pacific Highway	60 dB(A) LAeq (15 hour)
Local roads	55 dB(A) L _{Aeq (1 hour)}

^a Day is the period from 7 am to 10 pm every day in accordance with the EPA's NSW Road Noise Policy (2011).

5. Deleted

Noise Operating Conditions

- 6. The Applicant must:
 - (a) take all reasonable steps to minimise noise from construction and operational activities, including low frequency noise and other audible characteristics, associated with the development;
 - (b) implement reasonable and feasible noise attenuation measures on all plant and equipment that will operate in noise sensitive areas;
 - (c) operate a comprehensive noise management system commensurate with the risk of impact;
 - (d) take all reasonable steps to minimise the noise impacts of the development during noiseenhancing meteorological conditions when the noise criteria in this consent do not apply (see NPfI);
 - (e) carry out quarterly attended noise monitoring (unless otherwise agreed by the Planning Secretary) to determine whether the development is complying with the relevant conditions of this consent; and
 - (f) regularly assess the noise monitoring data and modify or stop operations on the site to ensure compliance with the relevant conditions of this consent.

Noise Management Plan

- 7. The Applicant must prepare a Noise Management Plan for the development to the satisfaction of the Planning Secretary. This plan must:
 - (a) be prepared by a suitably qualified and experienced person/s whose appointment has been endorsed by the Planning Secretary;
 - (b) be prepared in consultation with the EPA;
 - (c) describe the measures to be implemented to ensure:
 - (i) compliance with the noise criteria and operating conditions in this consent;
 - (ii) best practice management is being employed;
 - (iii) noise impacts of the development are minimised during noise-enhancing meteorological conditions when the noise criteria in this consent do not apply (see NPfI);
 - (d) describe the noise management system in detail; and
 - (e) include a monitoring program that:
 - (i) is capable of evaluating the performance of the development;
 - (ii) monitors noise at the nearest and/or most affected residences;
 - (iii) adequately supports the noise management system;
 - (iv) includes a protocol for distinguishing noise emissions of the development from any neighbouring developments; and
 - includes a protocol for identifying any noise-related exceedance, incident or noncompliance and for notifying the Department and relevant stakeholders of any such event.
- 7A. The Applicant must implement the plan as approved by the Planning Secretary.

BLASTING

Blasting Criteria

8. The Applicant must ensure that blasting on the site does not cause exceedances of the criteria in Table 5.

B.2 Environmental protection licence

Licence - 20611

L3 Waste

L3.1 The licensee must not cause, permit or allow any waste generated outside the premises to be received at the premises for storage, treatment, processing, reprocessing or disposal or any waste generated at the premises to be disposed of at the premises, except as expressly permitted by the licence.

L4 Noise limits

L4.1 Noise generated at the premises must not exceed the noise limits in the table below. The locations referred to in the table below are indicated in Table 2: Operational Noise Criteria, and Figure 1 of the document titled Project Approval 09_0175 Modification 9 (MOD 9) Department of Planning, Industry& Environment - which has been filed on EPA file Doc22/715570-1.

Noise Assesment Location	Morning Shoulder LAeq(15 min)	Morning shoulder LAmax	Day LAeq (15 min)	Evening LAeq (15 min)
A (74 Mill Hill Close, Karuah, Lot 100 DP 1028885)	35	52	42	40
B (64 Mill Hill Close, Karuah, Lot 3 DP785172)	35	52	40	40
G (2 Halloran Road, North Arm Cove Lot 1 DP1032636)	35	52	43	39
H (21 Halloran Road, North Arm Cove Lot 10 DP1032636)	35	52	44	46
l (83 Halloran Road, North Arm Cove Lot 12 DP1032636)	35	52	40	37
All other residences	35	52	40	35

L4.2 Noise limit definitions - For the purpose of the table at L4.1, the following definitions apply: Day is defined as the period from 7am to 6pm Monday to Saturday and 8am to 6pm Sunday and Public Holidays;

Morning Shoulder is defined as the period from 5:00am to 7:00am Monday to Saturday; Evening is defined as the period from 6:00pm to 10:00pm Monday to Saturday.

- L4.3 The noise limits set out in this licence apply under all meteorological conditions except for the following:
 - a) Wind speed greater than 3 metres/second at 10 metres above ground level; or

b) Stability category F temperature inversion conditions and wind speeds greater than 2 metres/second at 10 metres above ground level; or

NSU Manual in the second second

Licence - 20611

c) Stability category G temperature inversion conditions.

L4.4 Determining Compliance

To determine compliance with the noise limits set out in the table above, the licensee must locate monitoring equipment:

a) within 30 metres of a dwelling façade (but not closer than 3 metres) where any dwelling on the property is situated more than 30 metres from the property boundary that is closest to the premises;

b) approximately on the boundary where any dwelling is situated 30 metres or less from the property boundary that is closest to the premises;

c) at the most affected point at a location where there is no dwelling at the location; and

d) within approximately 50 metres of the boundary of a national park or nature reserve.

Note: A non-compliance of the Noise Limits table will still occur where noise generated from the premises in excess of the appropriate limit is measured:

i) at a location other than an area prescribed in part (a) and part (b); and/or

ii) at a point other than the most affected point at a location.

L4.5 For the purposes of determining the noise generated at the premises the modification factors in Fact Sheet C of the EPA's "Noise Policy for Industry" must be applied, as appropriate, to the noise levels measured by the noise monitoring equipment.

L5 Blasting

- L5.1 Blasting in or on the premises must only be carried out between the hours of 9:00 am and 4:00 pm Monday to Friday. No blasting is permitted on Saturdays, Sundays or public holidays. Blasting outside of the hours specified in this condition can only take place with the written approval of the EPA.
- L5.2 Blasting is not permitted simultaneously with adjacent quarry(s).
- L5.3 The airblast overpressure level from blasting operations in or on the premises must not exceed:
 a) 115 dB (Lin Peak) for more than 5% of the total number of blasts during each reporting period; and
 b) 120 dB (Lin Peak) at any time,
 at monitoring point 11 detailed in Condition P1.4.
- L5.4 The ground vibration peak particle velocity from blasting operations carried out in or on the premises must not exceed:

a) 5 mm/second for more than 5% of the total number of blasts during each reporting period; and

b) 10 mm/second at any time,

at monitoring point 11 detailed in Condition P1.4.

- L5.5 Error margins associated with any monitoring equipment used to measure airblast overpressure or peak particle velocity are not to be taken into account in determing whether or not the limit has been exceeded.
- L5.6 The airblast overpressure and ground vibration levels in the conditions above do not apply at noise sensitive locations that are owned by the licensee or subject to a private agreement, relating to airblast overpressure and ground vibration levels, between the licensee and land owner.

USN SURVEY



Licence - 20611

a) the date and time of the complaint;

b) the method by which the complaint was made;

c) any personal details of the complainant which were provided by the complainant or, if no such details were provided, a note to that effect;

d) the nature of the complaint;

e) the action taken by the licensee in relation to the complaint, including any follow-up contact with the complainant; and

f) if no action was taken by the licensee, the reasons why no action was taken.

- M5.3 The record of a complaint must be kept for at least 4 years after the complaint was made.
- M5.4 The record must be produced to any authorised officer of the EPA who asks to see them.

M6 Telephone complaints line

- M6.1 The licensee must operate during its operating hours a telephone complaints line for the purpose of receiving any complaints from members of the public in relation to activities conducted at the premises or by the vehicle or mobile plant, unless otherwise specified in the licence.
- M6.2 The licensee must notify the public of the complaints line telephone number and the fact that it is a complaints line so that the impacted community knows how to make a complaint.
- M6.3 The preceding two conditions do not apply until 1 month after the date of the issue of this licence.

M7 Blasting

M7.1 To determine complaince with Blast Limit conditions of this licence:

a) Airblast overpressure and ground vibration levels must be measured and electronically recorded for monitoring point 11 for the parameters specified in Column 1 of the table below; and
b) The licensee must use the units of measure, sampling method, and sample at the frequency specified opposite in the other columns.

Parameter	Units of Measure	Frequency	Sampling Method
Airblast Overpressure	Decibels (Linear Peak	All blasts	Australian Standard AS 2187.2-2006
Ground Vibration Peak Particle Velocity	millimetres/second	All blasts	Australian Standard AS 2187.2-2006

M8 Noise monitoring

- M8.1 To assess compliance with the noise limits for this premises attended noise monitoring must be undertaken in accordance with all noise conditions and:
 - a) during a period of normal quarry operations;
 - b) at each one of the locations listed in the noise limits table of this licence;



Licence - 20611

c) occur quarterly in the reporting period;

d) occur during each day period as defined in the NSW Noise Policy for Industry.

Note: Quarterly attended noise monitoring must be completed (unless otherwise agreed by the Planning Secretary) to determine whether the development is complying with the relevant conditions of this consent. The frequency of noise monitoring will be reviewed, upon request.

6 Reporting Conditions

R1 Annual return documents

- R1.1 The licensee must complete and supply to the EPA an Annual Return in the approved form comprising:
 - 1. a Statement of Compliance,
 - 2. a Monitoring and Complaints Summary,
 - 3. a Statement of Compliance Licence Conditions,
 - 4. a Statement of Compliance Load based Fee,
 - 5. a Statement of Compliance Requirement to Prepare Pollution Incident Response Management Plan,
 - 6. a Statement of Compliance Requirement to Publish Pollution Monitoring Data; and
 - 7. a Statement of Compliance Environmental Management Systems and Practices.

At the end of each reporting period, the EPA will provide to the licensee notification that the Annual Return is due.

- R1.2 An Annual Return must be prepared in respect of each reporting period, except as provided below.
- Note: The term "reporting period" is defined in the dictionary at the end of this licence. Do not complete the Annual Return until after the end of the reporting period.
- R1.3 Where this licence is transferred from the licensee to a new licensee:

a) the transferring licensee must prepare an Annual Return for the period commencing on the first day of the reporting period and ending on the date the application for the transfer of the licence to the new licensee is granted; and

b) the new licensee must prepare an Annual Return for the period commencing on the date the application for the transfer of the licence is granted and ending on the last day of the reporting period.

- Note: An application to transfer a licence must be made in the approved form for this purpose.
- R1.4 Where this licence is surrendered by the licensee or revoked by the EPA or Minister, the licensee must prepare an Annual Return in respect of the period commencing on the first day of the reporting period and ending on:

a) in relation to the surrender of a licence - the date when notice in writing of approval of the surrender is given; or

b) in relation to the revocation of the licence - the date from which notice revoking the licence operates.

R1.5 The Annual Return for the reporting period must be supplied to the EPA via eConnect EPA or by registered

B.3 Noise management plan

5 Noise limits

5.1 Operational noise

Condition 3 of Schedule 3 of PA 09_0175 provides the operational noise limits for KEQ. These are reproduced in Table 5.1.

Table 5.1 Operational noise criteria (dB) from Table 2 of PA 09_0175

Noise Assessment Location ¹	Morning Shoulder L _{Aeq(15 minute)}	Morning Shoulder L _{Amax}	Day L _{Aeq(15 minute)}	Evening L _{Aeq(15 minute)}
A	35	52	42	40
В	35	52	40	40
G	35	52	43	39
Н	35	52	44	46
I	35	52	40	37
All other residences	35	52	40	35

Noise assessment locations are shown in Figure 3.1.

Noise generated by the development must be monitored and measured in accordance with the relevant procedures and exemptions (including certain meteorological conditions) of the NPfI (EPA 2017).

The noise limits provided in Table 5.1 apply under standard and noise-enhancing meteorological conditions (as defined in the NPfI) determined by monitoring at the relevant weather station. In accordance with Condition L4.3 of EPL 20611 and consistent with Condition 3 of Schedule 3 of PA 09_0175 the noise limits provided in Table 5.1 apply under all meteorological conditions except for the following:

- wind speeds greater than 3m/s at 10m above ground level;
- stability category F temperature inversion conditions and wind speeds greater then 2m/s at 10m above ground level; or
- stability category G temperature inversion conditions.

In accordance with Fact Sheet D of the NPfI, for 'very noise enhancing meteorological conditions' the applicable noise limit is set at 5dB above those provided in Table 5.1.

Noise limits do not apply if Karuah East has an agreement with the owner/s of the relevant residence or land to exceed the noise criteria, and Karuah East has advised the Department in writing of the terms of this agreement.

5.2 Road traffic noise

Condition 4 of Schedule 3 of PA 09_0175 states that all reasonable and feasible measures must be taken to ensure that the traffic generated by KEQ does not cause additional exceedances of the criteria provided in Table 5.2 at any residence on privately-owned land.

Appendix C Calibration certificates



CERTIFICATE OF CALIBRATION

CERTIFICATE NO: C34022

EQUIPMENT TESTED : Sound Level Calibrator

• •	e No: vner: med:	Suite 0 St Leon Measur	k Serial Consulting 1, 20 Chandos nards NSW 20 ed Output Pres tails overleaf. A	s St 65 sure level, l	Frequency 8	& Distortion
Parameter	Pre- Adj	Adj Y/N	Output (dB re 20)	and the second second	requency (Hz)	THD&N (%)
Level1:	NA	N	94.01 di	3 1	000.00 Hz	2.00 %
Level2:	NA	N	113.92 d	B 1	000.00 Hz	0.35 %
Uncertainty			±0.11 d	3	±0.05%	±0.20 %
Uncertainty (at 9 CONDITION OF Ambient Pres Tempera	TEST: ssure	1013	hPa ±1 hPa °C ±1° C			17/10/2022 17/10/2022
Relative Hum Acu-Vib Proced CHECKED BY	Test lure:	AVP02	% ±5% (Calibrators) ethod: AS IEC 6 AUTHORISE	0942 - 201		17/10/2022

Accredited for compliance with ISO/IEC 17025 - Calibration

Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part. The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.



ACCREDITATION Accredited Lab No. 9262 Acoustic and Vibration Measurements Acu-Vib Electronics CALIBRATIONS SALES RENTALS REPAIRS

Head Office & Calibration Laboratory Unit 14, 22 Hudson Ave. Castle Hill NSW 2154 (02) 9680 8133 www.acu-vib.com.au

Page 1 of 2 Calibration Certificate AVCERT02.1 Rev.2.0 14.04.2021

CERTIFICATE OF CALIBRATION

CERTIFICATE NO: SLM34169

EQUIPMENT TESTED: Sound Level Meter

Manufacturer:	B&K	
Type No:	2250	
Mic. Type:	4189	
Pre-Amp. Type:	ZC0032	

Serial No: 3029363 Serial No: 3260501 Serial No: 30109 Test No: F034175

Filter Type: 1/3 Octave

Owner: EMM Consulting Suite 01, 20 Chandos St St Leonards NSW 2065

Tests Performed: IEC 61672-3:2013 & IEC 61260-3:2016

Comments:All Test passed for Class 1. (See overleaf for details)CONDITIONS OF TEST:Ambient Pressure1002hPa ±1 hPaDate of Receipt :02/11/2022

Temperature Relative Humidity 02 hPa ±1 hPa 24 °C ±1° C 35 % ±5%

Date of Calibration : 03/11/2022 Date of Issue : 04/11/2022

Jack Kielt

Accredited for compliance with ISO/IEC 17025 - Calibration

Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part. The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.



WORLD RECOGNISED ACCREDITATION Accredited Lab No. 9262 Acoustic and Vibration Measurements Acu-Vib Electronics CALIBRATIONS SALES RENTALS REPAIRS

Head Office & Calibration Laboratory Unit 14, 22 Hudson Ave. Castle Hill NSW 2154 (02) 9680 8133 www.acu-vib.com.au

Page 1 of 2 Calibration Certificate AVCERT10.14 Rev.2.0 14/04/2021

Australia

SYDNEY

Ground floor 20 Chandos Street St Leonards NSW 2065 T 02 9493 9500

NEWCASTLE

Level 3 175 Scott Street Newcastle NSW 2300 T 02 4907 4800

BRISBANE Level 1 87 Wickham Terrace Spring Hill QLD 4000

Spring Hill QLD 4000 T 07 3648 1200

CANBERRA

Suite 2.04 Level 2 15 London Circuit Canberra City ACT 2601

ADELAIDE

Level 4 74 Pirie Street Adelaide SA 5000 T 08 8232 2253

MELBOURNE

Suite 8.03 Level 8 454 Collins Street Melbourne VIC 3000 T 03 9993 1900

PERTH

Suite 9.02 Level 9 109 St Georges Terrace Perth WA 6000 T 08 6430 4800

Canada

TORONTO 2345 Yonge Street Suite 300 Toronto ON M4P 2E5 T 647 467 1605

VANCOUVER

60 W 6th Ave Vancouver BC V5Y 1K1 T 604 999 8297



linked in.com/company/emm-consulting-pty-limited



emmconsulting.com.au



Karuah East Quarry

Quarterly Attended Noise Monitoring - Q3 2023

Prepared for Karuah East Quarry Pty Limited

October 2023

Karuah East Quarry

Quarterly Attended Noise Monitoring - Q3 2023

Karuah East Quarry Pty Limited

E230083 RP4

October 2023

Version	Date	Prepared by	Reviewed by	Comments
1	23 August 2023	Lucas Adamson	Tony Welbourne	Draft
2	25 August 2023	Lucas Adamson	Tony Welbourne	Final
3	18 October 2023	Rick Scully	Robert Kirwan	Updated to include reference to EPL Conditions R3(a) and (c)

Approved by

lue

Robert Kirwan Associate Consultant 18 October 2023

Level 3 175 Scott Street Newcastle NSW 2300

This report has been prepared in accordance with the brief provided by Karuah East Quarry Pty Limited and, in its preparation, EMM has relied upon the information collected at the times and under the conditions specified in this report. All findings, conclusions or recommendations contained in this report are based on those aforementioned circumstances. The contents of this report are private and confidential. This report is only for Karuah East Quarry Pty Limited's use in accordance with its agreement with EMM and is not to be relied on by or made available to any other party without EMM's prior written consent. Except as permitted by the *Copyright Act 1968* (Cth) and only to the extent incapable of exclusion, any other use (including use or reproduction of this report for resale or other commercial purposes) is prohibited without EMM's prior written consent. Except where expressly agreed to by EMM in writing, and to the extent permitted by law, EMM will have no liability (and assumes no duty of care) to any person in relation to this document, other than to Karuah East Quarry Pty Limited (and subject to the terms of EMM's agreement with Karuah East Quarry Pty Limited).

© EMM Consulting Pty Ltd, Ground Floor Suite 01, 20 Chandos Street, St Leonards NSW 2065, October 2023.

TABLE OF CONTENTS

1	Introduction				
	1.1	Background	1		
	1.2	Attended monitoring locations	1		
	1.3	Terminology and abbreviations	3		
2	Noise	e limits	4		
	2.1	Project approval	4		
	2.2	Environment protection licence	4		
	2.3	Noise management plan	4		
	2.4	Noise limits	4		
	2.5	Meteorological conditions	4		
	2.6	Additional requirements	5		
	2.7	Very noise-enhancing meteorological conditions	5		
3	Meth	nodology	6		
	3.1	Overview	6		
	3.2	Attended noise monitoring	6		
	3.3	Meteorological data	6		
	3.4	Modifying factors	7		
	3.5	Site operations	7		
	3.6	Instrumentation	7		
4	Resu	lts	8		
	4.1	Total measured noise levels and atmospheric conditions	8		
	4.2	Site only noise levels	9		
5	Mitig	ation and management	12		
	5.1	Proposed management actions	12		
6	Sum	mary	13		

Appendices

Tables

Attended noise monitoring locations	1
Terminology and abbreviations	3
Noise impact limits, dB	4
Attended noise monitoring equipment	7
Total measured noise levels – Q3 2023 ¹	8
	Terminology and abbreviations Noise impact limits, dB Attended noise monitoring equipment

Table 4.2	Measured atmospheric conditions – Q3 2023	9
Table 4.3	Site noise levels and limits – Q3 2023	10
Table A.1	Perceived change in noise	A.2
Figures		
Figure 1.1	Attended noise monitoring locations	2
Figure A.1	Common noise levels	A.2

1 Introduction

1.1 Background

EMM Consulting Pty Ltd (EMM) was engaged by Karuah East Quarry Pty Limited to conduct a quarterly noise survey of operations at Karuah East Quarry (KEQ, the site) located at Blue Rock Close, Karuah NSW. The survey purpose was to quantify the acoustic environment and compare site noise levels against specified limits.

Attended environmental noise monitoring described in this report was done during morning shoulder, day and evening periods on Thursday 10 and Friday 11 August 2023 at five monitoring locations.


1.2 Attended monitoring locations

Site monitoring locations are detailed in Table 1.1 and shown on Figure 1.1. It should be noted that Figure 1.1 shows actual monitoring positions, not necessarily the location of residences.

Table 1.1 Attended noise monitoring locations

Location descriptor/ID	Description/address	Coordinates (MGA56)	
		Easting	Northing
А	Private residence - 74 Mill Hill Close, Karuah	406623	6388704
В	Private residence - 64 Mill Hill Close, Karuah	406405	6388859
F	Private residence - 1714 The Branch Lane, Karuah	405639	6389782
G	Private residence - 2 Halloran Road, North Arm Cove	405629	6389766
Н	Private residence - 21 Halloran Road, North Arm Cove	407795	6389868





KEY

- Site boundary
- A ttended noise monitoring location
- Approved disturbance area
- - Minor road
 - Vehicular track
- Cadastral boundary
- Waterbody
- NPWS reserve
- State forest

Attended noise monitoring locations

Karuah East Quarry Quarterly attended noise monitoring Figure 1.1



1.3 Terminology and abbreviations

Some definitions of terms and abbreviations which may be used in this report are provided in Table 1.2.

Table 1.2 Terminology and abbreviations

dB(A)	
ub(A)	Noise level measurement units are decibels (dB). The "A" weighting scale is used to approximate how humans hear noise.
L _{Amax}	The maximum root mean squared A-weighted noise level over a time period.
L _{A1}	The A-weighted noise level which is exceeded for 1 per cent of the time.
LA1,1minute	The A-weighted noise level which is exceeded for 1 per cent of the specified time period of 1 minute.
L _{A10}	The A-weighted noise level which is exceeded for 10 per cent of the time.
L _{Aeq}	The energy average A-weighted noise level.
LA50	The A-weighted noise level which is exceeded for 50 per cent of the time, also the median noise level during a measurement period.
LA90	The A-weighted noise level exceeded for 90 per cent of the time, also referred to as the "background" noise level and commonly used to derive noise limits.
LAmin	The minimum A-weighted noise level over a time period.
LCeq	The energy average C-weighted noise energy during a measurement period. The "C" weighting scale is used to take into account low-frequency components of noise within the audibility range of humans.
SPL	Sound pressure level. Fluctuations in pressure measured as 10 times a logarithmic scale, with the reference pressure being 20 micropascals.
Hertz (Hz)	The frequency of fluctuations in pressure, measured in cycles per second. Most sounds are a combination of many frequencies together.
AWS	Automatic weather station used to collect meteorological data, typically at an altitude of 10 metres
VTG	The vertical temperature gradient in degrees Celsius per 100 metres altitude.
Sigma-theta	The standard deviation of the horizontal wind direction over a period of time.
IA	Inaudible. When site noise is noted as IA then there was no site noise at the monitoring location.
NM	Not Measurable. If site noise is noted as NM, this means some noise was audible but could not be quantified.
Day	Monday – Saturday: 7 am to 6 pm, on Sundays and Public Holidays: 8 am to 6 pm.
Evening	Monday – Saturday: 6 pm to 10 pm, on Sundays and Public Holidays: 6 pm to 10 pm.
Morning Shoulder	Monday – Saturday: 5 am to 7 am.

Appendix A provides further information that indicates how an average person perceives changes in noise levels and examples of common noise levels.

2 Noise limits

2.1 Project approval

Karuah East Quarry noise limits are detailed in Condition 3 of Project Approval (PA) 09_0175. Relevant sections of PA 09_0175 are reproduced in Appendix B.1.

2.2 Environment protection licence

Karuah East Quarry noise limits are detailed in Condition L4.1 of Environment Protection Licence (EPL) 20611. Relevant sections of EPL 20611 are reproduced in Appendix B.2.

2.3 Noise management plan

The approved Noise Management Plan (NMP) adopts five attended noise monitoring locations that are representative of residences outlined in PA 09_0175 and EPL 20611. Relevant sections of the NMP are reproduced in Appendix B.3.

2.4 Noise limits

Noise impact limits based on PA 09_0175 and EPL 20611 are as shown in Table 2.1.

Table 2.1Noise impact limits, dB

Location	Day L _{Aeq,15minute}	Evening L _{Aeq,15} minute	Morning Shoulder L _{Aeq,15} minute	Morning Shoulder L _{A1,1minute}
А	42	40	35	52
В	40	40	35	52
F	40	35	35	52
G	43	39	35	52
Н	44	46	35	52

Notes: 1. Morning shoulder period is from 5:00 am to 7:00 am Monday to Saturday as defined in Condition L4.2 of EPL 20611.

2.5 Meteorological conditions

PA 09_0175 specifies that noise generated by the project is to be measured in accordance with the relevant requirements, and exemptions (including certain meteorological conditions), of the NSW EPA 'Noise Policy for Industry' (NPfI) issued in October 2017. Similarly, the requirements of Condition L4.3 of EPL 20611 state that noise limits do not apply under the following meteorological conditions:

- wind speeds greater than 3 m/s at 10 m above ground level;
- stability category F temperature inversion conditions and wind speeds greater than 2 m/s at 10 m above ground level; or
- stability category G temperature inversion conditions.

2.6 Additional requirements

Monitoring and reporting have been done in accordance with the NPfI and the NSW EPA 'Approved methods for the measurement and analysis of environmental noise in NSW' (Approved Methods) issued in January 2022.

2.7 Very noise-enhancing meteorological conditions

In accordance with the approved methods, noise monitoring for the site is scheduled to occur during forecasted meteorological conditions where noise limits in Table 2.1 will be applicable. However, in cases where actual meteorological conditions do not align with forecasts and noise limits are subsequently not directly applicable, it is the expectation of regulators that noise impact still be managed.

The NPfl states that:

Noise limits derived for consents and licences will apply under the meteorological conditions used in the environmental assessment process, that is, standard or noise-enhancing meteorological conditions. For 'very noise-enhancing meteorological conditions' ... a limit is set based on the limit derived under standard or noise-enhancing conditions (whichever is adopted in the assessment) plus 5 dB. In this way a development is subject to noise limits under all meteorological conditions.

Therefore, if monthly noise monitoring occurs during meteorological conditions outside of those specified in Section 2.5, site limits will be adjusted based on Table 2.1 plus 5 dB.

3 Methodology

3.1 Overview

Attended environmental noise monitoring was done in general accordance with Australian Standard AS1055 'Acoustics, Description and Measurement of Environmental Noise' and relevant EPA requirements. Meteorological data was obtained from the KEQ on-site meteorological station which allowed correlation of atmospheric parameters with measured noise levels.

3.2 Attended noise monitoring

During this survey, attended noise monitoring was conducted during the morning shoulder, day and evening periods at each location. The duration of each measurement was 15 minutes. Atmospheric conditions were measured at each monitoring location.

Measured sound levels from various sources were noted during each measurement, and particular attention was paid to the extent of the site's contribution (if any) to measured levels. At each monitoring location, the site-only $L_{Aeq,15minute}$ and L_{Amax} were measured directly or determined by other methods detailed in Section 7.1 of the NPfI.

The terms 'Inaudible' (IA) or 'Not Measurable' (NM) may be used in this report. When site noise is noted as IA, it was inaudible at the monitoring location. When site noise is noted as NM, this means it was audible but could not be quantified. All results noted as IA or NM in this report were due to one or more of the following:

- Site noise levels were very low, typically more than 10 dB below the measured background (L_{A90}), and unlikely to be noticed.
- Site noise levels were masked by more dominant sources that are characteristic of the environment (such as breeze in foliage or continuous road traffic noise) that cannot be eliminated by monitoring at an alternate or intermediate location.
- It was not feasible or reasonable to employ methods, such as to move closer and back calculate. Cases may include rough terrain preventing closer measurement, addition/removal of significant source to receiver shielding caused by moving closer, and meteorological conditions where back calculation may not be accurate.

If exact noise levels from site could not be established due to masking by other noise sources in a similar frequency range but were determined to be at least 5 dB lower than relevant limits, then a maximum estimate may be provided. This is expressed as a 'less than' quantity, such as <20 dB or <30 dB.

For this assessment, the measured L_{Amax} has been used as a conservative estimate of $L_{A1,1minute}$. The EPA accepts sleep disturbance analysis based on either the $L_{A1,1minute}$ or L_{Amax} metrics, with the L_{Amax} representing a more conservative assessment of site noise emissions.

3.3 Meteorological data

Meteorological data for the monitoring period was sourced from the Karuah East Quarry on-site meteorological station (the site AWS) to determine the applicability of criteria in accordance with the EPL and PA.

3.4 Modifying factors

All measurements were evaluated for potential modifying factors in accordance with the NPfI. Assessment of modifying factors is undertaken if the site was audible and directly quantifiable. If applicable, modifying factor penalties have been reported and added to measured site-only L_{Aeq} noise levels.

Low-frequency modifying factor penalties have only been applied to site-only L_{Aeq} levels if the site was the only contributing low-frequency noise source. Specific methodology for assessment of each modifying factor is outlined in Fact Sheet C of the NPfI.

3.5 Site operations

As required by Condition R4.3(a) of the EPL, the operations occurring at the time of monitoring are summarised per period below:

- Day
 - Routine quarry operations in the quarry pit
 - Routine plant processing operations
 - Routine material transport from the quarry pit to the processing plant and product stockpile areas
 - Routine product loading and dispatch to road trucks
- Evening
 - Routine material transport from the processing plant to product stockpile areas
 - Routine maintenance activities of plant and equipment
- Morning shoulder
 - Routine maintenance activities of plant and equipment
 - Routine product loading and dispatch to road trucks

3.6 Instrumentation

The equipment used to measure environmental noise levels is detailed in Table 3.1. Calibration certificates are provided in Appendix C.

Table 3.1 Attended noise monitoring equipment

Item	Serial number	Calibration due date	Relevant standard
Brüel & Kjær 2250 sound level meter	2759405	2/2/2024	IEC 61672-1:2002
Svantek SV-36 calibrator	79952	29/9/2024	IEC 60942

4 **Results**

4.1 Total measured noise levels and atmospheric conditions

Overall noise levels measured at each location during attended measurements are provided in Table 4.1.

Location	Start date and time	L _{Amax} dB	L _{A1} dB	L _{A10} dB	L _{Aeq} dB	L _{A50} dB	L _{A90} dB	L _{Amin} dB
A	10/08/2023 16:11	108	85	57	77	54	51	46
В	10/08/2023 16:28	76	74	69	66	65	60	54
F	10/08/2023 16:46	93	65	51	60	48	46	42
G	10/08/2023 17:09	63	50	38	41	35	33	31
н	10/08/2023 17:28	64	47	40	38	33	31	28
н	10/08/2023 18:00	78	49	37	46	34	33	31
G	10/08/2023 18:17	53	47	40	39	37	36	32
F	10/08/2023 18:40	83	59	55	55	52	49	44
В	10/08/2023 18:59	76	74	68	65	63	57	51
A	10/08/2023 19:16	68	61	57	55	53	50	46
A	11/08/2023 5:00	77	75	69	65	59	54	48
В	11/08/2023 5:17	79	75	68	65	60	55	48
F	11/08/2023 5:35	81	64	58	57	54	51	45
G	11/08/2023 5:59	68	58	46	46	43	40	37
Н	11/08/2023 6:16	65	60	47	47	43	41	38

Table 4.1Total measured noise levels – Q3 20231

Notes: 1. Levels in this table are not necessarily the result of activity at the site.

Atmospheric condition data measured by the operator during each measurement using a hand-held weather meter is shown in Table 4.2. The wind speed, direction and temperature were measured at approximately 1.5 metres above ground. Attended noise monitoring is not done during rain, hail, or wind speeds above 5 m/s at microphone height.

Location	Start date and time	Temperature °C	Wind speed m/s	Wind direction ^o Magnetic north ¹	Cloud cover 1/8s
A	10/08/2023 16:11	22.5	<0.5	-	1
В	10/08/2023 16:28	22.8	<0.5	-	1
F	10/08/2023 16:46	21.6	0.9	0	1
G	10/08/2023 17:09	20.1	<0.5	-	2
Н	10/08/2023 17:28	19.5	<0.5	-	2
Н	10/08/2023 18:00	18.6	<0.5	-	2
G	10/08/2023 18:17	18.1	<0.5	-	2
F	10/08/2023 18:40	17.7	<0.5	-	2
В	10/08/2023 18:59	17.5	<0.5	-	2
A	10/08/2023 19:16	17.1	<0.5	-	2
A	11/08/2023 5:00	12.5	<0.5	-	0
В	11/08/2023 5:17	12.8	<0.5	-	0
F	11/08/2023 5:35	13.2	<0.5	-	0
G	11/08/2023 5:59	13.3	<0.5	-	0
Н	11/08/2023 6:16	13.4	<0.5	_	0

Table 4.2 Measured atmospheric conditions – Q3 2023

Notes: 1. "-" indicates calm conditions at the monitoring location.

4.2 Site only noise levels

4.2.1 Modifying factors

No modifying factors were applicable during the survey, as defined in the NPfl.

4.2.2 Monitoring results

Table 4.3 provides site noise levels in the absence of other sources, where possible, and includes weather data obtained from the site AWS. Limits are applicable if weather conditions were within specified parameters during each measurement.

Table 4.3Site noise levels and limits – Q3 2023

Location	Start Date and Time (Period)	Wi	ind	Stability Class	Very enhancing? ¹	Limit, d	В	Site level,	dB ²	Exceedanc	e, dB
		Speed m/s	Direction ⁴			L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}
A	10/08/2023 16:11 (D)	1.4	313	А	Ν	42	N/A	NM	N/A	No	N/A
В	10/08/2023 16:28 (D)	1.2	273	А	Ν	40	N/A	IA	N/A	No	N/A
F	10/08/2023 16:46 (D)	1.0	223	А	Ν	40	N/A	IA	N/A	No	N/A
G	10/08/2023 17:09 (D)	0.3	189	А	Ν	43	N/A	<35	N/A	No	N/A
Н	10/08/2023 17:28 (D)	0.4	163	А	Ν	44	N/A	26	N/A	No	N/A
Н	10/08/2023 18:00 (E)	0.5	96	F	Ν	46	N/A	IA	N/A	No	N/A
G	10/08/2023 18:17 (E)	0.4	124	F	Ν	39	N/A	IA	N/A	No	N/A
F	10/08/2023 18:40 (E)	0.4	89	F	Ν	35	N/A	IA	N/A	No	N/A
В	10/08/2023 18:59 (E)	0.3	145	F	Ν	40	N/A	IA	N/A	No	N/A
А	10/08/2023 19:16 (E)	0.3	111	F	Ν	40	N/A	IA	N/A	No	N/A

Table 4.3Site noise levels and limits – Q3 2023

Location	Start Date and Time (Period)	Wi	nd	Stability Class	Very enhancing? ¹	Limit, d	В	Site level,	, dB ²	Exceedanc	e, dB
		Speed m/s	Direction ⁴			L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}
А	11/08/2023 5:00 (MS)	0.3	189	F	Ν	35	52	IA	IA	No	No
В	11/08/2023 5:17 (MS)	0.2	89	F	Ν	35	52	IA	IA	No	No
F	11/08/2023 5:35 (MS)	0.1	84	F	Ν	35	52	IA	IA	No	No
G	11/08/2023 5:59 (MS)	0.1	152	F	Ν	35	52	IA	IA	No	No
Н	11/08/2023 6:16 (MS)	0.2	150	F	Ν	35	52	IA	IA	No	No

Notes:1. Noise limits are adjusted by +5 dB during 'very noise-enhancing meteorological conditions' in accordance with the NPfl.2. Site-only LAeq,15minute, includes modifying factor penalties if applicable.

3. Degrees magnetic north, "-" indicates calm conditions.

4. MS = Morning Shoulder period; D = Day period; E = Evening period.

5 Mitigation and management

5.1 Proposed management actions

EPL Condition R4.3(c) requires details of any management actions taken within the monitoring period to address any exceedances of the limits. As there were no exceedances, no management actions were required.

6 Summary

EMM Consulting Pty Ltd (EMM) was engaged by Karuah East Quarry Pty Limited to conduct a quarterly noise survey of operations at the site. The survey purpose was to quantify the acoustic environment and compare site noise levels against specified PA and EPL noise limits.

Attended environmental noise monitoring described in this report was done during the morning shoulder, day and evening periods on Thursday 10 and Friday 11 August 2023 at five monitoring locations.

Noise levels from the site complied with relevant limits at all monitoring locations during the Q3 2023 survey.

Appendix A

Noise perception and examples




A.1 Noise levels

Table A.1 indicates how an average person perceives changes in noise level. Examples of common noise levels are provided in Figure A.1.

Table A.1Perceived change in noise

Change in sound pressure level (dB)	Perceived change in noise
up to 2	Not perceptible
3	Just perceptible
5	Noticeable difference
10	Twice (or half) as loud
15	Large change
20	Four times (or a quarter) as loud





Appendix B Regulator documents



B.1 Project approval

SCHEDULE 3 ENVIRONMENTAL PERFORMANCE CONDITIONS

IDENTIFICATION OF APPROVED LIMITS OF EXTRACTION

- 1. The Applicant shall, prior to carrying out quarrying operations on the site:
 - (a) engage a registered surveyor to mark out the boundaries of the approved limits of extraction within the Extraction Area; and
 - (b) submit a survey plan of the extraction boundaries,
 - to the satisfaction of the Planning Secretary.
- 2. The Applicant must ensure that the extraction boundaries are clearly marked at all times while quarrying operations are being carried out, in a manner that allows the limits of extraction to be clearly identified.

NOISE

Operational Noise Criteria

3. Except for the carrying out of construction works, the Applicant must ensure that the operational noise generated by the development does not exceed the criteria in Table 2 at any residence^a on privately-owned land.

Noise Assessment Location ^a	Morning Shoulder LAeq (15 min)	Morning Shoulder L _{Amax}	Day L _{Aeq (15 min)}	Evening L _{Aeq (15 min)}
А	35	52	42	40
В	35	52	40	40
G	35	52	43	39
Н	35	52	44	46
I	35	52	40	37
All other residences	35	52	40	35

Table 2: Operational noise criteria dB

^a Noise Assessment Locations referred to in Table 2 are shown in Appendix 2.

Noise generated by the development must be monitored and measured in accordance with the relevant procedures and modifications (including certain meteorological conditions) of the NPfI.

3A. The noise criteria in Table 2 do not apply if the Applicant has an agreement with the owner/s of the relevant residence or land to exceed the noise criteria, and the Applicant has advised the Department in writing of the terms of this agreement.

Road Traffic Noise Criteria

4. The Applicant must take all reasonable and feasible measures to ensure that the traffic noise generated by the development does not cause additional exceedances of the criteria in Table 3 at any residence on privately-owned land.

Table 3: Road traffic noise criteria

Road	Criteria (Dayª)
Pacific Highway	60 dB(A) LAeq (15 hour)
Local roads	55 dB(A) L _{Aeq (1 hour)}

^a Day is the period from 7 am to 10 pm every day in accordance with the EPA's NSW Road Noise Policy (2011).

5. Deleted

Noise Operating Conditions

- 6. The Applicant must:
 - (a) take all reasonable steps to minimise noise from construction and operational activities, including low frequency noise and other audible characteristics, associated with the development;
 - (b) implement reasonable and feasible noise attenuation measures on all plant and equipment that will operate in noise sensitive areas;
 - (c) operate a comprehensive noise management system commensurate with the risk of impact;
 - (d) take all reasonable steps to minimise the noise impacts of the development during noiseenhancing meteorological conditions when the noise criteria in this consent do not apply (see NPfI);
 - (e) carry out quarterly attended noise monitoring (unless otherwise agreed by the Planning Secretary) to determine whether the development is complying with the relevant conditions of this consent; and
 - (f) regularly assess the noise monitoring data and modify or stop operations on the site to ensure compliance with the relevant conditions of this consent.

Noise Management Plan

- 7. The Applicant must prepare a Noise Management Plan for the development to the satisfaction of the Planning Secretary. This plan must:
 - (a) be prepared by a suitably qualified and experienced person/s whose appointment has been endorsed by the Planning Secretary;
 - (b) be prepared in consultation with the EPA;
 - (c) describe the measures to be implemented to ensure:
 - (i) compliance with the noise criteria and operating conditions in this consent;
 - (ii) best practice management is being employed;
 - (iii) noise impacts of the development are minimised during noise-enhancing meteorological conditions when the noise criteria in this consent do not apply (see NPfI);
 - (d) describe the noise management system in detail; and
 - (e) include a monitoring program that:
 - (i) is capable of evaluating the performance of the development;
 - (ii) monitors noise at the nearest and/or most affected residences;
 - (iii) adequately supports the noise management system;
 - (iv) includes a protocol for distinguishing noise emissions of the development from any neighbouring developments; and
 - includes a protocol for identifying any noise-related exceedance, incident or noncompliance and for notifying the Department and relevant stakeholders of any such event.
- 7A. The Applicant must implement the plan as approved by the Planning Secretary.

BLASTING

Blasting Criteria

8. The Applicant must ensure that blasting on the site does not cause exceedances of the criteria in Table 5.

B.2 Environmental protection licence

Licence - 20611

L3 Waste

L3.1 The licensee must not cause, permit or allow any waste generated outside the premises to be received at the premises for storage, treatment, processing, reprocessing or disposal or any waste generated at the premises to be disposed of at the premises, except as expressly permitted by the licence.

L4 Noise limits

L4.1 Noise generated at the premises must not exceed the noise limits in the table below. The locations referred to in the table below are indicated in Table 2: Operational Noise Criteria, and Figure 1 of the document titled Project Approval 09_0175 Modification 9 (MOD 9) Department of Planning, Industry& Environment - which has been filed on EPA file Doc22/715570-1.

Noise Assesment Location	Morning Shoulder LAeq(15 min)	Morning shoulder LAmax	Day LAeq (15 min)	Evening LAeq (15 min)
A (74 Mill Hill Close, Karuah, Lot 100 DP 1028885)	35	52	42	40
B (64 Mill Hill Close, Karuah, Lot 3 DP785172)	35	52	40	40
G (2 Halloran Road, North Arm Cove Lot 1 DP1032636)	35	52	43	39
H (21 Halloran Road, North Arm Cove Lot 10 DP1032636)	35	52	44	46
l (83 Halloran Road, North Arm Cove Lot 12 DP1032636)	35	52	40	37
All other residences	35	52	40	35

L4.2 Noise limit definitions - For the purpose of the table at L4.1, the following definitions apply: Day is defined as the period from 7am to 6pm Monday to Saturday and 8am to 6pm Sunday and Public Holidays;

Morning Shoulder is defined as the period from 5:00am to 7:00am Monday to Saturday; Evening is defined as the period from 6:00pm to 10:00pm Monday to Saturday.

- L4.3 The noise limits set out in this licence apply under all meteorological conditions except for the following:
 - a) Wind speed greater than 3 metres/second at 10 metres above ground level; or

b) Stability category F temperature inversion conditions and wind speeds greater than 2 metres/second at 10 metres above ground level; or

NSU Manual in the second second

Licence - 20611

c) Stability category G temperature inversion conditions.

L4.4 Determining Compliance

To determine compliance with the noise limits set out in the table above, the licensee must locate monitoring equipment:

a) within 30 metres of a dwelling façade (but not closer than 3 metres) where any dwelling on the property is situated more than 30 metres from the property boundary that is closest to the premises;

b) approximately on the boundary where any dwelling is situated 30 metres or less from the property boundary that is closest to the premises;

c) at the most affected point at a location where there is no dwelling at the location; and

d) within approximately 50 metres of the boundary of a national park or nature reserve.

Note: A non-compliance of the Noise Limits table will still occur where noise generated from the premises in excess of the appropriate limit is measured:

i) at a location other than an area prescribed in part (a) and part (b); and/or

ii) at a point other than the most affected point at a location.

L4.5 For the purposes of determining the noise generated at the premises the modification factors in Fact Sheet C of the EPA's "Noise Policy for Industry" must be applied, as appropriate, to the noise levels measured by the noise monitoring equipment.

L5 Blasting

- L5.1 Blasting in or on the premises must only be carried out between the hours of 9:00 am and 4:00 pm Monday to Friday. No blasting is permitted on Saturdays, Sundays or public holidays. Blasting outside of the hours specified in this condition can only take place with the written approval of the EPA.
- L5.2 Blasting is not permitted simultaneously with adjacent quarry(s).
- L5.3 The airblast overpressure level from blasting operations in or on the premises must not exceed:
 a) 115 dB (Lin Peak) for more than 5% of the total number of blasts during each reporting period; and
 b) 120 dB (Lin Peak) at any time,
 at monitoring point 11 detailed in Condition P1.4.
- L5.4 The ground vibration peak particle velocity from blasting operations carried out in or on the premises must not exceed:

a) 5 mm/second for more than 5% of the total number of blasts during each reporting period; and

b) 10 mm/second at any time,

at monitoring point 11 detailed in Condition P1.4.

- L5.5 Error margins associated with any monitoring equipment used to measure airblast overpressure or peak particle velocity are not to be taken into account in determing whether or not the limit has been exceeded.
- L5.6 The airblast overpressure and ground vibration levels in the conditions above do not apply at noise sensitive locations that are owned by the licensee or subject to a private agreement, relating to airblast overpressure and ground vibration levels, between the licensee and land owner.

USN SURVEY



Licence - 20611

a) the date and time of the complaint;

b) the method by which the complaint was made;

c) any personal details of the complainant which were provided by the complainant or, if no such details were provided, a note to that effect;

d) the nature of the complaint;

e) the action taken by the licensee in relation to the complaint, including any follow-up contact with the complainant; and

f) if no action was taken by the licensee, the reasons why no action was taken.

- M5.3 The record of a complaint must be kept for at least 4 years after the complaint was made.
- M5.4 The record must be produced to any authorised officer of the EPA who asks to see them.

M6 Telephone complaints line

- M6.1 The licensee must operate during its operating hours a telephone complaints line for the purpose of receiving any complaints from members of the public in relation to activities conducted at the premises or by the vehicle or mobile plant, unless otherwise specified in the licence.
- M6.2 The licensee must notify the public of the complaints line telephone number and the fact that it is a complaints line so that the impacted community knows how to make a complaint.
- M6.3 The preceding two conditions do not apply until 1 month after the date of the issue of this licence.

M7 Blasting

M7.1 To determine complaince with Blast Limit conditions of this licence:

a) Airblast overpressure and ground vibration levels must be measured and electronically recorded for monitoring point 11 for the parameters specified in Column 1 of the table below; and
b) The licensee must use the units of measure, sampling method, and sample at the frequency specified opposite in the other columns.

Parameter	Units of Measure	Frequency	Sampling Method
Airblast Overpressure	Decibels (Linear Peak	All blasts	Australian Standard AS 2187.2-2006
Ground Vibration Peak Particle Velocity	millimetres/second	All blasts	Australian Standard AS 2187.2-2006

M8 Noise monitoring

- M8.1 To assess compliance with the noise limits for this premises attended noise monitoring must be undertaken in accordance with all noise conditions and:
 - a) during a period of normal quarry operations;
 - b) at each one of the locations listed in the noise limits table of this licence;



Licence - 20611

c) occur quarterly in the reporting period;

d) occur during each day period as defined in the NSW Noise Policy for Industry.

Note: Quarterly attended noise monitoring must be completed (unless otherwise agreed by the Planning Secretary) to determine whether the development is complying with the relevant conditions of this consent. The frequency of noise monitoring will be reviewed, upon request.

6 Reporting Conditions

R1 Annual return documents

- R1.1 The licensee must complete and supply to the EPA an Annual Return in the approved form comprising:
 - 1. a Statement of Compliance,
 - 2. a Monitoring and Complaints Summary,
 - 3. a Statement of Compliance Licence Conditions,
 - 4. a Statement of Compliance Load based Fee,
 - 5. a Statement of Compliance Requirement to Prepare Pollution Incident Response Management Plan,
 - 6. a Statement of Compliance Requirement to Publish Pollution Monitoring Data; and
 - 7. a Statement of Compliance Environmental Management Systems and Practices.

At the end of each reporting period, the EPA will provide to the licensee notification that the Annual Return is due.

- R1.2 An Annual Return must be prepared in respect of each reporting period, except as provided below.
- Note: The term "reporting period" is defined in the dictionary at the end of this licence. Do not complete the Annual Return until after the end of the reporting period.
- R1.3 Where this licence is transferred from the licensee to a new licensee:

a) the transferring licensee must prepare an Annual Return for the period commencing on the first day of the reporting period and ending on the date the application for the transfer of the licence to the new licensee is granted; and

b) the new licensee must prepare an Annual Return for the period commencing on the date the application for the transfer of the licence is granted and ending on the last day of the reporting period.

- Note: An application to transfer a licence must be made in the approved form for this purpose.
- R1.4 Where this licence is surrendered by the licensee or revoked by the EPA or Minister, the licensee must prepare an Annual Return in respect of the period commencing on the first day of the reporting period and ending on:

a) in relation to the surrender of a licence - the date when notice in writing of approval of the surrender is given; or

b) in relation to the revocation of the licence - the date from which notice revoking the licence operates.

R1.5 The Annual Return for the reporting period must be supplied to the EPA via eConnect EPA or by registered

B.3 Noise management plan

5 Noise limits

5.1 Operational noise

Condition 3 of Schedule 3 of PA 09_0175 provides the operational noise limits for KEQ. These are reproduced in Table 5.1.

Table 5.1 Operational noise criteria (dB) from Table 2 of PA 09_0175

Noise Assessment Location ¹	Morning Shoulder L _{Aeq(15 minute)}	Morning Shoulder L _{Amax}	Day L _{Aeq(15 minute)}	Evening L _{Aeq(15 minute)}
A	35	52	42	40
В	35	52	40	40
G	35	52	43	39
Н	35	52	44	46
I	35	52	40	37
All other residences	35	52	40	35

Noise assessment locations are shown in Figure 3.1.

Noise generated by the development must be monitored and measured in accordance with the relevant procedures and exemptions (including certain meteorological conditions) of the NPfI (EPA 2017).

The noise limits provided in Table 5.1 apply under standard and noise-enhancing meteorological conditions (as defined in the NPfI) determined by monitoring at the relevant weather station. In accordance with Condition L4.3 of EPL 20611 and consistent with Condition 3 of Schedule 3 of PA 09_0175 the noise limits provided in Table 5.1 apply under all meteorological conditions except for the following:

- wind speeds greater than 3m/s at 10m above ground level;
- stability category F temperature inversion conditions and wind speeds greater then 2m/s at 10m above ground level; or
- stability category G temperature inversion conditions.

In accordance with Fact Sheet D of the NPfI, for 'very noise enhancing meteorological conditions' the applicable noise limit is set at 5dB above those provided in Table 5.1.

Noise limits do not apply if Karuah East has an agreement with the owner/s of the relevant residence or land to exceed the noise criteria, and Karuah East has advised the Department in writing of the terms of this agreement.

5.2 Road traffic noise

Condition 4 of Schedule 3 of PA 09_0175 states that all reasonable and feasible measures must be taken to ensure that the traffic generated by KEQ does not cause additional exceedances of the criteria provided in Table 5.2 at any residence on privately-owned land.

Appendix C Calibration certificates



CERTIFICATE OF CALIBRATION

CERTIFICATE NO: C33872

EQUIPMENT TESTED: Sound Level Calibrator

	e No: wner: med:	L3, 17 Newca Measu	Seria Consulting Pt 5 Scott Stree astle, NSW 23	y Ltd t 300 essure le	79952 vel, Frequency Passed.	& Distortion
Parameter	Pre- Adj	Adj Y/N			Frequency (Hz)	THD&N (%)
Level1:	NA	N	94.09	dB	1000.00 Hz	1.12 %
Level2:	NA	N	114.06	dB	1000.00 Hz	0.71 %
Unce	ertainty	1	±0.11	dB	±0.05%	±0.20 %
Uncertainty (at	95% c.l	.) k=2	enerth Mitchen	E. Mar	al sociation in	CO repairs
CONDITION OF Ambient Pre Temper Relative Hun	essure ature	1004 23	hPa ±1 hPa °C ±1º C % ±5%		ate of Receipt : of Calibration : Date of Issue :	26/09/2022 29/09/2022 29/09/2022
Acu-Vib Procee Checked b	dure:		2 (Calibrators) lethod: AS IEC Authoris Signatu	SED	A	ein Soe

Accredited for compliance with ISO/IEC 17025 - Calibration

Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part. The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.




WORLD RECOGNIBED ACCREDITATION Accredited Lab No. 9262 Acoustic and Vibration Measurements

Head Office & Calibration Laboratory Unit 14, 22 Hudson Ave. Castle Hill NSW 2154 (02) 9680 8133 www.acu-vib.com.au

Acu-Vib Electronics

CALIBRATIONS SALES RENTALS REPAIRS

Page 1 of 2 Calibration Certificate AVCERT02.1 Rev.2.0 14.04.2021



CERTIFICATE NO: SLM31670

EQUIPMENT TESTED: Sound Level Meter

Manufacturer: B&K Type No: 2250 Mic. Type: 4189 Pre-Amp. Type: ZC0032

Serial No: 2759405 Serial No: 2983733 Serial No: 22666

Filter Type: 1/3 Octave

Owner: EMM Consulting Level 3, 175 Scott Street Newcastle, NSW 2300

Tests Performed: IEC 61672-3:2013 & IEC 61260-3:2016

Comments: All Test passed for Class 1. (See overleaf for details) **CONDITIONS OF TEST:**

Ambient Pressure Temperature **Relative Humidity**

992 hPa ±1 hPa 26 °C ±1° C 48 % ±5%

Date of Receipt : 02/02/2022 Date of Calibration: 02/02/2022 Date of Issue : 03/02/2022

Test No: F031671

Acu-Vib Test Procedure: AVP10 (SLM) & AVP06 (Filters) **CHECKED BY:**

AUTHORISED SIGNATURE:

Jack Kielt

Accredited for compliance with ISO/IEC 17025 - Calibration

Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part. The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.



REDITATION Accredited Lab No. 9262 Acoustic and Vibration

Measurements

Acu-Vib Electronics CALIBRATIONS SALES RENTALS REPAIRS

Head Office & Calibration Laboratory Unit 14, 22 Hudson Ave. Castle Hill NSW 2154 (02) 9680 8133 www.acu-vib.com.au

Page 1 of 2 Calibration Certificate AVCERT10.14 Rev.2.0 14/04/2021

Australia

SYDNEY Ground floor 20 Chandos Street St Leonards NSW 2065

T 02 9493 9500 **NEWCASTLE** Level 3 175 Scott Street Newcastle NSW 2300

Newcastle NSW 2300 T 02 4907 4800

BRISBANE Level 1 87 Wickham Terrace Spring Hill QLD 4000 T 07 3648 1200

CANBERRA

Suite 2.04 Level 2 15 London Circuit Canberra City ACT 2601 ADELAIDE Level 4 74 Pirie Street Adelaide SA 5000 T 08 8232 2253

MELBOURNE

Suite 8.03 Level 8 454 Collins Street Melbourne VIC 3000 T 03 9993 1900

PERTH

Suite 9.02 Level 9 109 St Georges Terrace Perth WA 6000 T 08 6430 4800

Canada

TORONTO 2345 Yonge Street Suite 300 Toronto ON M4P 2E5 T 647 467 1605

VANCOUVER 60 W 6th Ave Vancouver BC V5Y 1K1 T 604 999 8297



linkedin.com/company/emm-consulting-pty-limited



emmconsulting.com.au



Karuah East Quarry

Quarterly Attended Noise Monitoring - Q4 2023

Prepared for Karuah East Quarry Pty Limited

December 2023

Karuah East Quarry

Quarterly Attended Noise Monitoring - Q4 2023

Karuah East Quarry Pty Limited

E230083 RP5

December 2023

Version	Date	Prepared by	Reviewed by	Comments
1	6 December 2023	Lucas Adamson	Najah Ishac	Draft
2	7 December 2023	Lucas Adamson	Najah Ishac	Final

Approved by

Vajab that

Najah Ishac Director 7 December 2023

Level 3 175 Scott Street Newcastle NSW 2300

This report has been prepared in accordance with the brief provided by Karuah East Quarry Pty Limited and, in its preparation, EMM has relied upon the information collected at the times and under the conditions specified in this report. All findings, conclusions or recommendations contained in this report are based on those aforementioned circumstances. The contents of this report are private and confidential. This report is only for Karuah East Quarry Pty Limited's use in accordance with its agreement with EMM and is not to be relied on by or made available to any other party without EMM's prior written consent. Except as permitted by the *Copyright Act 1968* (Cth) and only to the extent incapable of exclusion, any other use (including use or reproduction of this report for resale or other commercial purposes) is prohibited without EMM's prior written consent. Except where expressly agreed to by EMM in writing, and to the extent permitted by law, EMM will have no liability (and assumes no duty of care) to any person in relation to this document, other than to Karuah East Quarry Pty Limited (and subject to the terms of EMM's agreement with Karuah East Quarry Pty Limited).

© EMM Consulting Pty Ltd, Ground Floor Suite 01, 20 Chandos Street, St Leonards NSW 2065, December 2023.

TABLE OF CONTENTS

1	Introd	duction	1
	1.1	Background	1
	1.2	Attended monitoring locations	1
	1.3	Terminology and abbreviations	3
2	Noise	limits	4
	2.1	Project approval	4
	2.2	Environment protection licence	4
	2.3	Noise management plan	4
	2.4	Noise limits	4
	2.5	Meteorological conditions	4
	2.6	Additional requirements	5
	2.7	Very noise-enhancing meteorological conditions	5
3	Meth	odology	6
	3.1	Overview	6
	3.2	Attended noise monitoring	6
	3.3	Meteorological data	6
	3.4	Modifying factors	7
	3.5	Site operations	7
	3.6	Instrumentation	7
4	Resul	ts	8
	4.1	Total measured noise levels and atmospheric conditions	8
	4.2	Site only noise levels	9
5	Mitig	ation and management	12
	5.1	Proposed management actions	12
6	Sumn	nary	13
Ар	pendice	25	
Ар	oendix A	Noise perception and examples	A.1
Ар	oendix B	Regulator documents	B.1
Ар	pendix C	Calibration certificates	C.1
Tal	oles		
Tak	ole 1.1	Attended noise monitoring locations	1

Table 1.2	Terminology and abbreviations	3
Table 2.1	Noise impact limits, dB	4
Table 3.1	Attended noise monitoring equipment	7
Table 4.1	Total measured noise levels – Q4 2023 ¹	8
Table 4.2	Measured atmospheric conditions – Q4 2023	9
Table 4.3	Site noise levels and limits – Q4 2023	10
Table A.1	Perceived change in noise	A.2
Figures		

Figure 1.1	Attended noise monitoring locations	2
Figure A.1	Common noise levels	A.2

1 Introduction

1.1 Background

EMM Consulting Pty Ltd (EMM) was engaged by Karuah East Quarry Pty Limited to conduct a quarterly noise survey of operations at Karuah East Quarry (KEQ, the site) located at Blue Rock Close, Karuah NSW. The survey purpose was to quantify the acoustic environment and compare site noise levels against specified limits.

Attended environmental noise monitoring described in this report was done during morning shoulder, day and evening periods on Friday 24 and Thursday 30 November 2023 at five monitoring locations.


1.2 Attended monitoring locations

Site monitoring locations are detailed in Table 1.1 and shown on Figure 1.1. It should be noted that Figure 1.1 shows actual monitoring positions, not necessarily the location of residences.

Table 1.1 Attended noise monitoring locations

Location	Description/address	Coordinates (MGA56)		
descriptor/ID		Easting	Northing	
А	Private residence - 74 Mill Hill Close, Karuah	406623	6388704	
В	Private residence - 64 Mill Hill Close, Karuah	406405	6388859	
F	Private residence - 1714 The Branch Lane, Karuah	405639	6389782	
G	Private residence - 2 Halloran Road, North Arm Cove	405629	6389766	
Н	Private residence - 21 Halloran Road, North Arm Cove	407795	6389868	





KEY

- Site boundary
- A ttended noise monitoring location
- Approved disturbance area
- - Minor road
 - Vehicular track
- Cadastral boundary
- Waterbody
- NPWS reserve
- State forest

Attended noise monitoring locations

Karuah East Quarry Quarterly attended noise monitoring Figure 1.1



1.3 Terminology and abbreviations

Some definitions of terms and abbreviations which may be used in this report are provided in Table 1.2.

Table 1.2 Terminology and abbreviations

dB(A) Noise level measurement units are decibels (dB). The "A" weighting scale is used to humans hear noise. LAmax The maximum root mean squared A-weighted noise level over a time period. LA1 The A-weighted noise level which is exceeded for 1 per cent of the time. LA1,1minute The A-weighted noise level which is exceeded for 1 per cent of the specified time p LA10 The A-weighted noise level which is exceeded for 10 per cent of the time. LAeq The energy average A-weighted noise level. LA50 The A-weighted noise level which is exceeded for 50 per cent of the time, also the r during a measurement period. LA90 The A-weighted noise level exceeded for 90 per cent of the time, also referred to as level and commonly used to derive noise limits. LAmin The minimum A-weighted noise level over a time period. LCeq The energy average C-weighted noise energy during a measurement period. The "C to take into account low-frequency components of noise within the audibility range SPL Sound pressure level. Fluctuations in pressure measured as 10 times a logarithmic s pressure being 20 micropascals.	
LA1 The A-weighted noise level which is exceeded for 1 per cent of the time. LA1,1minute The A-weighted noise level which is exceeded for 1 per cent of the specified time p LA10 The A-weighted noise level which is exceeded for 10 per cent of the time. LAeq The energy average A-weighted noise level. LA50 The A-weighted noise level which is exceeded for 50 per cent of the time, also the r LA90 The A-weighted noise level exceeded for 90 per cent of the time, also referred to as level and commonly used to derive noise limits. LAmin The minimum A-weighted noise level over a time period. LCeq The energy average C-weighted noise energy during a measurement period. The 'C to take into account low-frequency components of noise within the audibility range SPL Sound pressure level. Fluctuations in pressure measured as 10 times a logarithmic s pressure being 20 micropascals.	approximate how
LA1,1minuteThe A-weighted noise level which is exceeded for 1 per cent of the specified time pLA10The A-weighted noise level which is exceeded for 10 per cent of the time.LAeqThe energy average A-weighted noise level.LA50The A-weighted noise level which is exceeded for 50 per cent of the time, also the r during a measurement period.LA90The A-weighted noise level exceeded for 90 per cent of the time, also referred to a level and commonly used to derive noise limits.LAminThe minimum A-weighted noise level over a time period.LCeqThe energy average C-weighted noise energy during a measurement period. The "O to take into account low-frequency components of noise within the audibility rangeSPLSound pressure level. Fluctuations in pressure measured as 10 times a logarithmic s pressure being 20 micropascals.	
LA10The A-weighted noise level which is exceeded for 10 per cent of the time.LAeqThe energy average A-weighted noise level.LA50The A-weighted noise level which is exceeded for 50 per cent of the time, also the r during a measurement period.LA90The A-weighted noise level exceeded for 90 per cent of the time, also referred to as level and commonly used to derive noise limits.LAminThe minimum A-weighted noise level over a time period.LCeqThe energy average C-weighted noise energy during a measurement period. The "C to take into account low-frequency components of noise within the audibility rangeSPLSound pressure level. Fluctuations in pressure measured as 10 times a logarithmic s pressure being 20 micropascals.	
LAeqThe energy average A-weighted noise level.LA50The A-weighted noise level which is exceeded for 50 per cent of the time, also the r during a measurement period.LA90The A-weighted noise level exceeded for 90 per cent of the time, also referred to as level and commonly used to derive noise limits.LAminThe minimum A-weighted noise level over a time period.LCeqThe energy average C-weighted noise energy during a measurement period. The "C to take into account low-frequency components of noise within the audibility rangeSPLSound pressure level. Fluctuations in pressure measured as 10 times a logarithmic s pressure being 20 micropascals.	eriod of 1 minute.
LA50The A-weighted noise level which is exceeded for 50 per cent of the time, also the r during a measurement period.LA90The A-weighted noise level exceeded for 90 per cent of the time, also referred to as level and commonly used to derive noise limits.LAminThe minimum A-weighted noise level over a time period.LCeqThe energy average C-weighted noise energy during a measurement period. The "C to take into account low-frequency components of noise within the audibility rangeSPLSound pressure level. Fluctuations in pressure measured as 10 times a logarithmic s pressure being 20 micropascals.	
during a measurement period.LA90The A-weighted noise level exceeded for 90 per cent of the time, also referred to as level and commonly used to derive noise limits.LAminThe minimum A-weighted noise level over a time period.LCeqThe energy average C-weighted noise energy during a measurement period. The "C to take into account low-frequency components of noise within the audibility rangeSPLSound pressure level. Fluctuations in pressure measured as 10 times a logarithmic s pressure being 20 micropascals.	
Ievel and commonly used to derive noise limits. LAmin The minimum A-weighted noise level over a time period. LCeq The energy average C-weighted noise energy during a measurement period. The "C to take into account low-frequency components of noise within the audibility range SPL Sound pressure level. Fluctuations in pressure measured as 10 times a logarithmic s pressure being 20 micropascals.	median noise level
LCeq The energy average C-weighted noise energy during a measurement period. The "C to take into account low-frequency components of noise within the audibility range SPL Sound pressure level. Fluctuations in pressure measured as 10 times a logarithmic s pressure being 20 micropascals.	s the "background" noise
SPL Sound pressure level. Fluctuations in pressure measured as 10 times a logarithmic s pressure being 20 micropascals.	
pressure being 20 micropascals.	
	scale, with the reference
Hertz (Hz)The frequency of fluctuations in pressure, measured in cycles per second. Most sou of many frequencies together.	unds are a combination
AWS Automatic weather station used to collect meteorological data, typically at an altitu	ude of 10 metres
VTG The vertical temperature gradient in degrees Celsius per 100 metres altitude.	
Sigma-theta The standard deviation of the horizontal wind direction over a period of time.	
IA Inaudible. When site noise is noted as IA then there was no site noise at the monitor	oring location.
NM Not Measurable. If site noise is noted as NM, this means some noise was audible by quantified.	ut could not be
Day Monday – Saturday: 7 am to 6 pm, on Sundays and Public Holidays: 8 am to 6 pm.	
Evening Monday – Saturday: 6 pm to 10 pm, on Sundays and Public Holidays: 6 pm to 10 pm	n.
Morning Shoulder Monday – Saturday: 5 am to 7 am.	

Appendix A provides further information that indicates how an average person perceives changes in noise levels and examples of common noise levels.

2 Noise limits

2.1 Project approval

Karuah East Quarry noise limits are detailed in Condition 3 of Project Approval (PA) 09_0175. Relevant sections of PA 09_0175 are reproduced in Appendix B.1.

2.2 Environment protection licence

Karuah East Quarry noise limits are detailed in Condition L4.1 of Environment Protection Licence (EPL) 20611. Relevant sections of EPL 20611 are reproduced in Appendix B.2.

2.3 Noise management plan

The approved Noise Management Plan (NMP) adopts five attended noise monitoring locations that are representative of residences outlined in PA 09_0175 and EPL 20611. Relevant sections of the NMP are reproduced in Appendix B.3.

2.4 Noise limits

Noise limits based on PA 09_0175 and EPL 20611 are as shown in Table 2.1.

Table 2.1Noise impact limits, dB

Location	Day L _{Aeq,15} minute	Evening L _{Aeq,15} minute	Morning Shoulder L _{Aeq,15} minute	Morning Shoulder ^L A1,1minute
A	42	40	35	52
В	40	40	35	52
F	40	35	35	52
G	43	39	35	52
Н	44	46	35	52

Notes: 1. Morning shoulder period is from 5:00 am to 7:00 am Monday to Saturday as defined in Condition L4.2 of EPL 20611.

2.5 Meteorological conditions

PA 09_0175 specifies that noise generated by the project is to be measured in accordance with the relevant requirements, and exemptions (including certain meteorological conditions), of the NSW EPA 'Noise Policy for Industry' (NPfI) issued in October 2017.

The EPA requirements in Condition L4.3 of EPL 20611 state that noise limits do not apply under the following meteorological conditions:

- wind speeds greater than 3 m/s at 10 m above ground level;
- stability category F temperature inversion conditions and wind speeds greater than 2 m/s at 10 m above ground level; or
- stability category G temperature inversion conditions.

2.6 Additional requirements

Monitoring and reporting have been done in accordance with the NPfI and the NSW EPA 'Approved methods for the measurement and analysis of environmental noise in NSW' (Approved Methods) issued in January 2022.

2.7 Very noise-enhancing meteorological conditions

In accordance with the approved methods, noise monitoring for the site is scheduled to occur during forecasted meteorological conditions where noise limits in Table 2.1 will be applicable. However, in cases where actual meteorological conditions do not align with forecasts and noise limits are subsequently not directly applicable, it is the expectation of regulators that noise impact still be managed.

The NPfl states that:

Noise limits derived for consents and licences will apply under the meteorological conditions used in the environmental assessment process, that is, standard or noise-enhancing meteorological conditions. For 'very noise-enhancing meteorological conditions' ... a limit is set based on the limit derived under standard or noise-enhancing conditions (whichever is adopted in the assessment) plus 5 dB. In this way a development is subject to noise limits under all meteorological conditions.

Therefore, if monthly noise monitoring occurs during meteorological conditions outside of those specified in Section 2.5, site limits will be adjusted based on Table 2.1 plus 5 dB.

3 Methodology

3.1 Overview

Attended environmental noise monitoring was done in general accordance with Australian Standard AS1055 'Acoustics, Description and Measurement of Environmental Noise' and relevant EPA requirements. Meteorological data was obtained from the KEQ on-site meteorological station which allowed correlation of atmospheric parameters with measured noise levels.

3.2 Attended noise monitoring

During this survey, attended noise monitoring was conducted during the morning shoulder, day and evening periods at each location. The duration of each measurement was 15 minutes. Atmospheric conditions were measured at each monitoring location.

Measured sound levels from various sources were noted during each measurement, and particular attention was given to the extent of the site's contribution (if any) to measured levels. At each monitoring location, the site-only $L_{Aeq,15minute}$ and L_{Amax} were measured directly or determined by other methods detailed in Section 7.1 of the NPfI.

The terms 'Inaudible' (IA) or 'Not Measurable' (NM) may be used in this report. When site noise is noted as IA, it was inaudible at the monitoring location. When site noise is noted as NM, this means it was audible but could not be quantified. All results noted as IA or NM in this report were due to one or more of the following:

- Site noise levels were very low, typically more than 10 dB below the measured background (L_{A90}), and unlikely to be noticed.
- Site noise levels were masked by more dominant sources that are characteristic of the environment (such as breeze in foliage or continuous road traffic noise) that cannot be eliminated by monitoring at an alternate or intermediate location.
- It was not feasible or reasonable to employ methods, such as to move closer and back calculate. Cases may include rough terrain preventing closer measurement, addition/removal of significant source to receiver shielding caused by moving closer, and meteorological conditions where back calculation may not be accurate.

If exact noise levels from site could not be established due to masking by other noise sources in a similar frequency range but were determined to be at least 5 dB lower than relevant limits, then a maximum estimate may be provided. This is expressed as a 'less than' quantity, such as <20 dB or <30 dB.

For this assessment, the measured L_{Amax} has been used as a conservative estimate of $L_{A1,1minute}$. The EPA accepts sleep disturbance analysis based on either the $L_{A1,1minute}$ or L_{Amax} metrics, with the L_{Amax} representing a more conservative assessment of site noise emissions.

3.3 Meteorological data

Meteorological data for the monitoring period was sourced from the Karuah East Quarry on-site meteorological station (the site AWS) to determine the applicability of criteria in accordance with the EPL and PA.

3.4 Modifying factors

All measurements were evaluated for potential modifying factors in accordance with the NPfI. Assessment of modifying factors is undertaken if the site was audible and directly quantifiable. If applicable, modifying factor penalties have been reported and added to measured site-only L_{Aeq} noise levels.

Low-frequency modifying factor penalties have only been applied to site-only L_{Aeq} levels if the site was the only contributing low-frequency noise source. Specific methodology for assessment of each modifying factor is outlined in Fact Sheet C of the NPfI.

3.5 Site operations

As required by Condition R4.3(a) of the EPL, the operations occurring at the time of monitoring are summarised per period below:

- Day
 - Routine quarry operations in the quarry pit
 - Routine plant processing operations
 - Routine material transport from the quarry pit to the processing plant and product stockpile areas
 - Routine product loading and dispatch to road trucks
- Evening
 - Routine material transport from the processing plant to product stockpile areas
 - Routine maintenance activities of plant and equipment
- Morning shoulder
 - Routine maintenance activities of plant and equipment
 - Routine product loading and dispatch to road trucks

3.6 Instrumentation

The equipment used to measure environmental noise levels is detailed in Table 3.1. Calibration certificates are provided in Appendix C.

Table 3.1 Attended noise monitoring equipment

Item	Serial number	Calibration due date	Relevant standard
Brüel & Kjær 2250 sound level meter	3029363	3/11/2024	IEC 61672-1:2002
Svantek SV-36 calibrator	79952	27/9/2025	IEC 60942

4 **Results**

4.1 Total measured noise levels and atmospheric conditions

Overall noise levels measured at each location during attended measurements are provided in Table 4.1.

Location	Start date and time	L _{Amax} dB	L _{A1} dB	L _{A10} dB	L _{Aeq} dB	L _{A50} dB	L _{A90} dB	L _{Amin} dB
A	24/11/2023 5:02	56	55	53	49	49	42	37
В	24/11/2023 5:20	74	70	65	61	57	49	42
F	24/11/2023 5:40	96	74	53	70	48	43	39
G	24/11/2023 6:08	59	48	40	39	37	33	30
Н	24/11/2023 6:27	57	48	43	39	35	32	29
Н	24/11/2023 7:00	64	59	52	48	38	31	28
G	24/11/2023 7:19	66	42	37	36	34	31	28
F	24/11/2023 7:45	96	73	51	65	47	44	40
В	24/11/2023 8:14	74	69	65	62	61	57	50
A	24/11/2023 8:33	60	55	53	51	51	48	44
А	30/11/2023 18:07	61	58	55	52	52	48	43
В	30/11/2023 18:25	78	74	68	65	63	58	51
F	30/11/2023 18:45	89	60	51	57	47	44	41
G	30/11/2023 19:11	59	47	43	41	40	37	33
Н	30/11/2023 19:33	66	43	41	39	39	37	34

Table 4.1Total measured noise levels – Q4 20231

Notes: 1. Levels in this table are not necessarily the result of activity at the site.

Atmospheric condition data measured by the operator during each measurement using a hand-held weather meter is shown in Table 4.2. The wind speed, direction and temperature were measured at approximately 1.5 metres above ground. Attended noise monitoring is not done during rain, hail, or wind speeds above 5 m/s at microphone height.

Location	Start date and time	Temperature ° C	Wind speed m/s	Wind direction ^o Magnetic north ¹	Cloud cover 1/8s
А	24/11/2023 5:02	19.2	<0.5	-	8
В	24/11/2023 5:20	19.3	<0.5	-	8
F	24/11/2023 5:40	19.5	<0.5	-	8
G	24/11/2023 6:08	19.5	<0.5	-	7
Н	24/11/2023 6:27	19.6	<0.5	-	7
Н	24/11/2023 7:00	20.4	<0.5	-	7
G	24/11/2023 7:19	20.8	<0.5	-	7
F	24/11/2023 7:45	21.4	<0.5	-	7
В	24/11/2023 8:14	22.1	<0.5	-	7
А	24/11/2023 8:33	22.2	<0.5	-	7
A	30/11/2023 18:07	27.9	<0.5	-	7
В	30/11/2023 18:25	27.5	<0.5	-	7
F	30/11/2023 18:45	27.3	<0.5	-	7
G	30/11/2023 19:11	27.1	<0.5	-	6
Н	30/11/2023 19:33	26.7	<0.5	-	6

Table 4.2 Measured atmospheric conditions – Q4 2023

Notes: 1. "-" indicates calm conditions at the monitoring location.

4.2 Site only noise levels

4.2.1 Modifying factors

No modifying factors were applicable during the survey, as defined in the NPfI.

4.2.2 Monitoring results

Table 4.3 provides site noise levels in the absence of other sources, where possible, and includes weather data obtained from the site AWS. Limits are applicable if weather conditions were within specified parameters during each measurement.

Table 4.3Site noise levels and limits – Q4 2023

Location	Start Date and Time (Period)	Wi	ind	Stability Class	Very enhancing? ¹	Limit, d	В	Site level,	dB ²	Exceedanc	e, dB
		Speed m/s	Direction ⁴			L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}
А	24/11/2023 5:02 (MS)	0.1	254	F	Ν	35	52	IA	IA	No	No
В	24/11/2023 5:20 (MS)	0.1	22	F	Ν	35	52	IA	IA	No	No
F	24/11/2023 5:40 (MS)	0.3	339	F	Ν	35	52	IA	IA	No	No
G	24/11/2023 6:08 (MS)	0.2	310	F	Ν	35	52	IA	IA	No	No
Н	24/11/2023 6:27 (MS)	0.1	307	F	Ν	35	52	IA	IA	No	No
Н	24/11/2023 7:00 (D)	0.1	275	А	Ν	44	N/A	<27	N/A	No	N/A
G	24/11/2023 7:19 (D)	0.3	132	А	Ν	43	N/A	<26	N/A	No	N/A
F	24/11/2023 7:45 (D)	0.7	140	А	Ν	40	N/A	IA	N/A	No	N/A
В	24/11/2023 8:14 (D)	0.5	283	А	Ν	40	N/A	IA	N/A	No	N/A
А	24/11/2023 8:33 (D)	0.9	208	А	Ν	42	N/A	IA	N/A	No	N/A

Table 4.3Site noise levels and limits – Q4 2023

Location	Start Date and Time (Period)	Wi	nd	Stability Class	Very enhancing? ¹	Limit, d	В	Site level,	dB ²	Exceedanc	e, dB
		Speed m/s	Direction ⁴	-		L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}	L _{Aeq,15} minute	L _{Amax}
А	30/11/2023 18:07 (E)	2.1	287	F	Ν	40	N/A	IA	N/A	No	N/A
В	30/11/2023 18:25 (E)	0.8	312	F	Ν	40	N/A	IA	N/A	No	N/A
F	30/11/2023 18:45 (E)	1.0	312	F	Ν	35	N/A	IA	N/A	No	N/A
G	30/11/2023 19:11 (E)	0.8	312	F	Ν	39	N/A	IA	N/A	No	N/A
Н	30/11/2023 19:33 (E)	1.0	298	F	Ν	46	N/A	IA	N/A	No	N/A

Notes:1. Noise limits are adjusted by +5 dB during 'very noise-enhancing meteorological conditions' in accordance with the NPfl.2. Site-only LAeq,15minute, includes modifying factor penalties if applicable.

3. Degrees magnetic north, "-" indicates calm conditions.

4. MS = Morning Shoulder period; D = Day period; E = Evening period.

5 Mitigation and management

5.1 Proposed management actions

EPL Condition 4.3(c) requires details of any management actions taken within the monitoring period to address any exceedances of the limits. As there were no exceedances, no management actions were required.

6 Summary

EMM Consulting Pty Ltd (EMM) was engaged by Karuah East Quarry Pty Limited to conduct a quarterly noise survey of operations at the site. The survey purpose was to quantify the acoustic environment and compare site noise levels against specified PA and EPL noise limits.

Attended environmental noise monitoring described in this report was done during the morning shoulder, day and evening periods on Friday 24 and Thursday 30 November 2023 at five monitoring locations.

Noise levels from the site complied with relevant limits at all monitoring locations during the Q4 2023 survey.

Appendix A

Noise perception and examples




A.1 Noise levels

Table A.1 indicates how an average person perceives changes in noise level. Examples of common noise levels are provided in Figure A.1.

Table A.1Perceived change in noise

Change in sound pressure level (dB)	Perceived change in noise
up to 2	Not perceptible
3	Just perceptible
5	Noticeable difference
10	Twice (or half) as loud
15	Large change
20	Four times (or a quarter) as loud





Appendix B Regulator documents



B.1 Project approval

SCHEDULE 3 ENVIRONMENTAL PERFORMANCE CONDITIONS

IDENTIFICATION OF APPROVED LIMITS OF EXTRACTION

- 1. The Applicant shall, prior to carrying out quarrying operations on the site:
 - (a) engage a registered surveyor to mark out the boundaries of the approved limits of extraction within the Extraction Area; and
 - (b) submit a survey plan of the extraction boundaries,
 - to the satisfaction of the Planning Secretary.
- 2. The Applicant must ensure that the extraction boundaries are clearly marked at all times while quarrying operations are being carried out, in a manner that allows the limits of extraction to be clearly identified.

NOISE

Operational Noise Criteria

3. Except for the carrying out of construction works, the Applicant must ensure that the operational noise generated by the development does not exceed the criteria in Table 2 at any residence^a on privately-owned land.

Noise Assessment Location ^a	Morning Shoulder LAeq (15 min)	Morning Shoulder L _{Amax}	Day L _{Aeq (15 min)}	Evening L _{Aeq (15 min)}
А	35	52	42	40
В	35	52	40	40
G	35	52	43	39
Н	35	52	44	46
I	35	52	40	37
All other residences	35	52	40	35

Table 2: Operational noise criteria dB

^a Noise Assessment Locations referred to in Table 2 are shown in Appendix 2.

Noise generated by the development must be monitored and measured in accordance with the relevant procedures and modifications (including certain meteorological conditions) of the NPfI.

3A. The noise criteria in Table 2 do not apply if the Applicant has an agreement with the owner/s of the relevant residence or land to exceed the noise criteria, and the Applicant has advised the Department in writing of the terms of this agreement.

Road Traffic Noise Criteria

4. The Applicant must take all reasonable and feasible measures to ensure that the traffic noise generated by the development does not cause additional exceedances of the criteria in Table 3 at any residence on privately-owned land.

Table 3: Road traffic noise criteria

Road	Criteria (Dayª)
Pacific Highway	60 dB(A) LAeq (15 hour)
Local roads	55 dB(A) L _{Aeq (1 hour)}

^a Day is the period from 7 am to 10 pm every day in accordance with the EPA's NSW Road Noise Policy (2011).

5. Deleted

Noise Operating Conditions

- 6. The Applicant must:
 - (a) take all reasonable steps to minimise noise from construction and operational activities, including low frequency noise and other audible characteristics, associated with the development;
 - (b) implement reasonable and feasible noise attenuation measures on all plant and equipment that will operate in noise sensitive areas;
 - (c) operate a comprehensive noise management system commensurate with the risk of impact;
 - (d) take all reasonable steps to minimise the noise impacts of the development during noiseenhancing meteorological conditions when the noise criteria in this consent do not apply (see NPfI);
 - (e) carry out quarterly attended noise monitoring (unless otherwise agreed by the Planning Secretary) to determine whether the development is complying with the relevant conditions of this consent; and
 - (f) regularly assess the noise monitoring data and modify or stop operations on the site to ensure compliance with the relevant conditions of this consent.

Noise Management Plan

- 7. The Applicant must prepare a Noise Management Plan for the development to the satisfaction of the Planning Secretary. This plan must:
 - (a) be prepared by a suitably qualified and experienced person/s whose appointment has been endorsed by the Planning Secretary;
 - (b) be prepared in consultation with the EPA;
 - (c) describe the measures to be implemented to ensure:
 - (i) compliance with the noise criteria and operating conditions in this consent;
 - (ii) best practice management is being employed;
 - (iii) noise impacts of the development are minimised during noise-enhancing meteorological conditions when the noise criteria in this consent do not apply (see NPfI);
 - (d) describe the noise management system in detail; and
 - (e) include a monitoring program that:
 - (i) is capable of evaluating the performance of the development;
 - (ii) monitors noise at the nearest and/or most affected residences;
 - (iii) adequately supports the noise management system;
 - (iv) includes a protocol for distinguishing noise emissions of the development from any neighbouring developments; and
 - includes a protocol for identifying any noise-related exceedance, incident or noncompliance and for notifying the Department and relevant stakeholders of any such event.
- 7A. The Applicant must implement the plan as approved by the Planning Secretary.

BLASTING

Blasting Criteria

8. The Applicant must ensure that blasting on the site does not cause exceedances of the criteria in Table 5.

B.2 Environmental protection licence

Licence - 20611

L3 Waste

L3.1 The licensee must not cause, permit or allow any waste generated outside the premises to be received at the premises for storage, treatment, processing, reprocessing or disposal or any waste generated at the premises to be disposed of at the premises, except as expressly permitted by the licence.

NSU Multiple

L4 Noise limits

L4.1 Noise generated at the premises must not exceed the noise limits in the table below. The locations referred to in the table below are indicated in Table 2: Operational Noise Criteria, and Figure 1 of the document titled Project Approval 09_0175 Modification 9 (MOD 9) Department of Planning, Industry& Environment - which has been filed on EPA file Doc22/715570-1.

Noise Assesment Location	Morning Shoulder LAeq(15 min)	Morning shoulder LAmax	Day LAeq (15 min)	Evening LAeq (15 min)
A (74 Mill Hill Close, Karuah, Lot 100 DP 1028885)	35	52	42	40
B (64 Mill Hill Close, Karuah, Lot 3 DP785172)	35	52	40	40
G (2 Halloran Road, North Arm Cove Lot 1 DP1032636)	35	52	43	39
H (21 Halloran Road, North Arm Cove Lot 10 DP1032636)	35	52	44	46
All other residences	35	52	40	35

L4.2 Noise limit definitions - For the purpose of the table at L4.1, the following definitions apply: Day is defined as the period from 7am to 6pm Monday to Saturday and 8am to 6pm Sunday and Public Holidays;

Morning Shoulder is defined as the period from 5:00am to 7:00am Monday to Saturday; Evening is defined as the period from 6:00pm to 10:00pm Monday to Saturday.

- L4.3 The noise limits set out in this licence apply under all meteorological conditions except for the following:
 - a) Wind speed greater than 3 metres/second at 10 metres above ground level; or

b) Stability category F temperature inversion conditions and wind speeds greater than 2 metres/second at 10 metres above ground level; or

c) Stability category G temperature inversion conditions.

L4.4 **Determining Compliance**



Licence - 20611

To determine compliance with the noise limits set out in the table above, the licensee must locate monitoring equipment:

a) within 30 metres of a dwelling façade (but not closer than 3 metres) where any dwelling on the property is situated more than 30 metres from the property boundary that is closest to the premises;

b) approximately on the boundary where any dwelling is situated 30 metres or less from the property boundary that is closest to the premises;

c) at the most affected point at a location where there is no dwelling at the location; and

d) within approximately 50 metres of the boundary of a national park or nature reserve.

Note: A non-compliance of the Noise Limits table will still occur where noise generated from the premises in excess of the appropriate limit is measured:

i) at a location other than an area prescribed in part (a) and part (b); and/or

ii) at a point other than the most affected point at a location.

L4.5 For the purposes of determining the noise generated at the premises the modification factors in Fact Sheet C of the EPA's "Noise Policy for Industry" must be applied, as appropriate, to the noise levels measured by the noise monitoring equipment.

L5 Blasting

- L5.1 Blasting in or on the premises must only be carried out between the hours of 9:00 am and 4:00 pm Monday to Friday. No blasting is permitted on Saturdays, Sundays or public holidays. Blasting outside of the hours specified in this condition can only take place with the written approval of the EPA.
- L5.2 Blasting is not permitted simultaneously with adjacent quarry(s).
- L5.3 The airblast overpressure level from blasting operations in or on the premises must not exceed:
 a) 115 dB (Lin Peak) for more than 5% of the total number of blasts during each reporting period; and
 b) 120 dB (Lin Peak) at any time,
 at monitoring point 11 detailed in Condition P1.4.
- L5.4 The ground vibration peak particle velocity from blasting operations carried out in or on the premises must not exceed:

a) 5 mm/second for more than 5% of the total number of blasts during each reporting period; and

b) 10 mm/second at any time,

at monitoring point 11 detailed in Condition P1.4.

- L5.5 Error margins associated with any monitoring equipment used to measure airblast overpressure or peak particle velocity are not to be taken into account in determing whether or not the limit has been exceeded.
- L5.6 The airblast overpressure and ground vibration levels in the conditions above do not apply at noise sensitive locations that are owned by the licensee or subject to a private agreement, relating to airblast overpressure and ground vibration levels, between the licensee and land owner.
- L5.7 Offensive blast fume must not be emitted from the premises.

Definition:



Licence - 20611

d) the nature of the complaint;

e) the action taken by the licensee in relation to the complaint, including any follow-up contact with the complainant; and

f) if no action was taken by the licensee, the reasons why no action was taken.

- M5.3 The record of a complaint must be kept for at least 4 years after the complaint was made.
- M5.4 The record must be produced to any authorised officer of the EPA who asks to see them.

M6 Telephone complaints line

- M6.1 The licensee must operate during its operating hours a telephone complaints line for the purpose of receiving any complaints from members of the public in relation to activities conducted at the premises or by the vehicle or mobile plant, unless otherwise specified in the licence.
- M6.2 The licensee must notify the public of the complaints line telephone number and the fact that it is a complaints line so that the impacted community knows how to make a complaint.
- M6.3 The preceding two conditions do not apply until 1 month after the date of the issue of this licence.

M7 Blasting

M7.1 To determine complaince with Blast Limit conditions of this licence:
a) Airblast overpressure and ground vibration levels must be measured and electronically recorded for monitoring point 11 for the parameters specified in Column 1 of the table below; and
b) The licensee must use the units of measure, sampling method, and sample at the frequency specified opposite in the other columns.

Parameter	Units of Measure	Frequency	Sampling Method
Airblast Overpressure	Decibels (Linear Peak	All blasts	Australian Standard AS 2187.2-2006
Ground Vibration Peak Particle Velocity	millimetres/second	All blasts	Australian Standard AS 2187.2-2006

M8 Noise monitoring

- M8.1 To assess compliance with the noise limits for this premises attended noise monitoring must be undertaken in accordance with all noise conditions and:
 - a) during a period of normal quarry operations;
 - b) at each one of the locations listed in the noise limits table of this licence;
 - c) occur quarterly in the reporting period;
 - d) occur during each day period as defined in the NSW Noise Policy for Industry.

Note: Quarterly attended noise monitoring must be completed (unless otherwise agreed by the Planning



Licence - 20611

Secretary) to determine whether the development is complying with the relevant conditions of this consent. The frequency of noise monitoring will be reviewed, upon request.

6 Reporting Conditions

R1 Annual return documents

R1.1 The licensee must complete and supply to the EPA an Annual Return in the approved form comprising:

- 1. a Statement of Compliance,
- 2. a Monitoring and Complaints Summary,
- 3. a Statement of Compliance Licence Conditions,
- 4. a Statement of Compliance Load based Fee,
- 5. a Statement of Compliance Requirement to Prepare Pollution Incident Response Management Plan,
- 6. a Statement of Compliance Requirement to Publish Pollution Monitoring Data; and
- 7. a Statement of Compliance Environmental Management Systems and Practices.

At the end of each reporting period, the EPA will provide to the licensee notification that the Annual Return is due.

- R1.2 An Annual Return must be prepared in respect of each reporting period, except as provided below.
- Note: The term "reporting period" is defined in the dictionary at the end of this licence. Do not complete the Annual Return until after the end of the reporting period.
- R1.3 Where this licence is transferred from the licensee to a new licensee:a) the transferring licensee must prepare an Annual Return for the period commencing on the first day of the reporting period and ending on the date the application for the transfer of the licence to the new licensee is granted; and

b) the new licensee must prepare an Annual Return for the period commencing on the date the application for the transfer of the licence is granted and ending on the last day of the reporting period.

- Note: An application to transfer a licence must be made in the approved form for this purpose.
- R1.4 Where this licence is surrendered by the licensee or revoked by the EPA or Minister, the licensee must prepare an Annual Return in respect of the period commencing on the first day of the reporting period and ending on:

a) in relation to the surrender of a licence - the date when notice in writing of approval of the surrender is given; or

b) in relation to the revocation of the licence - the date from which notice revoking the licence operates.

- R1.5 The Annual Return for the reporting period must be supplied to the EPA via eConnect *EPA* or by registered post not later than 60 days after the end of each reporting period or in the case of a transferring licence not later than 60 days after the date the transfer was granted (the 'due date').
- R1.6 The licensee must retain a copy of the Annual Return supplied to the EPA for a period of at least 4 years after

B.3 Noise management plan

5 Noise limits

5.1 Operational noise

Condition 3 of Schedule 3 of PA 09_0175 provides the operational noise limits for KEQ. These are reproduced in Table 5.1.

Table 5.1 Operational noise criteria (dB) from Table 2 of PA 09_0175

Noise Assessment Location ¹	Morning Shoulder L _{Aeq(15 minute)}	Morning Shoulder L _{Amax}	Day L _{Aeq(15 minute)}	Evening L _{Aeq(15 minute)}
A	35	52	42	40
В	35	52	40	40
G	35	52	43	39
Н	35	52	44	46
I	35	52	40	37
All other residences	35	52	40	35

Noise assessment locations are shown in Figure 3.1.

Noise generated by the development must be monitored and measured in accordance with the relevant procedures and exemptions (including certain meteorological conditions) of the NPfI (EPA 2017).

The noise limits provided in Table 5.1 apply under standard and noise-enhancing meteorological conditions (as defined in the NPfI) determined by monitoring at the relevant weather station. In accordance with Condition L4.3 of EPL 20611 and consistent with Condition 3 of Schedule 3 of PA 09_0175 the noise limits provided in Table 5.1 apply under all meteorological conditions except for the following:

- wind speeds greater than 3m/s at 10m above ground level;
- stability category F temperature inversion conditions and wind speeds greater then 2m/s at 10m above ground level; or
- stability category G temperature inversion conditions.

In accordance with Fact Sheet D of the NPfI, for 'very noise enhancing meteorological conditions' the applicable noise limit is set at 5dB above those provided in Table 5.1.

Noise limits do not apply if Karuah East has an agreement with the owner/s of the relevant residence or land to exceed the noise criteria, and Karuah East has advised the Department in writing of the terms of this agreement.

5.2 Road traffic noise

Condition 4 of Schedule 3 of PA 09_0175 states that all reasonable and feasible measures must be taken to ensure that the traffic generated by KEQ does not cause additional exceedances of the criteria provided in Table 5.2 at any residence on privately-owned land.

Appendix C Calibration certificates



CERTIFICATE OF CALIBRATION

CERTIFICATE NO: C33872

EQUIPMENT TESTED: Sound Level Calibrator

	e No: wner: med:	L3, 17 Newca Measu	Seria Consulting Pt 5 Scott Stree astle, NSW 23	y Ltd t 300 ssure le	79952 vel, Frequency Passed.	& Distortion
Parameter	Pre- Adj	Adj Y/N			Frequency (Hz)	THD&N (%)
Level1:	NA	N	94.09	dB	1000.00 Hz	1.12 %
Level2:	NA	N	114.06	dB	1000.00 Hz	0.71 %
Unce	ertainty	1	±0.11	dB	±0.05%	±0.20 %
Uncertainty (at	95% c.l	.) k=2	earth Michaen	fight by	ad spectrometry	CO repairs
CONDITION OF Ambient Pre Temper Relative Hun	essure ature	1004 23	hPa ±1 hPa °C ±1º C % ±5%		ate of Receipt : of Calibration : Date of Issue :	26/09/2022 29/09/2022 29/09/2022
Acu-Vib Procee Checked b	dure:		2 (Calibrators) lethod: AS IEC AUTHORIS SIGNATUI	SED		ein Soe

Accredited for compliance with ISO/IEC 17025 - Calibration

Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part. The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.



WORLD RECOGNIBED ACCREDITATION Accredited Lab No. 9262 Acoustic and Vibration Measurements

Head Office & Calibration Laboratory Unit 14, 22 Hudson Ave. Castle Hill NSW 2154 (02) 9680 8133 www.acu-vib.com.au

Acu-Vib Electronics

CALIBRATIONS SALES RENTALS REPAIRS

Page 1 of 2 Calibration Certificate AVCERT02.1 Rev.2.0 14.04.2021

CERTIFICATE OF CALIBRATION

CERTIFICATE NO: SLM34169

EQUIPMENT TESTED: Sound Level Meter

Manufacturer:	B&K	
Type No:	2250	
Mic. Type:	4189	
Pre-Amp. Type:	ZC0032	

Serial No: 3029363 Serial No: 3260501 Serial No: 30109 Test No: F034175

Filter Type: 1/3 Octave

Owner: EMM Consulting Suite 01, 20 Chandos St St Leonards NSW 2065

Tests Performed: IEC 61672-3:2013 & IEC 61260-3:2016

Comments:All Test passed for Class 1. (See overleaf for details)CONDITIONS OF TEST:Ambient Pressure1002hPa ±1 hPaDate of Receipt :02/11/2022

Temperature Relative Humidity 02 hPa ±1 hPa 24 °C ±1° C 35 % ±5%

Date of Calibration : 03/11/2022 Date of Issue : 04/11/2022

Jack Kielt

Accredited for compliance with ISO/IEC 17025 - Calibration

Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part. The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.



WORLD RECOGNISED ACCREDITATION Accredited Lab No. 9262 Acoustic and Vibration Measurements Acu-Vib Electronics CALIBRATIONS SALES RENTALS REPAIRS

Head Office & Calibration Laboratory Unit 14, 22 Hudson Ave. Castle Hill NSW 2154 (02) 9680 8133 www.acu-vib.com.au

Page 1 of 2 Calibration Certificate AVCERT10.14 Rev.2.0 14/04/2021

Australia

SYDNEY

Ground floor 20 Chandos Street St Leonards NSW 2065 T 02 9493 9500

NEWCASTLE

Level 3 175 Scott Street Newcastle NSW 2300 T 02 4907 4800

BRISBANE Level 1 87 Wickham Terrace Spring Hill QLD 4000

Spring Hill QLD 4000 T 07 3648 1200

CANBERRA

Suite 2.04 Level 2 15 London Circuit Canberra City ACT 2601

ADELAIDE

Level 4 74 Pirie Street Adelaide SA 5000 T 08 8232 2253

MELBOURNE

Suite 8.03 Level 8 454 Collins Street Melbourne VIC 3000 T 03 9993 1900

PERTH

Suite 9.02 Level 9 109 St Georges Terrace Perth WA 6000 T 08 6430 4800

Canada

TORONTO 2345 Yonge Street Suite 300 Toronto ON M4P 2E5 T 647 467 1605

VANCOUVER

60 W 6th Ave Vancouver BC V5Y 1K1 T 604 999 8297



linked in.com/company/emm-consulting-pty-limited



emmconsulting.com.au



Appendix 4 – KEQ IEA 2023: Response to Audit Recommendations

Page
202 of 399



KEQ 2	2020 IEA Action Review – Project Approval (MP09_0175)				
No	Requirement	Details of Non-Compliance	2020 KEQ Response / Action	2023 IEA Finding	ĺ
S2, C11	 The Applicant must pay Council, in accordance with Council's Great Lakes Wide Development Contributions Plan (November 2007) – Amended: (a) a one-off Headquarters Building contribution of \$1.00 per \$1,000.00 of capital value of the development; and (b) Annual road maintenance contributions of \$.037 per tonne per km, for every tonne of quarry products transported from the site on local roads in accordance with Council's Great Lakes Wide Development Contributions Plan (November 2007) – Amended. Each payment must be: i. paid to Council at the end of each calendar year. ii. Based on weighbridge records of the quantity of quarry products transported from the site; and iii. Increased annually over the life of the development in accordance with the CPI. <i>Note: If the parties are not able to agree on any aspect of the road maintenance contributions, either party may refer the matter to the Planning Secretary for resolution.</i> 	 (a) Records of one-off contribution to Council for Headquarters Building were not available at the time of audit. (b) Records of annual contributions to Council for road maintenance in the 2019/20 Financial Year were not available at the time of audit. 	KEQ are investigating payments made to MidCoast Council to ensure that all required developer contribution payments have been made. If payments have not been made, KEQ will consult with Council to establish a payment plan.	Deemed as Non- Compliant during the audit.	
S3, C11 (d) (ii)	 The Applicant must: (d) Not undertake blasting within 500 metres of: any land outside the site not owned by the Applicant, unless: The Applicant has a written agreement with the relevant landowner to allow blasting to be carried out closer to the land, and the Applicant has advised the Department in writing of the terms of this agreement, or the Applicant has: Demonstrated to the satisfaction of the Planning Secretary that the blasting can be carried out closer to the land without compromising the safety of the people or livestock on the land, or damaging the buildings and/or structures on the land; and Updated the Blast Management Plan to include the specific measures that would be implemented while blasting is being carried out within 500 metres of the land, to the satisfaction of the Planning Secretary. 	Evidence that written agreements with landholders within 500 m of project blasting was not available at the time of audit.	KEQ have operated in accordance with the approved Blast Management Plan (2015) which identifies that there are no residents/receivers within 500 metres from the potentially nearest blasting areas. Refer to Section 3.4 – Sensitive Receivers of the Karuah East Quarry Blast Management Plan for further details. KEQ have never received a community complaint regarding blasting undertaken at the Quarry. KEQ will consult with the Department to determine if any action is required.	Deemed as Non- Compliant during the audit. It is considered that blasting activities during the audit period would have occurred within 500 m of privately owned land without a written agreement. Sale of the subject property has since taken place and thus there are no further actions required in relation to this. Further detail is available in Appendix A1.	
S3, C16	 The Applicant must prepare an Air Quality Management Plan for the development to the satisfaction of the Planning Secretary. This plan must: (a) Be prepared by a suitably qualified expert whose appointment has been approved by the Planning Secretary. (b) Be prepared in consultation with Council and EPA and submitted for approval to the Planning Secretary prior to the commencement of construction activities. (c) Describe the measures that would be implemented to ensure: Compliance with the relevant air quality conditions of this consent; 	In June and December of 2017, HVAS monitor filters were not changed at the correct time leading to an overrun of the sample. Filters were changed as soon as errors were identified.	No recommendation made.	Deemed as Non- Compliant during the audit. Whilst ERM consider KEQ are generally compliant with	

2023 KEQ Response / Action

RESPONSE:

KEQ can confirm:

(a) Headquarters building contribution was provided to Council on 11 April 2022.

 (b) Road maintenance contributions for FY18 to FY22 was provided to Council on 30 June 2023. This was subject to compensatory cost escalation in accordance with CPI.

FY23 was provided to Council on 03 August 2023 (remittance advice date).

STATUS:

KEQ considers this 2020 finding to be resolved. **RESPONSE:**

KEQ can confirm the property (Lot 4, DP838128) has been acquired.

STATUS:

KEQ considers this 2020 finding to be resolved.

RESPONSE:

KEQ have since updated our processes to ensure HVAS monitoring is completed. This failure to monitor has not since been repeated.

STATUS:

KEQ considers this 2020 finding to be resolved.



KEQ 2	2020 IEA Action Review – Project Approval (MP09_0175)			
No	Requirement	Details of Non-Compliance	2020 KEQ Response / Action	2023 IEA Finding
	 best management practice is employed; and The air quality impacts of the development are minimised during adverse meteorological conditions and extraordinary events. (d) Describe the proposed air quality management system; and (e) Include a monitoring program that: Can evaluate the performance of the development. Includes a protocol for determining any exceedances of the relevant conditions of consent. Effectively supports the air quality management system; and Evaluates and reports on the adequacy of the air quality management system. The applicant must implement the plan as approved by the Planning Secretary 			conditions (a) to (e), implementation of the plan requires a period review in accordance with Schedule 5, Condition 5 meaning that the 2019 version of the AQMP is now outdated.
S3, C19	The Applicant must comply with the discharge limits in any EPL, or with Section 120 of the POEO Act.	Uncontrolled and controlled discharges from sediment dams in exceedance of discharge limits occurred during the audit period in 2017, 2018 and 2019.	Responses outlined in S3, C21 below.	Deemed as Non- Compliant during the audit. Non-compliant discharges were recorded within the audit period. This is discussed in further detail in Condition 19, Schedule 3 of Appendix A1.
\$3, C21	 The Applicant must prepare a Water Management Plan for the development to the satisfaction of the Planning Secretary. This plan must: (a) Be prepared in consultation with the EPA and DPE Water by suitably qualified and experienced person/s whose appointment has been approved by the Planning Secretary. (b) Be submitted to the Planning Secretary for approval prior to the commencement of construction activities. (c) Include: A Site Water Balance that includes details of: Sources and security of water supply, including contingencyplanning; Water use on site; and Measures that would be implemented to minimise use of clean water and maximise recycling of dirty water on the site. A Surface Water Management Plan, that includes: Baseline data on surface water flows and quality in the watercourses that could be affected by the development. A detailed description of the surface water management system on the site, including the design objectives and performance criteria for the: clean water diversions; water storages (including Maximum Harvestable Rights requirements); and control of water pollution from areas of the site that have been rehabilitated. 	The surface water monitoring does not include a program for the monitoring of stream ecosystem health. A noncompliance with the WMP was recorded in 2017 due to frequency of Groundwater level monitoring (as reported in Section 7.4.2 of the 2017 Annual Review). Quarterly monitoring commenced in accordance with the required frequency in October 2017; prior to this date monitoring had been undertaken on a six- monthly basis.	KEQ agree with this recommendation and will consult with the Department during the next review of the WMP. KEQ will consult with the Department during the next review of the WMP and BOAMP to determine whether additional monitoring is required to monitor the health of local watercourses. However, let it be noted that local watercourses are monitored and reported on in the annual Biodiversity Offset Area Monitoring Report; this is in line with the approved BOAMP.	Deemed as Non- Compliant during the audit. There was no evidence to confirm a review has taken place due to exceedances in surface water discharge limits (refer Section 3 Condition 19).

2023 KEQ Response / Action Refer to the 2023 audit response for details regarding the 2023 findings.

RESPONSE:

Discharge events were associated with rainfall events greater than the designated design-storm events outlined by the Blue Book (Managing Urban Stormwater: Soils and Construction – Volume 2E, Mines and quarries).

STATUS:

KEQ considers this 2020 finding to be resolved.

Refer to the 2023 audit response for details regarding the 2023 findings.

KEQ considers the 2020 findings to be superseded.



KEQ 2	020 IEA Action Review – Project Approval (MP09_0175)			
No	Requirement	Details of Non-Compliance	2020 KEQ Response / Action	2023 IEA Finding
	 Surface water impact assessment criteria, to be developed following analysis of baseline data, including trigger levels for investigating any potentially adverse surface water quality impacts. A program to monitor: any surface water discharges; the effectiveness of the water management system; surface water flows and quality in local watercourses; and ecosystem health of local watercourses; and accordance with Managing Urban Stormwater: Soils and Construction (Landcom); A Groundwater Monitoring Program that includes: Baseline data of groundwater levels surrounding the site. Groundwater impact assessment criteria, to be developed following analysis of baseline data, including trigger levels for investigating any potentially adverse groundwater impacts; and A program to monitor and/or validate the impacts of the development on groundwater resources; and A Surface and Ground Water Response Plan that describes the measures and/or procedures that would be implemented to: Respond to any exceedances of the surface water impact assessment criteria and groundwater impact assessment criteria; and Mitigate and/or offset any adverse impacts on surface water and groundwater resources located within and adjacent to the site. 			
S3, C23	The Applicant must keep accurate records of all laden truck movements to and from the site (including time of arrival and dispatch) and publish a summary of records on its website every 6 months and in the Annual Review.	 (a) Production records are reported in the audit period Annual Reviews, however the transportation of product from site per calendar month and the number of laden truck movements is not reported. (b) Viewed KEQ website on 17/8/20 and quarterly truck movement records were not available. 	KEQ agree with this recommendation. Future environmental monitoring reports will include information on the factors identified in mentioned conditions.	Deemed as Non- Compliant during the audit. Laden truck movements are not recorded within the KEQ Annual Reviews.
S3, C28	The Applicant must, prior to the commencement of vegetation clearing activities for Modification 10, finalise the Biodiversity Offset Strategy, as described in documents listed in condition 2 of Schedule 2, summarised in Table 10 and Table 11 and shown conceptually in Figure 1 of Appendix 4, in consultation with BCD and Council, and to the satisfaction of the Planning Secretary.	The Biodiversity Offset Strategy Finalisation letter (as referenced in Section 2.2 and Appendix 2 in the BOAMP) and evidence of consultation with OEH (now BCD) and Council was not available for review at the time of audit.	Officers of the Biodiversity Conservation Trust are attending site in November to assess the Biodiversity Area and consult on the progress of the Biodiversity Offset Strategy. KEQ will consult with the Department and seek	Deemed as Non- Compliant during the audit. The Biodiversity Offset Strategy should have been updated within 3 months of any

2023 KEQ Response / Action

KEQ considers the 2020 findings to be superseded.

Refer to the 2023 audit response for details regarding the 2023 findings.

The 2020 audit finding was prior to MOD10 being assessed and approved. Therefore, the resulting actions are no-longer current due to the revised condition.

KEQ considers the 2020 findings to be superseded.



KEQ 2	2020 IEA Action Review – Project Approval (MP09_0175)				
No	Requirement	Details of Non-Compliance	2020 KEQ Response / Action	2023 IEA Finding	
	Within 6 months of the date of approval of Modification 1, the Applicant must prepare a Landscape and Rehabilitation Management Plan for the development to the satisfaction of the	The revisions detailed in Table 2 of the Landscape	extension to the timeframe required if required. KEQ agree with the recommendation made by	modification to the conditions of this consent. It is noted that latest version of the BOS is dated July 2013. Deemed as Non- Compliant during	
S3, C32	 Planning Secretary. This Plan would relate to the area of the quarry and all perimeter lands. This plan must: (a) Be prepared by a suitably qualified expert whose appointment has been approved by the Planning Secretary. (b) Be prepared in consultation with BCD and Council, and submitted to the Planning Secretary for approval prior to the commencement of construction activities; (c) Describe the short, medium and long-term measures that would be implemented to: Manage remnant vegetation and habitat on the site; and Ensure compliance with the rehabilitation objectives and progressive rehabilitation obligations of this consent. (e) include detailed performance and completion criteria for evaluating the performance of the rehabilitation of the site; including triggers for any remedial action; (f) Include a detailed for each 3 year period following initial preparation of the plan), including the procedures to be implemented for: Ensuring compliance with the rehabilitation objectives and progressive rehabilitation obligations of this consent; Ensuring compliance with the rehabilitation objectives and progressive rehabilitation obligations of this consent; Ensuring compliance with the rehabilitation objectives and progressive rehabilitation obligations of this consent; Ensuring the quality of remnant vegetation and fauna habitat; Restoring native endemic vegetation and fauna habitat; Restoring native endemic vegetation communities of the rehabilitation area, including the alvage of environmental resources within the approved disturbance area - including tree hollows, vegetative and soil resources - for beneficial reuse in the enhancement of the rehabilitation area; Coordinating the relabilitation area; Collecting and propagating seed; Ensuring minimal environmental consequences for threatened species, populations and habitat;; Minimising the impac	and Rehabilitation Management Plan (LRMP) do not describe updating the measures to implemented over the three-year period. The condition requires update every three years following initial preparation of the plan, in this case being November 2018. Chapters 6-9 of the LRMP detail management measures, however the plan does not specify which activities will occur over the next three years of the plan.	the auditor and will conduct a revision of the LRMP in the near future. The revisions describe here will be made. During the revision of the LRMP, KEQ will ensure all procedures to record, and responsible employees are made aware of their obligations.	the audit. The LRMP has not been updated within a 3 year period as required by clause (f) of this condition. Further details are discussed in Appendix A1.	

2023 KEQ Response / Action

KEQ considers the 2020 findings to be superseded.



 the satisfaction of the Planning Secretary. This Plan would relate to the area of the Biodiversity Offset Area required in these conditions. This plan must: (a) Be prepared by a suitably qualified expert whose appointment has been approved by the Planning Secretary (b) Be prepared in consultation with BCD and Council (c) Describe how the implementation of the Tetratheca juncea Translocation Program would be integrated with the Biodiversity Offset Area management. (d) Describe the short, medium and long-term measures that would be implemented to manage remnant vegetation and habitat on the Biodiversity Offset Area (e) Include detailed performance and completion criteria for evaluating the performance of the conservation, restoration and management of the Biodiversity Offset Area. (f) Providing for the transfer of environmental resources - for beneficial reuse in the enhancement of the Biodiversity Offset Area. (f) Providing tree hollows, vegetative and soil resources - for beneficial reuse in the enhancement of the Biodiversity Offset Area. 	2023 IEA Finding Deemed as Non- Compliant during the audit. A number of outstanding actions recommended within the latest Ecological Monitoring Report (included within the 2022
 translocation Program and rehabilitation of the site, and include a description of the contingency measures that would be implemented to mitigate these risks. (k) Include details as to how the rehabilitated land would be permanently conserved and managed as part of the broader Biodiversity Offset Area approved in these conditions. (i) Include details of the volume the plan as approved by the Planning Secretary. The Applicant must implement the plan as approved by the Planning Secretary. This Plan would relate to the area of the Biodiversity Offset Area required in these conditions. This plan must: (a) Be prepared by a suitably qualified expert whose appointment has been approved by the Planning Secretary. (b) Be prepared by a suitably qualified expert whose appointment has been approved by the Planning Secretary. (c) Describe how the implementation of the Teartheca juncea Translocation Program would be integrated with the Biodiversity Offset Area management. (c) Describe the short, medium and long-term measures that would be implemented to manage (e) Include detailed performance and completion criteria for evaluating the performance of the conservation, restoration and management of the Biodiversity Offset Area including triggers for any remedial action. (f) Providing for the transfer of environmental resources from the approved disturbance area including tree hollows, vegetative and soil resources - for beneficial reuse in the enhancement of the Biodiversity Offset Area. 	Compliant during the audit. A number of outstanding actions recommended within the latest Ecological Monitoring Report (included within the 2022
 (h) Include a detailed description of the measures that would be implemented over the next 3 years (to be updated for each 3-year period following initial preparation of the plan), including the procedures to be implemented for: Enhancing the quality of remnant vegetation and fauna habitat 	Annual Review) have not been closed out and constitutes a non- compliance against clause (h) of this condition. Further details are discussed in Appendix A1.

2023 KEQ Response / Action

RESPONSE: The BOAMP was updated in May 2021.

STATUS:

KEQ considers the 2020 findings to be resolved.



	2020 IEA Action Review – Project Approval (MP09_0175)			
No	Requirement	Details of Non-Compliance	2020 KEQ Response / Action	2023 IEA Finding
	 (k) Include details of who would be responsible for monitoring, reviewing, and implementing the plan. (l) Include details of the indicative costs of management actions; and Include details as to the timing of actions set out in the plan. 			
55,	 The Applicant must assess and manage development-related risks to ensure that there are no exceedances of the criteria and/or performance measures in this consent. Any exceedance of these criteria and/or performance measures constitutes a breach of this consent and may be subject to penalty or offence provisions under the EP&A Act or EP&A Regulation. Where any exceedance of these criteria and/or performance measures has occurred, the Applicant must, at the earliest opportunity: (a) Take all reasonable and feasible measures to ensure that the exceedance ceases and does not recur. (b) Consider all reasonable and feasible options for remediation (where relevant) and submit a report to the Department describing those options and any preferred remediation measures or other course of action; and (c) Implement remediation measures as directed by the Planning Secretary. 	Evidence was not available at the time of audit to confirm that reports were provided to DPIE which reviewed control measures and remedial actions required following identified exceedances.	KEQ are in the process of reviewing and where necessary revising the PIRMP. During this process KEQ will review all communication and notification procedures for reporting of pollution exceedances to ARAs.	Deemed as Non- Compliant during the audit. During the audit period, there have been multiple exceedances of the surface water discharge limits, however it is not clear to the auditors whether feasible measures (including a review of appropriate Management Plans) have been taken to ensure the exceedance ceases.
55 <i>,</i> C5	 Within 3 months of: (a) The submission of an annual review under Condition 4 above. (b) The submission of an incident report under Condition 7 below. (c) The submission of an audit report under Condition 9 below; or (d) Any modification to the conditions of this consent, (unless the conditions require otherwise), the Applicant must review the strategies, plans, and programs required under this consent, to the satisfaction of the Planning Secretary. Where this review leads to revisions in any such document, then within 4 weeks of the review the revised document must be submitted for the approval of the Planning Secretary. Note: The purpose of this condition is to ensure that strategies, plans and programs are regularly updated to incorporate any measures recommended to improve environmental performance of the development. 	(a – d) No evidence was available at the time of audit to confirm that KEQ had reviewed strategies, plans and programs required under the approval following audit period Annual Reviews, incidents, audit reports and modifications.	KEQ agree with this recommendation. A controlled templates will be prepared for use when reviewing documents (such as procedures or management plans).	Deemed as Non- Compliant during the audit. Multiple plans and programs required under this consent have not been reviewed within the requirements of this condition. This is discussed in further detail in Appendix A1.

The Statement of Commitments have been removed from the Project Approval following MOD10. Therefore, no further response or action from KEQ is required.

2023 KEQ Response / Action

RESPONSE:

All exceedances of criteria are now reported to the Department and NSW EPA as required.

STATUS: KEQ considers the 2020 findings to be resolved.

Refer to the 2023 audit response for details regarding the 2023 findings.

KEQ considers the 2020 findings to be superseded.



KEQ 2	2020 IEA Action Review – Environment Protection Licence (EPL 20611)				
No	Requirement	Details of Non-Compliance	2020 KEQ Response / Action	2023 IEA Finding	2023 KEQ Response / Action
	L1.1 – Except as may be expressly provided in any other condition of this licence, the licensee	Some discharges during	No recommendation made.	Deemed as Non-Compliant	No actions required.
	must comply with section 120 of the Protection of the Environment Operations Act 1997.	the audit period exceeded		during the audit.	
		the concentration limits			
	L2.1 – For each monitoring/discharge point or utilisation area specified in the table/s below (by a	prescribed by Condition		There have been reoccurrences	
	point number), the concentration of a pollutant discharged at that point, or applied to that area,	L2.4, thereby		of exceedances of surface water	
	must not exceed the concentration limits specified for that pollutant in the table.	contravening Section 120		discharge concentration limits	
		of the POEO Act (see		within this audit period. Further	
	L2.2 – Where a pH quality limit is specified in the table, the specified percentage of samples must	Condition L2.1 below).		details available in Appendix A2	
	be within the specified ranges.			–EPL Table.	
		Uncontrolled and			
		controlled discharges from			
		sediment dams in			
		exceedance of EPL			
		discharge limits occurred			
		during the audit period in			
L1.1,		2017, 2018 and 2019. KEQ			
L2.1,		self-reported the			
L2.2		June 2019 discharge			
		exceedances to EPA on			
		26/06/19 and EPA provided an associated			
		Show Cause Notice' on			
		27/06/19. KEQ provided a			
		response to the Show			
		Cause/notice on			
		02/08/19. EPA issued a			
		Penalty Infringement			
		Notice for the 24 June			
		2019 discharge and			
		Formal Warning regarding			
		the other discharge events			
		of 24 – 27 June 2019 via			
		letter dated 15/08/19.			
	All acoustic bunds necessary to achieve compliance with the noise limits specified in this licence	Acoustic bunding for site	No recommendation made.	Deemed as Non-Compliant	No actions required.
	must be constructed prior to the commencement of quarrying activities and be maintained	infrastructure identified in		during the audit.	
	throughout the operational life of the premises to the height and location described in the Noise	the EA (ADW Johnson,			
	Management Plan.	2013) was not constructed		Acoustic bunding not installed	
		prior to the		during audit period. The	
07.1		commencement of		condition though was varied	
		quarrying operations. See		during the audit period which	
		Schedule 3, Condition 7 of		removed the condition as	
		PA 09_0175.		another control was implement.	
				Further detail is available in	
				Appendix A2 – EPL Table.	



KEQ 2	2023 IEA Findings and KEQ Response – Project Approval (MP09_0175)		
No	Requirement	2023 IEA Assessment & Recommendation	
		 Assessment: (a) An invoice for payment was issued by MidCoast Council to "Branch Land Pty Ltd" in relation to Application No. DA-09-0175 on 11 April 2022 for a value of \$5,000. Remittance Advice for the same amount with the matching supplier invoice reference number (20221212) was provided from MidCoast Council on 10 June 2022. ERM has not been provided with evidence to determine how this contribution amount was calculated and thus cannot verify that compliance with this condition has been met. (b) Road Maintenance Contributions were provided in one invoice to MidCoast Council, with remittance advice prepared on 30 June 2023 for the following amounts: FY2018: \$3,438.77; FY2019: \$14,876.66; FY2020: \$112,797.25; FY2021: \$65,794.58; and FY2022: \$130,498.26. 	RESPONSE: KEQ can confirm (a) Headquarte based on the concerns ha (b) Road mainte provided to compensato the intent of The CPI incre methodolog 13 April 201 Rock Quarry between the apply the sa On 30 June 3 provided to
S3, C11 (d) (ii)	 The Applicant must: (d) Not undertake blasting within 500 metres of: ii. Any land outside the site not owned by the Applicant, unless: The Applicant has a written agreement with the relevant landowner to allow blasting to be carried out closer to the land, and the Applicant has advised the Department in writing of the terms of this agreement, or the Applicant has: Demonstrated to the satisfaction of the Planning Secretary that the blasting can be carried out closer to the land without compromising the safety of the people or livestock on the land, or damaging the buildings and/or structures on the land; and Updated the Blast Management Plan to include the specific measures that would be implemented while blasting is being carried out within 500 metres of the land, to the satisfaction of the Planning Secretary. 	 (e.g. a cost calculation and/or evidence of Council acceptance) that the payments made: Correctly represent the value of the Headquarters Building contribution; and Are based on weighbridge records and increased annually over the life of the development in accordance with the CPI. Should any contribution shortfalls be identified, it is recommended that KEQ make an additional payment to cover this amount as soon as practicable. Assessment: ERM review the Blast Management Plan (BMP) prepared by SLR Consulting Ltd in May 2019. The following potential non-compliance in the BMP was observed: (d) (ii) A property is situated approximately 340 m north-north-west to the closest perimeter of the quarry. It is understood that the property is unoccupied, however the land is privately owned. As a result, it is considered that blasting activities during the audit period would have occurred within 500m of privately owned land without a written agreement or as to the satisfaction of the Planning Secretary. Recommendation: It was confirmed that the sale of the property within 500 m of the KEQ quarry pit took place. Therefore, no	corresponde this matter. FY23 was pr advice date) on 28 Augu Council rega from the Kan STATUS: KEQ considers th RESPONSE: KEQ can confirm acquired. STATUS: KEQ considers th

2023 KEQ Response / Action

rm:

ters building contribution was provided to Council the capital investment value of the project. No have been raised by Council.

ntenance contributions for FY18 to FY22 was to Council on 30 June 2023. This was subject to atory cost escalation in accordance with CPI as per t of the Condition.

acreases were completed in accordance with the logy provided by the former Great Lakes Council on 010 in relation to affiliated quarry, Karuah Hard rry (DA 265-10-2004). Given the close relationship the two quarry sites, KEQ considers it appropriate to same methodology.

ne 2023, Council advised the matter had been to the Manager Finance for review. No further indence has been received from Council regarding er.

provided to Council on 03 August 2023 (remittance te). Council acknowledged receipt of the payment ugust 2023. No concerns have been raised by egarding the provision of Developer Contributions Karuah East Quarry.

this 2023 finding to be resolved.

rm the property (Lot 4, DP838128) has been

s this 2023 finding to be resolved.



KEQ 2	2023 IEA Findings and KEQ	Response – Pro	ject Approval (MP09_0	0175)		
No		Re	equirement		2023 IEA Assessment & Recommendation	
S3, C12	 the Planning Secretar (b) Be prepared in consult Secretary for approvation (c) Describe the measure best managemen compliance with (d) Include a road closure (e) Include a specific blass will be minimised include and 	are a Blast Mana ng Secretary. The cably qualified e ry; Itation with Cou al prior to the co es that would be the relevant cou e protocol if bla st fume manage luding risk mana program for even the applicable of emissions from	agement Plan for the de is plan must: xpert whose appointme uncil and EPA, and subn ommencement of const e implemented to ensur ng employed; and nditions of this consent sting occurs within 500 ment protocol, to dem agement strategies if bl aluating the performan criteria; and the site.	ent has been approved by nitted to the Planning cruction activities. re: ; metres of a public road onstrate how emissions last fumes are generated; ce of the development	 Assessment: ERM reviewed the Blast Management Plan (BMP) prepared by SLR Consulting Ltd in May 2019. The following potential non-compliance in the BMP was observed: (b) The BMP includes evidence of consultation with the EPA and Council and DPE approval occurring in 2015. There is no evidence of consultation provided for the May 2019 update. (c) Best management and control measures are discussed in section 6 of the BMP including operating conditions, blast design, public safety, road closure management, monitoring of meteorological conditions, avoidance of concurrent blasts with nearby quarrying operations, and consultation with neighbouring residences. For most conditions of this consent, the BMP describes measures to be implemented to ensure compliance is met, however in relation to condition 11 (d), the BMP does not describe the details of measures implemented to ensure a blast is not carried out within 500m of land outside the site not owned by the Applicant. Recommendation: The BMP is recommended to be updated to account for control measures carried out in order to meet compliance with Condition 11 d) ii and approved by the Planning Secretary. The BMP is recommended to be updated in consultation with the Council and EPA 	ACTION: KEQ to complete Management PI Planning Secreta DUE: 28 May 2024 in STATUS: Underway – dra completed by IE accordance with
S3, C13	The Applicant must ensur measures are employed s development do not exce owned land. <i>Table 7: Long-term impact asse</i> Pollutant Total suspended particul Particulate matter < 10 <i>Table 8: Short-term impact asse</i> Pollutant Particulate matter < 10 <i>Table 9: Long-term Impact Asse</i> Pollutant © Deposited dust	ed that particula ed the criteria i essment criteria for p lates (TSP) μm (PM ₁₀) μm (PM ₁₀)	te matter emissions ge n Tables 7 to 9 at any n articulate matter Averaging period Annual Annual articulate matter Averaging period 24 hour	nerated by the	and be submitted to the Planning Secretary. Assessment: Annual reviews report the measured particulate matter (PM) and depositional dust (DD) results against the approved criteria of this condition. The Short-term impact assessment criteria for particulate matter was exceeded on one occasion during the audit period and there were two "failure to monitor" events which ERM consider having been appropriately responded to. Additional detail relating to compliance with this CoC is provided in Appendix A1. Recommendation: It is recommended to continue the monitoring per the AQMP as only one low-range exceedance was recorded during the audit period. Should additional exceedances reoccur, examine additional mitigation measures in conjunction with a review of the AQMP.	ACTION: KEQ to include t review of the Ai Refer to the resp details.

2023 KEQ Response / Action

ete a comprehensive review of the Blast Plan and submit the revised document to the etary for approval.

in accordance with Schedule 5, Condition 5(c).

draft revision of the management plan has been IEMA. Further revisions are to be assessed in *v*ith these recommendations.

e this recommendation into the comprehensive Air Quality Management Plan.

esponse under Schedule 3, Condition 16 for further



KEQ 2	2023 IEA Findings and KEQ Response – Project Approval (MP09_0175)		
No	Requirement	2023 IEA Assessment & Recommendation	
S3, C16	 The Applicant must prepare an Air Quality Management Plan for the development to the satisfaction of the Planning Secretary. This plan must: (a) Be prepared by a suitably qualified expert whose appointment has been approved by the Planning Secretary. (b) Be prepared in consultation with Council and EPA and submitted for approval to the Planning Secretary prior to the commencement of construction activities. (c) Describe the measures that would be implemented to ensure: Compliance with the relevant air quality conditions of this consent; best management practice is employed; and The air quality impacts of the development are minimised during adverse meteorological conditions and extraordinary events. (d) Describe the proposed air quality management system; and (e) Include a monitoring program that: Can evaluate the performance of the development. Includes a protocol for determining any exceedances of the relevant conditions of consent. Effectively supports the air quality management system; and Evaluates and reports on the adequacy of the air quality management system. 	Assessment: The AQMP was most recently updated in May 2019 by SLR Consulting. Whilst ERM consider KEQ are generally compliant with conditions (a) to (e), implementation of the plan requires a period review in accordance with Schedule 5 Condition 5 meaning that the 2019 version of the AQMP is now outdated. Additional detail relating to compliance with this CoC is provided in Appendix A1. Recommendation: Refer to recommendation under Schedule 5 Condition 4 in relation to updates of strategies, plans and programs required under this consent.	ACTION: KEQ to complete Management Pla Planning Secreta DUE: 28 May 2024 in a STATUS: Underway – drat completed by IE accordance with
S3, C19	The Applicant must comply with the discharge limits in any EPL, or with Section 120 of the POEO Act.	Assessment:There are three Licenced Discharge Points (LDP) associated with the site. This includes LDP001 (Dam 1), LDP002 (Dam 2) and LDP003 (Dam 3). Discharge results are recorded within the KEQ Discharge Register. Heavy rainfall, particularly in 2021 and 2022 resulted in multiple uncontrolled and non-compliant discharges during the audit period. A review of the WMP has not been carried out as required following the multiple exceedances of the discharge limits. Additional detail relating to compliance with this CoC is provided in Appendix A1.Recommendation: Conduct a review the effectiveness of the WMP and TARP to ensure that the response plans can be effectively implemented to prevent exceedances of relevant water quality assessment criteria and ensure sufficient capacity is available in dams.The review should consider the multiple surface water discharge exceedances of associated response procedures. The review should be conducted by a suitable qualified specialist and recommendations	ACTION: KEQ to include t comprehensive Refer to the resp details.
S3, C21	 The Applicant must prepare a Water Management Plan for the development to the satisfaction of the Planning Secretary. This plan must: (a) Be prepared in consultation with the EPA and DPE Water by suitably qualified and experienced person/s whose appointment has been approved by the Planning Secretary. (b) Be submitted to the Planning Secretary for approval prior to the commencement of construction activities. (c) Include: i. A Site Water Balance that includes details of: • Sources and security of water supply, including contingencyplanning; 	should be reflected within an update to the WMP. Assessment: The KEQ Water Management Plan (WMP) was prepared by SLR Consulting Ltd and most recently updated in May 2019. There is no evidence to confirm a review has taken place due to exceedances in surface water discharge limits (refer Section 3 Condition 19). Additional detail relating to compliance with this CoC is provided in Appendix A1.	ACTION: KEQ to complete Management Pla Planning Secreta DUE: 28 May 2024 in a

2023 KEQ Response / Action

ete a comprehensive review of the Air Quality Plan and submit the revised document to the etary for approval.

n accordance with Schedule 5, Condition 5(c).

raft revision of the management plan has been IEMA. A further revision is to be assessed in th these recommendations.

e these two recommendations into the e review of the Water Management Plan.

sponse under Schedule 3, Condition 21 for further

ete a comprehensive review of the Water Plan and submit the revised document to the etary for approval.

n accordance with Schedule 5, Condition 5(c).



KEQ 2	023 IEA Findings and KEQ Response – Project Approval (MP09_0175)		
No	Requirement	2023 IEA Assessment & Recommendation	
	 Water use on site; and Measures that would be implemented to minimise use of clean water and maximise recycling of dirty water on the site. A Surface Water Management Plan, that includes: Baseline data on surface water flows and quality in the watercourses that could be affected by the development. A detailed description of the surface water management system on the site, including the design objectives and performance criteria for the: clean water diversions; erosion and sediment controls; water storages (including Maximum Harvestable Rights requirements); and control of water pollution from areas of the site that have been rehabilitated. Surface water impact assessment criteria, to be developed following analysis of baseline data, including trigger levels for investigating any potentially adverse surface water quality impacts. A program to monitor: any surface water discharges; the effectiveness of the water courses; and ecosystem health of local watercourses; and ecosystem health of local watercourses; and A surdace water impact assessment criteria, to be developed following analysis of baseline data, including trigger levels for investigating any potentially adverse groundwater levels surrounding the site. A foroundwater Monitoring Program that includes: Baseline data of groundwater levels surrounding the site. Groundwater Monitoring Program that includes: Baseline data of groundwater levels surrounding the site. Groundwater impact assessment criteria, to be developed following analysis of baseline data, including trigger levels for investigating any potentially adve	 Recommendation: The following recommendations are made in relation the WMP: Updates to the WMP should include details of a contingency plan; It is recommended that KEQ implement a framework to log all steps and actions to be taken in accordance with the TARP, in particular when a 'Condition Amber' or 'Condition Red' Trigger Response is enacted. WMP updates are to be undertaken in consultation with the EPA and DPE Water and be submitted to the Planning Secretary. Additional recommendations which are applicable to this condition are made in relation to Adaptive Management (refer Schedule 5 Condition 2). 	STATUS: Underway – IEM management pla be incorporated
	The Applicant must implement the plan as approved by the Planning Secretary The Applicant must keep accurate records of all laden truck movements to and from the site (including time of arrival and dispatch) and publish a summary of records on its	Assessment: Monitoring of product transport is recorded and uploaded to Hunter	ACTION: KEQ to include la
S3, C23	website every 6 months and in the Annual Review.	Quarry's website under Karuah East Quarry. The monitoring data includes hourly truck movements for every day of each calendar year. Laden truck movements are not recorded within the KEQ Annual Reviews.	all future submis DUE: 31 March 2024 i
		Recommendation: It is recommended to publish a summary of laden truck movements to and from site in future Annual Reviews.	STATUS: Completed – Pro 2023 Annual Rev

2023 KEQ Response / Action

MA has been engaged to draft a revision of the plan. These water-themed recommendations will ed.

e laden truck movements in the Annual Reviews for nissions.

4 in accordance with Schedule 5, Condition 4.

Product transport report has been included in the Review document template.



KEQ 2	2023 IEA Findings and K	EQ Response – Project Approval (N	/IP09_0175)		
No		Requirement		2023 IEA Assessment & Recommendation	
	Modification 10, finalis in condition 2 of Scheo conceptually in Figure satisfaction of the Plar	rior to the commencement of veget se the Biodiversity Offset Strategy, a dule 2, summarised in Table 10 and 1 of Appendix 4, in consultation wi nning Secretary. at Strategy – land-based offsets	as described in documents listed Table 11 and shown	Assessment: As Table 10 pre-existed Modification 10, in accordance with Condition 5 of Schedule 5, the Biodiversity Offset Strategy should have been updated within 3 months of any modification to the conditions of this consent. It is noted that latest version of the BOS is dated July 2013.	ACTION: KEQ to complete Offset Strategy a Secretary for app DUE:
	Area Offset Area	Offset Type Existing vegetation to be managed and enhanced	Minimum Size (ha) 130.36 ha	At the time of writing, as confirmed by Site Management, the updated Biodiversity Offset Strategy is pending Commonwealth EPBC Approval.	TBD – pending t MOD10 (EPBC 2 1999.
S3, C28	Credit Type Ecosystem Credits PCT 1619: Smooth-barked / Hairpin Banksia heathy oper PCT 695: Blackbutt – Turpe coastal foothills of the central Species Credits Tetratheca juncea (Black-ey Grevillea parviflora subsp. p. Squirrel Glider (Petaurus not Southern Myotis (<u>Myotis man</u> Notes: 1. The Biodiversity Offset Strate dwelling-houses and associa structures so as to preserve must also provide details of	Apple – Red Bloodwood – Brown Stringybark – h forest of coastal lowlands ntine – Tallowwood shrubby open forest of the h NSW North Coast Bioregion Total ed Susan) arviflora (Small-flower Grevillea) rfolcensis) cropus) Total egy must direct that the land proposed as the Offset A ated sheds, bushfire asset protection zones and of the integrity and function of that offset area. The Bio the integrity and function of that offset area. The Bio the revegetation of any parts of the offset area the wise substantially modified state, other than required	7 195 260 250 260 107 877 Area must be free of any other related utilities or diversity Offset Strategy at are cleared of native	It was confirmed by Site Management and observed by the auditors during the site visit that no vegetation clearing activities have taken place for Modification 10 and thus an assessment of compliance against Table 11 of this condition is Not Triggered. <u>Recommendation:</u> Consultation with the BCD and Council in relation to this condition is recommended to be published in the latest Biodiversity Offset Strategy and uploaded to the Hunter Quarries website. Review and update the BOS when the consent is modified.	 STATUS: Table 10 – Unde KEQ is c regardin Table 11 (Ecosys PCT1619 PCT695 Table 11 (Specie Black-ey credits h credit pi Small-flo credit pi Squirrel with the Souther purchas
S3, C32	 Credits required for impacts to Within 6 months of the Landscape and Rehabil of the Planning Secretar perimeter lands. This perimeter lands.	e EPBC Act listed species and associated habitats mu e date of approval of Modification i litation Management Plan for the c ary. This Plan would relate to the a plan must: suitably qualified expert whose app	1, the Applicant must prepare a development to the satisfaction rea of the quarry and all pointment has been approved by and submitted to the Planning of construction activities; juncea Translocation Program of the site; that would be implemented to: site; and ives and progressive a for evaluating the performance any remedial action; yould be implemented over the llowing initial preparation of the	Assessment: The Landscape and Rehabilitation Management Plan (LRMP) was most recently updated in March 2020. The LRMP has not been updated within a 3 year period as required by clause (f) of this condition. Additional detail relating to compliance with this CoC is provided in Appendix A1. Recommendation: Ensure the LRMP is updated every 3 years and that implementation of measures detailed in the plan have been reviewed and updated where required. Scheduled reminders should be implemented to ensure that future updates of the LRMP are undertaken within the required 3 year period. Where required, update associated monitoring programs to ensure the effectiveness of the procedures can be effectively measured.	ACTION: KEQ to complete Rehabilitation M document to the DUE: 28 May 2024 in NOTE – this may Commonwealth the Commonwealth the Commonweal STATUS: Underway – The plan is complete being reviewed delayed, subject

2023 KEQ Response / Action

ete a comprehensive review of the Biodiversity y and submit the revised document to the Planning approval.

the receipt of Commonwealth Approval for 2022 – 9164) under the Commonwealth EPBC Act

derway:

continuing to engage with NSW Planning ling the mechanism used for the land-based offset.

ystem Credits) – Underway:

619 have been secured. 95 have been secured.

ies Credits) – Underway:

eyed Susan – in-principle sale agreement for 25x s has been reached. KEQ are continuing to review purchase options for the outstanding credits. flower Grevillea – KEQ are continuing to review purchase options.

el Glider – purchase agreement has been executed he Credit Supply Taskforce.

ern Myotis – KEQ are continuing to review credit ase options.

ete a comprehensive review of the Landscape and Management Plan and submit the revised the Planning Secretary for approval.

n accordance with Schedule 5, Condition 5(c). ay be delayed, subject to the receipt of th Approval for MOD10 (EPBC 2022 – 9164) under vealth EPBC Act 1999.

The rehabilitation component of the management ete; and the landscape component is currently ed by KEQ's ecologist. However, this may be ect to Commonwealth approval.



KEQ 2	2023 IEA Findings and KEQ Response – Project Approval (MP09_0175)		
No	Requirement	2023 IEA Assessment & Recommendation	
	 Ensuring compliance with the rehabilitation objectives and progressive 		
	rehabilitation obligations of this consent;		
	 Enhancing the quality of remnant vegetation and fauna habitat; 		
	 Restoring native endemic vegetation and fauna habitat within the rehabilitation 		
	area, including details of the target revegetation communities of the rehabilitated		
	landform;		
	 Coordinating the relocation of native fauna to protected habitats associated with 		
	preclearing fauna surveys;		
	 Maximising the salvage of environmental resources within the approved 		
	disturbance area - including tree hollows, vegetative and soil resources - for		
	beneficial reuse in the enhancement of the rehabilitation area;		
	 Collecting and propagating seed; 		
	 Ensuring minimal environmental consequences for threatened species, 		
	populations and habitats;		
	 Minimising the impacts on native fauna on site, including the details and 		
	implementation of appropriate pre-clearance surveys;		
	Minimising the impacts on fauna movement between undisturbed areas of the		
	site and nearby vegetation (including potential fauna crossings);		
	 Controlling weeds and feral pests; 		
	Controlling erosion;		
	Controlling access and providing for management trails; and		
	Bushfire management and implementation of ecologically appropriate bushfire		
	intervals.		
	(i) Include a program to monitor the effectiveness of these measures, and progress		
	against the performance and completion criteria. (j) Identify the potential risks to successful implementation of the Tetratheca juncea		
	translocation Program and rehabilitation of the site, and include a description of the		
	contingency measures that would be implemented to mitigate these risks.		
	(k) Include details as to how the rehabilitated land would be permanently conserved and		
	managed as part of the broader Biodiversity Offset Area approved in these conditions.		
	(I) Include details of who would be responsible for monitoring, reviewing, and		
	implementing the plan; and		
	(m) Include details as to the timing of actions set out in the plan		
	The Applicant must implement the plan as approved by the Planning Secretary.		
	The Applicant must prepare a Biodiversity Offset Area Management Plan for the	Assessment:	ACTION:
	development to the satisfaction of the Planning Secretary. This Plan would relate to the	The Biodiversity Offset Area Management Plan (BOAMP) was most	KEQ to cont
	area of the Biodiversity Offset Area required in these conditions. This plan must:	recently updated in April 2021. A number of outstanding actions	in accordance
	(a) Be prepared by a suitably qualified expert whose appointment has been approved by	recommended within the latest Ecological Monitoring Report	will need to
	the Planning Secretary	(included within the 2022 Annual Review) have not been closed out	monitoring
	(b) Be prepared in consultation with BCD and Council	and constitutes a non-compliance against clause (h) of this condition.	
	(c) Describe how the implementation of the Tetratheca juncea Translocation Program	Additional detail relating to compliance with this CoC is provided in	DUE:
S3,	would be integrated with the Biodiversity Offset Area management.	Appendix A1.	As soon as p
C33	(d) Describe the short, medium and long-term measures that would be implemented to		
	manage remnant vegetation and habitat on the Biodiversity Offset Area	Recommendation:	STATUS:
	(e) Include detailed performance and completion criteria for evaluating the performance	ERM notes that KEQ have implemented a "BOA Completion Status and	Underway –
	of the conservation, restoration and management of the Biodiversity Offset Area,	Action Plan" and recommends that the status of actions be reviewed	surrounding
	including triggers for any remedial action. (f) Providing for the transfer of environmental resources from the approved disturbance	and updated as soon as practicable.	
	(f) Providing for the transfer of environmental resources from the approved disturbance area - including tree hollows, vegetative and soil resources - for beneficial reuse in the		
	enhancement of the Biodiversity Offset Area.		

2023 KEQ Response / Action

ntinue implementing the 2022 BOA Monitoring Actions ance with the developed action plan. This action plan to be consolidated to include actions from the 2023 g period.

practicable.

 The key action of repairs to fauna fencing ng Dam 1 commenced 30 January 2024.



KEQ	2023 IEA Findings and KEQ Response – Project Approval (MP09_0175)		
No	Requirement	2023 IEA Assessment & Recommendation	
	 (g) Providing for the incorporation of the final rehabilitated landform into the Biodiversity Offset Area and its management. (h) Include a detailed description of the measures that would be implemented over the next 3 years (to be updated for each 3-year period following initial preparation of the plan), including the procedures to be implemented for: Enhancing the quality of remnant vegetation and fauna habitat Restoring native endemic vegetation and fauna habitat within the parts of the Biodiversity Offset Area that are cleared or modified, including details of the target revegetation communities of the restored landform. Coordinating the relocation of native fauna to protected habitats associated with preclearing fauna surveys. Collecting and propagating seed Maximising the protection and restoration of threatened species, populations and habitats. Controlling weeds and feral pests Controlling erosion Controlling access and providing for management trails; and Bushfire management and implementation of ecologically appropriate bushfire intervals. (j) Include a program to monitor the effectiveness of these measures, and progress against the performance and completion criteria. (j) Identify the potential risks to successful implementation of the Biodiversity Offset program and include a description of the contingency measures that would be implemented to mitigate these risks. (k) Include details of who would be responsible for monitoring, reviewing, and implementing the plan. (l) Include details of the indicative costs of management actions; and 		
S3, C39	(m) Include details as to the timing of actions set out in the plan. The Applicant must ensure that the storage, handling, and transport of dangerous goods and hazardous materials is conducted in accordance with the relevant Australian Standards, particularly AS1940 and AS1596, and the Dangerous Goods Code.	Assessment:KEQ have developed a Hazardous Substances (SDS) Register, most recently updated in December 2022, which describes the list of products, quantities, location on site, type of application, SDS issue and expiry dates, and "stability and reactivities" classification.Based on a review of tank compliance plates, tank brochures and site observations, the auditors are satisfied that dangerous good and hazardous materials are stored in accordance with AS1940, AS1596 ad the Dangerous Goods Code. However, it is noted that neither of the Diesel ASTs are included on the Hazardous Substances Register.Recommendation: The hazardous materials storage container should be repaired (to ensure it does not allow rainfall to fill the bund – making it inoperable) to ensure it complies with AS1940.It is recommended to update the Hazardous Subsidence Register to ensure it includes both diesel ASTs.	ACTIONS: 1. KEQ to rev implement 2. KEQ to rev KEQ repor revisions a DUE: As soon as pra

2023 KEQ Response / Action

eview repair options to the storage container and ent as needed.

eview Hazardous Substances Register and include in orting processes to ensure routine updates and sare carried out.

racticable.



KEQ 2	2023 IEA Findings and KEQ Response – Project Approval (MP09_0175)		
No	Requirement	2023 IEA Assessment & Recommendation	
S5, C1	 The Applicant must prepare an Environmental Management Strategy for the development to the satisfaction of the Planning Secretary. This strategy must: (a) Be submitted to the Planning Secretary for approval prior to the commencement of construction activities (b) Provide the strategic framework for environmental management of the development. (c) Identify the statutory approvals that apply to the development. (d) Describe the role, responsibility, authority and accountability of all key personnel involved in the environmental management of the development. (e) Describe the procedures that would be implemented to: Keep the local community and relevant agencies informed about the operation and environmental performance of the development. Receive, handle, respond to, and record complaints; • resolve any disputes that may arise during the course of the development; respond to any non-compliance; and Respond to emergencies; and (f) Include: Copies of any strategies, plans and programs approved under the conditions of this consent; and Clear plan depicting all the monitoring required to be carried out under the conditions of this consent. 	Assessment: The latest version of the Environmental Management Strategy (EMS) was prepared in December 2015. It is noted that there are references to management plans within the EMS which are now superseded, therefore the version is not considered up to date as required by clause (f) of this condition. Additional detail relating to compliance with this CoC is provided in Appendix A1. Recommendation: It is recommended that a review of the EMS be undertaken and updated where required to ensure it is current. This includes but not limited to updates in statutory requirements and references to updated management plans and monitoring programs.	ACTION: KEQ to complete Management Str Planning Secreta DUE: 28 May 2024 in a STATUS: Underway – drat completed by IE accordance with
S5, C2	 The Applicant must implement the strategy as approved by the Planning Secretary. The Applicant must assess and manage development-related risks to ensure that there are no exceedances of the criteria and/or performance measures in this consent. Any exceedance of these criteria and/or performance measures constitutes a breach of this consent and may be subject to penalty or offence provisions under the EP&A Act or EP&A Regulation. Where any exceedance of these criteria and/or performance measures has occurred, the Applicant must, at the earliest opportunity: (a) Take all reasonable and feasible measures to ensure that the exceedance ceases and does not recur. (b) Consider all reasonable and feasible options for remediation (where relevant) and submit a report to the Department describing those options and any preferred remediation measures or other course of action; and (c) Implement remediation measures as directed by the Planning Secretary. 	 Assessment: (a) During the audit period, there have been multiple exceedances of the surface water discharge limits, however it is not clear to the auditors whether feasible measures (including a review of appropriate Management Plans) have been taken to ensure the exceedance ceases. (b) Example incident reports have been issued to the DPE and reviewed by ERM. Some incident reports have not been issued to the Department immediately after an incident occurred. (c) There have been no specific remediation measures directed by the Planning Secretary within this audit period. Recommendation: Conduct a review of short term adaptive management processes to consider whether temporary solutions such as pumping and storage of water to enable short term provisioning of additional capacity is recommended. The above recommendations should be incorporated within an update to the Water Management Plan. 	
S5, C4	 By the end of March each year, the Applicant must review the environmental performance of the development to the satisfaction of the Planning Secretary. This review must: (a) describe the development (including rehabilitation) that was carried out in the previous calendar year, and the development that is proposed to be carried out over the current calendar year. 	Assessment: The Annual Reviews which are applicable within this audit period are for the years 2020, 2021 and 2022. The auditors reviewed the Annual Reviews and confirm each contain the required details as listed within (a) to (f) of this condition.	RESPONSE: KEQ acknowledg submission. KEQ processes to ens stakeholders is c

2023 KEQ Response / Action

ete a comprehensive review of the Environmental Strategy and submit the revised document to the etary for approval.

in accordance with Schedule 5, Condition 5(c).

Iraft revision of the management plan has been IEMA. A further revision is to be assessed in ith this recommendation.

bleted a water management review of the KEQ site stember 2023, which concluded no reasonable n measures could be completed without securing oprovals.

KEQ disagrees with the non-compliance findings.

e these two recommendations into the ve review of the Water Management Plan.

esponse under Schedule 3, Condition 21 for further

edges the 2022 Annual Review was subject a late EQ has since implemented improved reporting ensure submission of documents to external is completed.



KEQ 2	2023 IEA Findings and KEQ Response – Project Approval (MP09_0175)		
No	Requirement	2023 IEA Assessment & Recommendation	
	 (b) include a comprehensive review of the monitoring results and complaints records of the development over the previous calendar year, which includes a comparison of these results against: The relevant statutory requirements, limits or performance measures/criteria; The monitoring results of previous years; and The relevant predictions in the documents referred to in condition 2(d) of Schedule 2 of this consent. (c) identify any non-compliance over the last year, and describe what actions were (or are being) taken to ensure compliance. (d) identify any trends in the monitoring data over the life of the development; (e) identify any discrepancies between the predicted and actual impacts of the development and analyse the potential cause of any significant discrepancies; and (f) describe the measures that would be implemented over the current calendar year to improve the environmental performance of the development. 	Following consultation with the Planning Secretary and as captured within the 2022 Annual Review and "Post Approval Document Received" email notification, the 2021 Annual Review was identified to have been lodged in October 2022 therefore considered a late submission in accordance with this condition. <u>Recommendation:</u> It is recommended that all Annual Reviews are submitted to the Planning Secretary by the end of March each year.	STATUS: Completed – no
S5, C5	 Within 3 months of: (a) The submission of an annual review under Condition 4 above. (b) The submission of an incident report under Condition 7 below. (c) The submission of an audit report under Condition 9 below; or (d) Any modification to the conditions of this consent, (unless the conditions require otherwise), the Applicant must review the strategies, plans, and programs required under this consent, to the satisfaction of the Planning Secretary. Where this review leads to revisions in any such document, then within 4 weeks of the review the revised document must be submitted for the approval of the Planning Secretary. Note: The purpose of this condition is to ensure that strategies, plans and programs are regularly updated to incorporate any measures recommended to improve environmental performance of the development. 	Assessment: The management plans and strategies which are applicable to this condition are as follows: Environmental Management Strategy – dated Dec 2015 Air Quality Management Plan – dated May 2019 Blast Management Plan – dated May 2019 Noise Management Plan – dated May 2019 Noise Management Plan – dated May 2019 Heritage Management Plan – dated May 2019 Traffic Management Plan – dated May 2019 Traffic Management Plan – dated May 2019 Traffic Management Plan – dated December 2015 Tetratheca Juncea Translocation Plan – dated January 2019 Biodiversity Offset Strategy – dated July 2013 Landscape and Rehabilitation Management Plan – dated March 2020 Biodiversity Offset Area Management Plan – dated April 2021 There is no evidence within the respective strategies, plans and programs required under this consent to demonstrate that a review has taken place within the requirements of this condition. Recommendation: Ensure that all strategies, plans and programs required under this consent are updated to include a document control or similar so that revision dates are clear to the reader. Opportunities to improve notification systems are recommended to be reviewed to ensure programs are revised within the timeframes as required under this consent.	RESPONSE: KEQ acknowledg consultation and requires signific In 2023, KEQ ha document contr numbers, and a new Manageme document upda ACTIONS: Refer to constitu actions. STATUS: Completed – do

2023 KEQ Response / Action

no further actions required.

dges the review, revision, completion of agency nd re-submission of statutory management plans icant improvement.

has implemented a new document template, htrol system (inclusive of Document ID and version a consolidated document history table) as well as a ment Plan register to enable improved timeliness of dates when revision triggers are reached.

ituent management plan conditions for individual

document management system.



KEQ 20	EQ 2023 IEA Findings and KEQ Response - Environment Protection Licence (EPL 20611)					
No	Requirement	2023 IEA Assessment	2023 IEA Recommendation	2023 KEQ Response / Action		
L1.1, L2.1, L2.2	 L1.1 – Except as may be expressly provided in any other condition of this licence, the licensee must comply with section 120 of the Protection of the Environment Operations Act 1997. L2.1 – For each monitoring/discharge point or utilisation area specified in the table/s below (by a point number), the concentration of a pollutant discharged at that point, or applied to that area, must not exceed the concentration limits specified for that pollutant in the table. L2.2 – Where a pH quality limit is specified in the table, the specified percentage of samples must be within the specified ranges. 	 From the review of the Annual Returns and Surface Water Monitoring Discharge Register it is noted that numerous reoccurring uncontrolled discharges of surface waters that exceed the concentration limits have occurred during the audit period. According to the Discharge Register, the following discharges were recorded which exceeded the concentration limits defined in EPL 20611 [summary]: 2020 – a total of 11 discharges non-compliant with the EPL concentration limits. 2021 – a total of 18 discharges non-compliant with the EPL concentration limits. 2022 – a total of 29 discharges non-compliant with the EPL concentration limits. 2022 – a total of 29 discharges non-compliant with the EPL concentration limits. 2021 – a total of 29 discharges non-compliant with the EPL concentration limits. 2022 – a total of 29 discharges non-compliant with the EPL concentration limits. 2021 – a total of 29 discharges non-compliant with the EPL concentration limits. 2022 – a total of 29 discharges non-compliant with the EPL concentration limits. All discharges exceeding the concentration criteria have been reported within the Annual Returns. Heavy rainfall, particularly in 2021 and 2022 resulted in multiple uncontrolled and non-compliant discharges during the audit period. A review of the WMP has not been carried out as required following the multiple exceedances of the discharge limits. It is not clear whether the response 	Conduct a detailed review of the effectiveness of the WMP, inclusive of the TARP to ensure that management measure are appropriate to ensure sufficient storage capacity of the KEQ dams is effectively maintained, such that uncontrolled discharges do not occur. The review should consider the multiple surface water discharge exceedances which took place in 2020, 2021 and 2022 and the effectiveness of associated preventative measures and procedures, such as scheduling of dam desedimentation works prior to forecast rainfall events. The review should be conducted by a suitably qualified specialist and recommendations should be reflected within an update to the WMP. It is recommended that KEQimplement a framework to log all steps and actions to be taken in accordance with the TARP, in particular when a 'Condition Amber' or 'Condition Red' Trigger Response is enacted.	Duplicate recommendations. Refer to water-related conditions of the Project Approval for further details.		
01.1, 05.1, 05.2	 O1.1 – Licensed activities must be carried out in a competent manner. This includes: (a) The processing, handling, movement and storage of materials and substances used to carry out the activity; and (b) The treatment, storage, processing, reprocessing, transport and disposal of waste generated by the activity. O5.1 – All tanks and storage areas for drums containing material that has potential to cause environmental harm must be bunded or have an alternative spill containment system inplace. The bunding and/or spill containment systems must be properly designed, engineered, and constructed to be suitable for the material types and quantities stored therein in accordance with all appropriate standards, including Australian Standards (AS)1940 and AS1596. O5.2 – Bunds must: (a) have walls and floors constructed of impervious materials; (b) Be of sufficient capacity to contain 110% of the volume of the tank (or 110% volume of the largest tank where a group of tanks are installed); (c) Have floors graded to a collection sump; (d) Not have a drain valve incorporated in the bund structure; or be constructed and operated in a manner that achieves the same environmental outcome. 	procedures described in the WMP are effective in preventing non-compliant discharges during heavy rainfall. Lubricants and associated materials were stored within a hazardous material storage container that was no longer structurally sound and open to the weather which results in the bund being filled with water, this considered non- compliant with this condition. There are two aboveground storage tanks (ASTs) containing diesel onsite, both of which comprise a double walled construction. The primary storage area has been constructed with a drainage system to sump, but the sump was noted to be under-sized and it would offer limited containment in the event of a spill.	The hazardous materials storage container should be repaired (to ensure it does not allow rainfall to fill the bund – making it inoperable) to ensure it complies with AS1940.	Duplicate recommendation. Refer to the Schedule 3, Condition 39 for further details.		



KEQ 20	Q 2023 IEA Findings and KEQ Response - Environment Protection Licence (EPL 20611)				
No	Requirement	2023 IEA Assessment	2023 IEA Recommendation	2023 KEQ Response / Action	
	 O3.1 – The premises must be maintained in a condition which minimises or prevents the emission of dust from the premises. O3.2 - Any activity carried out in or on the premises must be carried out by such practical means as to prevent dust or minimise the emission of dust to the air. 	Central control room to manage dust suppression sprays at each transfer point and stockpile within crushing and screening plant. Water spray truck actively wets internal roads and product stockpiles. Biggest observable issue during the site visit was noted to be from main drop point to boot – jaw crusher.	As only a single incident of a lowrange exceedance occurred during the audit period, no specific recommendations are made beyond continuing to monitor for exceedances as per the requirement of the EPL.	Duplicate recommendations. Refer to air quality- related conditions of the Project Approval for	
03.1, 03.2, 03.3	O3.3 – Any plant operated in or on the premises must be operated by such practical means to prevent or minimise dust or other air pollutants.	 Across the audit period it was noted that dust was generally managed in accordance with this condition, although an exceedance of the air quality limits stated in the Project Approval, as below: Short term PM: One exceedance of the short-term criteria for PM10, occurring on 16 June 2023 with a PM10 monitoring value of 51 µg/m3. This result is considered a low-range exceedance with the PM10 limit of 50 µg/m3 and as this is the only exceedance recorded within this audit period, no further actions are recommended at this stage. 	If exceedances reoccur examine additional measure to manage.	further details.	
07.1	All acoustic bunds necessary to achieve compliance with the noise limits specified in this licence must be constructed prior to the commencement of quarrying activities and be maintained throughout the operational life of the premises to the height and location described in the Noise Management Plan.	It was noted in the Annual return for the reporting period 26-08-2020 to 25-08-2021 that acoustic bunding was not constructed as required by condition O7.1 as it was deemed to be ineffective. Enclosures were built around the crushers which meets noise limit protection requirements. The EPL was varied on 02/09/2022, removing the requirement for bunding and amending condition O7.1. The noncompliance noted for this condition was limited to the previous version of the EPL. The site is compliant as at the close of the audit period.	As the original requirement has been removed from the EPL condition, no further action is recommended.	RESPONSE: KEQ disagrees with this finding as the implementation of noise enclosures as part of MOD8 addressed the intent of this condition which was not removed at the time due to administrative oversight.	
M2.1, M3.1	 M2.1 – For each monitoring/discharge point or utilisation area specified below (by a point number), the licensee must monitor (by sampling and obtaining results by analysis) the concentration of each pollutant specified in Column 1. The licensee must use the sampling method, units of measure, and sample at the frequency, specified opposite in the other columns. M3.1 – Monitoring for the concentration of a pollutant emitted to the air required to be conducted by this licence must be done in accordance with: (a) Any methodology which is required by or under the Act to be used for the testing of the concentration of the pollutant; or (b) If no such requirement is imposed by or under the Act, any methodology which a condition of this licence requires to be used for that testing; or (c) If no such requirement is imposed by or under the Act or by a condition of this licence, any methodology approved in writing by the EPA for the purposes of that testing prior to the testing place. Note: The Protection of the Environment Operations (Clean Air) Regulation 2021 requires testing for certain purposes to be conducted in accordance with test methods contained in the publication "Approved Methods for the Sampling and Analysis of Air Pollutants in NSW". 	 Monitoring of discharges is outlined in Section 8.1.3 of the WMP. The monitoring frequency is generally conducted in accordance with Condition M2.1. Examples of air quality monitoring for deposited dust, TSP and PM10 during the audit period were viewed. Sampling from reports reviewed is undertaken in accordance with the stated methods. A review of the Annual Returns noted 2 separate non-compliances against condition M2.1 & M3.1. The first was reported as being due to a HVAS sample jar being shattered twice (03/06/2021 and 05/07/2021) at the laboratory prior to analysis. KEQ stated the action taken was to instruct laboratory /field technicians to take greater care when handling sample jars. The second was reported as a failure of HVAS equipment failing during periods of extreme rainstorms 	Ensure monitoring is undertaken in accordance with requirements of M2 conditions.	RESPONSE: KEQ acknowledges the finding, but considers no further actions are required.	



No	23 IEA Findings and KEQ Response - Environment Protection Licence (EPL 20611) Requirement	2023 IEA Assessment	2023 IEA Recommendation	2023 KEQ Response / Action
		(22/03/2021, 28/03/2021 and 03/04/2021) resulting in scheduled runs not being able to be undertaken. Make up runs were subsequently undertaken to make up for the missed runs.		
		Beyond the above noted issues, air quality monitoring is undertaken as per the methodology prescribed by the NSW Environment Protection Authority (EPA) in their document, Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales (2022) (Approved Methods).		
W8.1	To assess compliance with the noise limits for this premises attended noise monitoring must be undertaken in accordance with all noise condition and: a) During a period of normal quarry operations. b) at each one of the locations listed in the noise limits table of this licence c) Occur quarterly in the reporting period. d) Occur during each day period as defined in the NSW Noise Policy for Industry. <i>Note: Quarterly attended noise monitoring must be completed (unless otherwise agreed by the Planning Secretary) to determine whether the development is complying with the relevant conditions of this consent. The frequency of noise monitoring will be reviewed, upon request.</i>	A review of the Quarterly Monitoring Reports, prepared by EMM Consulting, across the audit period identified the methodology includes the requirements of this condition. Recorded Weather and Operating Conditions as reported stated monitoring was conducted in accordance with the stated criteria a), b) and d). A review of the Annual Returns noted 1 noncompliance for c) Noise monitoring not undertaken during the 26-08-2020 to 25-08-2021 reporting period. KEQ stated due to statistically wet year, monitoring under the required meteorological conditions proved difficult and therefore the last quarter monitoring was not conducted in time. KEQ stated in response to the failure to monitor they were amending the process of planning for quarterly monitoring to account for weather impacts. It is noted that the	Following the incident KEQ amended quarterly monitoring planning and the failure to conduct quarterly monitoring has not reoccurred. Therefore, no further action is recommended.	RESPONSE: KEQ acknowledges the finding, but considers no further actions are required.
R1.5	The Annual Return for the reporting period must be supplied to the EPA via eConnect EPA or by registered post not later than 60 days after the end of each reporting period or in the case of a transferring licence not later than 60 days after the date the transfer was granted (the 'due date').	 incident has not reoccurred during the audit period. A review of the submission dates of the Annual Returns noted that the Annual Return for the reporting period 26-08-21 to 25-08-2022 was submitted on 26-10-2022, 2 days after the due date of 24-10-2022. All other Annual returns for the audit period were noted to have been submitted within the required time period. 	Ensure Annual Returns are submitted within the 60 days and the due date as notified by the EPA.	RESPONSE: KEQ acknowledges the 2021/22 Annual Return was subject a late submission. KEQ has since implemented improved reporting processes to ensure submission of documents to external stakeholders is completed.
				STATUS: Completed – no furthe actions required.